4 -	93	1858
DES. SY	DATE	DAN. BY DA

SCREW						
NCE						
NC.						
SCOPE MOUNT SCREW						

DO NOT SCALE THIS DRAWING: WORK TO FIGURES UNLESS OTHERWISE NOTED.
TOLERANCES ON DECIMAL DIMENSIONS ARE:

TOLERANCES ON DECIMAL DIMENSIONS ARE:

1 PLACE (.1) — TOLERANCE ± .015

2 PLACE (.01) — TOLERANCE ± .010

3 PLACE (.001) — TOLERANCE ± .009

8 ON FRACTIONAL DIMENSIONS ± 1/44

9 ON ANGULAR DIMENSIONS ± 00° – 30°

FINISMES ARE DESIGNATED BY ROOT MEAN
SQUARE (R.M.S.) MICRO-INCH ROUGHNESS
VALUES AND ARE THE MAXIMUM ROUGHNESS

ACCEPTABLE. UNLESS OTHERWISE SPECIFIED.
FINISH ROUGHNESS TO BE 120 OR BETTER.

RECOMMENDED MATERIAL AND HEAT TREAT
MATERIAL VEG DORS SPEC

HEAT TREAT_____HARDNESS_____

COLOR_

HEAT TREAT AND COLOR TO BE DONE BY REMINGTON

THIS DRAWING OR INFORMATION IS PROPRIETARY INFORMATION TO THE REMINGTON ARMS COMPANY, INC.

NO. 5-40 SOCKET HEAD CAP SCREW 1/4"LENGTH 2 REQ'D. PER ASSEMBLY

ALTERATIONS					
ALT.	WAS	REF.	97	DATE	
		ļ			
			-		

FORD TPA 664, 200 H.H.S. 10 (152)