TITLE HAGAZINE AT THE SUPERSEDES REPERENCE REMINGTON ARMS CO. INC. ILIOM RESEARCH DIV. PART USE				DO NOT SCALE THIS DRAWING: WORK TO FIGURES UNLESS OTHERWISE NOTED. TOLERANCES ON DECIMAL DIMENSIONS ARE: 1 PLACE (.1) — TOLERANCE ± .018 2 PLACE (.01) — TOLERANCE ± .010 3 PLACE (.001) — TOLERANCE ± .008 5 ON FRACTIONAL DIMENSIONS ± 1/64 6 ON ANGULAR DIMENSIONS ± 1/64 6 ON ANGULAR DIMENSIONS ± 00°—30' FINISHES ARE DESIGNATED BY ROOT MEAN SQUARE (R. M. S.) MICRO-INCH ROUGHNESS VALUES AND ARE THE MAXIMUM ROUGHNESS ACCEPTABLE UNLESS OTHERWISE SPECIFIED. FINISH ROUGHNESS TO BE 100 DETTER.	MATERIAL MATERIAL HEAT TREAT HARDNESS COLOR HEAT TREAT AND COLOR TO BE DONE BY REMINGTON
NBAZ	CATCA	PINOT PIN		THIS DRAWING OR INFORMATION IS PROPRIETARY INFORMATION TO THE REMINGTON ARMS COMPANY, INC.	
				Deadar 1/2 5/2"	P D
				PREMASE 16 x 5/8"	Roce-AN
				PLRCHASE 16 x 5/8"	Roce-An
				RECHASE 16 x 5/8"	Roce-AN
ALT	WAB	OCF.	EV PAYS	RECHASE 16 x 5/8"	Roce-An

PORD TPA 86V. 200 11.0.0. 10 103+