

A-17676-V1		RESEARCH & DEV. DEPT.	
TITLE PIN		SCALE	SUPERSEDES REFERENCE A-17676-N 3-2-50
DES. BY DATE	CHK. BY DATE	APP. BY DATE	FOR DETAILS SEE PROCESS RECORD
23 6/30/65	PN 6-30-65	SM 6/1/65	
MODEL	PART USE	QUAN.	SEE
514-P	EJECTOR PIN		
514-P	TRIGGER PIN		
514-P	EJECTOR PIN		
514-P	TRIGGER PIN		
721	EJECTOR PIN		
722	" "		
725	" "		
401B	" "		
58	BOET REYUAN PLUNGER CROSS PIN		
700 E	EJECTOR PIN		
700 E	" "		
1P-100	" "		
600	" "		
783	" " 22-250 REM		
788	" " 222 REM.		
700AR	EJECTOR PIN		P.L.
660	EJECTOR PIN		P.L.
26	ADD USE	6773	EA 3/13/62
25	ADD USE 660	6658	FP 9/5/66
24	ADDED USE	6479	DD 3-14-66
23	ADDED 222 R.	6276	PN 7/23/65
22	ADDED 22-250	6276	PN 7/23/65
21	REMOVED SHEAR PROOF SPRG	6257	PN 7/23/65
20	REDRAWN	06234	23 6/30/65
ALT.	WAS	REFERENCE	BY DATE
ALTERATIONS			
TFA-3 REV. 1			

UNLESS OTHERWISE NOTED, TOLERANCES
ON DECIMAL DIMENSIONS ARE $\pm .005$
& ON FRACTIONAL DIMENSIONS $\pm \frac{1}{64}$
& ON ANGULAR DIMENSIONS $\pm 00^\circ 30'$
FINISHES ARE DESIGNATED BY ROOT MEAN
SQUARE (R.M.S.) MICRO-INCH ROUGHNESS
VALUES AND ARE THE MAXIMUM ROUGH-
NESS ACCEPTABLE, UNLESS OTHERWISE
SPECIFIED. FINISH ROUGHNESS TO BE
125 OR BETTER.

188	EJECTOR PIN 308 WIN.	
788	" " 243 WIN.	
788	" " 6MM REM.	
788	" " 308 WIN.	
"	" " 6MM REM	
28	POLICE MAG. EXT. KIT	FRONT SWIVEL SCREW PIN (M/B70)
29	28	
30	29	
31	1100	RETURN PLUNGER RETAINING PIN 12-16-20 GA.

DRIV LOC PIN

TYPE "C"

NOMINAL DIA. $-.078^{+0.078}_{-0.077}$ EXPANDED DIA. $-.085^{+0.085}_{-0.083}$

LENGTH $-\frac{3}{8} \pm .005$

NOT HEAT TREATED

NOT PLATED



.025 X 45° CHAMFER

30

26 27 28 31

A-17676-V1