

4.5° CHAMFER

RECOMMENDED MATERIAL AND HEAT TREAT

MATERIAL 9151-52100
 HEAT TREAT
 HARDNESS R45N 93-98
 COLOR BLACK OXIDE
~~NO SCALING OR MARKING BY OTHERS~~

B-17022

21
 22
 26 25

700BDL	FIRING PIN CROSS PIN	C26335
700ADL	FIRING PIN CROSS PIN	P.L.
40XCF	FIRING PIN CROSS PIN	P.L.
413	FIRING PIN CROSS PIN	P.L.
412A	FIRING PIN CROSS PIN	P.L.
412	FIRING PIN CROSS PIN	P.L.
725	FIRING PIN CROSS PIN	P.L.
411-C	FIRING PIN CROSS PIN	P.L.
411-B	FIRING PIN CROSS PIN	22555
40-X	FIRING PIN CROSS PIN	22555
722	FIRING PIN CROSS PIN	Y22040
721	FIRING PIN CROSS PIN	Y22040

MODEL	PART USE	QUAN.	SEC.
DES'D BY DATE	DRAWN BY DATE	CHECK BY DATE	APPR. BY DATE
	G. REED 5-16-62	6-11-62	WLB/12/62
TITLE PIN			
NUMBER	SCALE	SUPERSEDED - REFERENCE	
B-17022	5:1	A-17022	
REMINGTON ARMS CO. INC. RESEARCH & DEV. DEPT.			