C-93653

THIS DRAWING OR INFORMATION IS PROPRIETARY INFORMATION TO THE REMINGTON ARMS COMPANY, INC.

DO NOT SCALE THIS DRAWING. WORK TO FIGURES UNLESS OTHERWISE NOTED.
TOLERANCES ON DECIMAL DIMENSIONS ARE:
1 PLACE (.X) - TOLERANCE ± .05
2 PLACE (.XX) - TOLERANCE ± .005
3 PLACE (.XXX) - TOLERANCE ± .005
& ON FRACTIONAL DIMENSIONS ± 1/64
& ON ANGULAR DIMENSIONS ± 00° 30'
FINISHES AND DESIGNATED BY ROUGH GRAIN SQUARE SMALL MICRO-INCH ROUGHNESS VALUES AND ARE THE AVERAGE ROUGHNESS ACCEPTABLE UNLESS OTHERWISE SPECIFIED.
FINISH ROUGHNESS TO BE 32 OR BETTER.

RECOMMENDED MATERIAL AND HEAT TREAT
MATERIAL STEEL-VENDOR'S SPEC
HEAT TREAT
HARDNESS
COLOR BLACK OXIDE
HEAT TREAT AND COLOR TO BE DONE BY REMINGTON

ALTERATIONS

ALT.	DIS	DATE	BY	DATE



NBAR	93653	TRIG. PULL ADJ. SCREW
MODEL	PART NO.	PART USE
	MC 8-21-86	FEW 3-13-86
TITLE SCREW		
C-93653	10:1	REMINGTON ARMS CO. INC. ILION NEW YORK

CV FILENAME - REG. JFY.NBAR.TRIG-PULL-ADJ-SCREW