

MOH. 7600

MODEL	MOHAWK 600	308 Win.	6MM Rem.	222 Rem.	243 Win.		
BARREL	Round tapered to breech and crowned at muzzle. Black color alloy steel.				medium lustre.	Remington specification	
Bedding	No requirement.						
Barrel Bracket	Elevated type						
Length (Nominal)	18 1/2"						
Diameter (O.D.)	Mag num size						
Bore (in.)		.300 min. .302 max.	.237 min. .238 max.	.219 min. .220 max.	.237 min. .238 max.		
Groove (in.) (6)		.308 min. .310 max.	.243 min. .244 max.	.2240 min. .2250 max.	.243 min. .244 max.		
Twist (R. H.) 1 Turn in		10 inches	9 1/8 inches	14 inches	9 1/8 inches		
Markings	See MARKINGS -- Barrel						
BOLT (Final Assembly)	Includes Bolt Assembly, Firing Pin Assembly.						
Bolt Body	Bright steel						
Bolt Plug	Black color						
Bolt Handle	Bright steel color. Forward "S" shape with oval "half ball".				Serrated on bottom of half ball.		
Firing Pin Head	Black color						
Markings	Serial number on bottom of bolt. See MARKINGS-- Bolt (last four (4) numbers) Use "shrouded" bolt plug.						
BOLT STOP	Located in left rear of "bolt track" in receiver.				Use narrow tool to push down for release.		

5-3-76
REVISED 7-23-73

ILION RESEARCH DIVISION JFF:bmg
REMINGTON STANDARDS - ARMS

SHEET 5 of 7

MODEL	MOHAWK 600	308 Win.	6MM Rem.	222 Rem.	243 Win.
PACKAGING	Full length.	Exposed metal	parts coated with rust preventive.	Bolt packaged out of rifle.	
Accessories					
Literature	Instruction Folder - RD				
Single Shipper	Single piece corrugated sheet, Added fillers for rifle support. Marbleized color with red and black artwork. Lid taped to close.				
Multiple Shipper	Sleeve or full carton of corrugated material.				
Label	Model, serial number, caliber, packers code on label.				
Markings	Name and address of addressee, with copy of shipping ticket, return address.				
(2) Shipping Weight					
1 Gun	10 lbs.				
2 Guns	18 lbs.				
3 Guns	27 lbs.				
5 Guns	45 lbs.				
Export	Same as domestic except: Legal or actual weight on label.				
PROOF TEST (REP)	Fire one (1) standard proof cartridge in each gun. For location of marking (REP) see MARKINGS- Barrel. For bolt proof - see Markins - Bolt.				
RECEIVER	Cylindrical alloy steel, black color, medium lustre. Screw fitted to barrel and barrel bracket (solid frame.)				
Sighting	Drilled and tapped (5 holes) for receiver sight and telescope mount. Fitted with receiver plug screws.				
Gas Escape	One (1) hole - right side.				
Length	Standard				
Markings	See MARKINGS - Receiver.				
(1) RIB (and Spacer)	Supports rear sight. Striated on top surface. Attached to barrel with two (2) rear sight screws. Material Nylon (Rib) Metal (Spacer) Color - Black				
(1) Added : Ref. Design change 7-9-73.					
(2) Revised shipping weights. Per warehouse.					

