

P.I. NO GUN EXAMINATION REPORT NUMBER: 624

MODEL: 700 BDL

GENERAL CONDITION: GOOD

R #: 01873

OUTSIDE WORK: SCOPE SCREWS REMOVED

DATE: 12-28-81

FIRED AMMO TYPE: NOT KNOWN

FROM: POOR TOM'S
GUN SHOP
RD 4 MIDLINE RD.
AMSTER DAM NY 12010

& CONDITION: _____

GUN #: 136317842

PROOF: REP INSP.: 108 TEST: 119

CODE: CB = 4-81

HEADING: OK

GA./CAL.: 7MM REM MAG

BREECH OPENING: OK

CHECKED BY: M HAROLD

RECOIL SHOULDERS: OK

APPROVED: GH 2/16/82

CHAMBER: OK

APPROVED: CB 2/10/82

TEST: _____

APPROVED: GH 2/16/82

COMPONENT CONDITION: (Damaged, Broken, Old Style)

APPROVED: GH 2/16/82

SLIGHT DENTS IN STOCK

COMPLAINT: RIFLE GOES OFF UPON RELEASING
SAFETY PERIODICALLY

INCIDENT: _____

COMMENTS:

- Unable to duplicate customer complaint
- OK on Trickle test
- .019 bear engagement
- .0135 bear lift - full safe
- Trigger Pull 4 1/2*

4.5

RECEIVING and ESTIMATE REPORT

ORDER # 01873

2-25-81

1-15-82

WY

CHARGE

MAR

22

POOR Tom's GUN SHOP

RD # 4 MIDLINE RD, AMSTERDAM, N.Y. 12010

GRADE 700 7mm MAG

SERIAL NO. BG317842

DATE

CODE

CB

BDL

GRADE CODE

4-81

ENTER REPAIR ONLY

REPAIR CHG.

81-40

INS.

PARCEL POST

CONDITION (New) (Slightly worn) (Very worn) (Misused) (Gauge)

TOTAL

MR'S COMPLAINT

fire when safe removed

AULT

Met all tests by P.F.C. found no faults

GALLERY REPORT

DEPART CODE

Trigger assembly

Emm

D.W.H.

(Clean) (Fest) (Farger)

Repairman

S.P.P.

MAR 25 1982

FROM THE DESK OF

Poor Tom's Gun Shop

YON SWINARSKI

RD#4 MIDLINE RD.

AMSTERDAM, N.Y. 12010

12/11/81

Remington

Dear Sir

Please check enclosed Rem 700

BOL 7mm mag # B6317842

goes off upon releasing
safety periodically

Thanks

Tom S.

24, 1982

7mm Rem. Mag.
turned to us
safety, period-

1981, has
at it contained
al inspection
ad all our neces-

i, and it was
fter it originally
is stock contained
re found the head-
al.

not duplicate the
and dimensions were
sent. Also, factory
indicating no al-
my. Trigger pull

. cannot accept
any liability or responsibility for the incidents. It is possible
that while the safety lever was being moved from the "safe" to the
"fire" position, the trigger was inadvertently contacted. When the
safety lever reached the "fire" position, the gun then discharged - as
it is designed to do - because the trigger was being pulled with the
gun no longer on "safe".

Hold for Reply
R-01823

February 24, 1982

Poor Tom's Gun Shop
Mr. Tom Swinarski
R.D. #4, Midline Rd.
Amsterdam, New York 12010

Dear Mr. Swinarski:

Examination has been completed on the Model 700 BDL 7mm Rem. Mag. caliber rifle, serial number B6317842, which you returned to us because it allegedly "goes off upon releasing the safety, periodically".

The returned firearm, which was produced in April of 1981, has been examined by our firearms experts who report that it contained our high-pressure proof test, gallery test, and final inspection stampings, indicating that it had successfully passed all our necessary tests prior to shipment.

The general condition of the gun appeared to be good, and it was noted that the scope base screws had been removed after it originally left our factory. In addition, it was noted that the stock contained slight dents. In going over the individual parts, we found the headspace, recoil shoulders, and chamber all to be normal.

Examination of the rifle and trigger assembly could not duplicate the condition that was reported. All parts tolerances and dimensions were found to be normal, including sear-connector engagement. Also, factory seals were intact on the trigger adjusting screws, indicating no alterations were made on the trigger outside our company. Trigger pull was within our specifications at 4½ pounds.

Based on our findings, Remington Arms Company, Inc., cannot accept any liability or responsibility for the incidents. It is possible that while the safety lever was being moved from the "safe" to the "fire" position, the trigger was inadvertently contacted. When the safety lever reached the "fire" position, the gun then discharged - as it is designed to do - because the trigger was being pulled with the gun no longer on "safe".

DCC: ~~W. T. Bennett~~
F.T. Millener
K.D. Green
R.B. Sperling
~~D.J. Sanita~~
R-01873

~~Amis:~~
Please hold rifle for reply.
Thank you,
JAS

February 24, 1982

-2-

We trust that we have clarified the circumstances that could possibly have caused the accidental firings and, as a gesture of good-will, even though there is nothing wrong with the present trigger assembly, we can replace it with another assembly at no-charge, to insure that faith in the rifle is restored, or, the rifle can be returned as received. We will await the decision and reply.

Thank you for having afforded us this opportunity to examine the rifle and to be of service.

Sincerely,

J.A. Stekl, Supervisor
Firearms Product Service

JAS:tp

FROM THE DESK OF

★ Poor Tom's Gun Shop

TOM SWINARSKI

RD#4 MIDLINE RD.

AMSTERDAM, N.Y. 12010

Dear Sir:

*Please return
customer satisfied with
your findings*

*Thank
Tom S.*

*P
U
R*

MAR 1 1982

NY, INC.

ry 24, 1982

DL 7mm Rem. Mag.
returned to us
safety, period-

of 1981, has
that it contained
inal inspection
ssed all our neces-

ood, and it was
after it originally
the stock contained
, we found the head-
r-mal.

ld not duplicate the
s and dimensions were
ement. Also, factory
, indicating no al-
pany. Trigger pull

∴, cannot accept
any responsibility or compensation for the incidents. It is possible
that while the safety lever was being moved from the "safe" to the
"fire" position, the trigger was inadvertently contacted. When the
safety lever reached the "fire" position, the gun then discharged - as
it is designed to do - because the trigger was being pulled with the
gun no longer on "safe".