

SHOTGUN SHELL CATCHER - DEFLECTOR

| | | 201 S 45 45 C | 2 | | | | | | |
|--|--|---------------|----------------------------------|----------|----------|---------|--------|------------------------|--|
| Device for Catching or | 4,540) | Catch | 1 | 1 | | 1 | Damage | Accommodates | Protects |
| Deflecting Shells from | W. S. | Catch | Deflect | Function | Function | Safe to | to | Varied Bult Velocities | Nearby |
| Shotguns | Patented | Shells | Shells | Singles | Doubles | Shooter | Gun | Factory Ammunition | Shooter |
| Wire - (Jordan) | Yes | Yes | No | Yes | No | Yes . | Yes | Reasonably well | Reasonably well, but cannot be adjusted for variable ammunition. |
| Remington Controlled Orifice Device | No. Submitted to J.H. Lewis 5/26/66 - 1T-208. (Remington provides in European M/1100.) | Yes | Yes | Yes | Yes · | Yes | No | Yea | Yes |
| Nelson Deflector | Patent applied for. | No | Yes. If adjusted properly (50%). | Yes | Yes | Yes | No | No | No, if using All American or Federal Trap Load. |
| Fork Seymour | Yes | Yes | No | Yes 🛒 | No | No | Yes | Yes | Yes |
| | | | | | | | | | WELeek:sp 11-19-69 |