

B. Warehouse Evaluation - Pressure

	Avg.	Max.	Min.
T290 6mm 80 PSP	585	634	563
T310 6mm 80 PSP	578	604	559
U20F 6mm 80 PLHP (1)	597	667	551
T29U 6mm 80 PLHP	541	570	536
U20F 6mm 80 PSP	569	570	519

Remington Control - Pressure - 506 Max.

U23F 303 Brit 180 SPCL	387	388	355
------------------------	-----	-----	-----

Remington Control - Pressure - 443 Max.

T16H 8mm Mau 170 SPCL	329	360	337
T17H 8mm Mau 170 SPCL	328	365	332

Remington Control - Pressure - 363 Max.

6mm 80 PSP loaded with 303 Brit powder (46.7 Grains)	584	608	559
--	-----	-----	-----

303 Brit 180 SPCL loaded with 6mm Rem Powder (47.1 Grains)	356	369	332
--	-----	-----	-----

Hercules Powder Lot 3 - Vendor Test - M&V - 1.03%

6mm U20F	- 0.90% & 0.89%	as is from Warehouse
303 Brit U21F	- 1.02%	as is from Warehouse
8mm Mau T16H	- 0.99%	as is from Warehouse
6mm Rem T290	- 1.01	as is from Warehouse

(1) 1 Blown Primer - 667 - shot