

C. Humidified Storage - Pressure

	Avg.	Max.	Min.
6mm U20F 66 hrs/84% RH 5 major primer leaks M&V 1.16%	548	553	516
6mm T290 66 hrs/84% RH 1 blown primer M&V 1.25%	621	716	561
6mm U20F 66 hrs/20% RH 4 major primer leaks M&V 0.56%	626	638	574
6mm T290 66 hrs/20% RH 1 blown primer M&LV 0.57%	644	678	579
6mm Customer Complaint #11352 66 hr/84% R.H. M&V 1.04	589	587	557

D. Hot Storage - Pressure

	Avg.	Max.	Min.
303 Brit - 24 hrs/150° F	390	392	365
303 Brit - 4 days/150° F	377	411	388
Complaint #11,352 3 days/150° F	684	681	649
6mm Code T310 3 days/150° F	634	634	596
6mm Code U20F 3 days/150° F	630	664	557

E. Cold Storage - Pressure

	Avg.	Max.	Min.
6mm Code U20F 24 hrs/-20° F 1 Blown primer	602	671	520

F. F&C Shooting

Twenty rounds 6mm U20F in 7400 - 13 Minor primer leaks
 Twenty rounds 6mm U20F in 760 - 1 Blown primer
 3 Hard extractions