

TLW _____

Project No. 241095

Page 1 of 2

S.A.A.M.I. JAR-OFF, DROP & ROTATION TEST

Firecontrol No. _____ Firecontrol Type: _____ Date: 8-10-00

Dry Cycles/Rounds Completed: _____ Stock Type _____ Engagement at Start _____

Model No. 710 Serial No. 71001047 Engagement at End _____Trigger Pull at Start of Test (1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ 83

Average Trigger Pull at Start of Test: _____ Std. Dev. of Trigger Pull at Start of Test: _____

Trigger Pull at End of Test (1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____

Average Trigger Pull at End of Test: _____ Std. Dev. of Trigger Pull at End of Test: _____

Additional Notes and Comments

For additional details on the proper procedures to be used for this Test Procedure refer to:

ANSI / SAAMI Z299.5-1990

SAAMI Specifications for Standard Jar-Off Test:

Jar-Off Test: 12 inch drop - onto 1" thick 85 durameter (ShoreA) Rubber Matt
 Firearm ready to fire, Safe in "Fire" position, Fresh Primed Case in
 Chamber, Magazine loaded to capacity with Dummy Rounds.
 After each drop Fire Primed Case to verify firearm will still function.

12 inch drop (safety in "Fire" position) - one drop per orientation.

Comments

Barrel Horizontal, Bottom of Stock Down :	Pass	<input checked="" type="checkbox"/>	Fail	_____
Barrel Horizontal, Bottom of Stock Up :	Pass	<input checked="" type="checkbox"/>	Fail	_____
Barrel Horizontal, Left side of Stock Up :	Pass	<input checked="" type="checkbox"/>	Fail	_____
Barrel Horizontal, Right side of Stock Up :	Pass	<input checked="" type="checkbox"/>	Fail	_____
Barrel Vertical, Muzzle Up :	Pass	<input checked="" type="checkbox"/>	Fail	_____
Barrel Vertical, Muzzle Down :	Pass	<input checked="" type="checkbox"/>	Fail	_____

ET07322