

TLW 0300A0

Project No. 241095

S.A.A.M.I. JAR-OFF, DROP & ROTATION TEST

Gun
Firecontrol No. C28 Firecontrol Type: Std. Date: 12-10-00
Dry Cycles/Rounds Completed: _____ Stock Type Syn. Engagement at Start .0203
Model No. 710 Serial No. 71002565 Engagement at End _____
Trigger Pull at Start of Test (1) 4.25 (2) 3.75 (3) 4.0 (4) 3.75 (5) 4.0 (6) 4.0
Average Trigger Pull at Start of Test: 3.96 Std. Dev. of Trigger Pull at Start of Test: _____
Trigger Pull at End of Test (1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____
Average Trigger Pull at End of Test: _____ Std. Dev. of Trigger Pull at End of Test: _____

Tester Initials: JW + SW

Additional Notes and Comments

W/D Scope

83

For additional details on the proper procedures to be used for this Test Procedure refer to:

ANSI / SAAMI Z299.5-1990

SAAMI Specifications for Standard Jar-Off Test:

Jar-Off Test: 12 inch drop - onto 1" thick 85 durometer (Shore A) Rubber Matt
Firearm ready to fire, Safe in "Fire" position, Fresh Primed Case in Chamber, Magazine loaded to capacity with Dummy Rounds.
After each drop, fire Primed Case to verify firearm will still function.

12 inch drop (safety in "Fire" position) - one drop per orientation.

Note: for Firearms with the ISS system installed - The ISS will be set in the unlocked position for all six orientations of the Jar-Off Test

Orientation	ISS Unlocked	Comments
Barrel Vertical, Muzzle Up:	Pass _____ Fail _____	_____
Barrel Vertical, Muzzle Down:	Pass _____ Fail _____	_____
Barrel Horizontal, Left side of Stock Up:	Pass _____ Fail _____	_____
Barrel Horizontal, Right side of Stock Up:	Pass _____ Fail _____	_____
Barrel Horizontal, Bottom of Stock Up:	Pass _____ Fail _____	_____
Barrel Horizontal, Bottom of Stock Down:	Pass _____ Fail _____	_____

ET07688

TLW 0300AN

Project No. 241095

S.A.A.M.I. JAR-OFF, DROP & ROTATION TEST*SAAMI Specifications for Standard Drop Test:*

Drop Test: 48-inch drop - onto 1" thick 85 durometer (Shore A) Rubber Matt
Firearm not ready to fire, Safe in "Safe" position, Fresh Primed Case
in Chamber, Magazine loaded to capacity with Dummy Rounds.
After each drop Fire Primed Case to verify firearm will still function.

48 inch drop (safety in "Safe" position) - one drop per orientation.

Note: for Firearms with the ISS system installed - The Firearms will be set with the

ISS system in the unlocked position for all six orientations of the Drop Test

Orientation	ISS Unlocked	Comments
Barrel Vertical, Muzzle Up:	Pass _____ Fail _____	_____
Barrel Vertical, Muzzle Down:	Pass _____ Fail _____	_____
Barrel Horizontal, Left side of Stock Up:	Pass _____ Fail _____	_____
Barrel Horizontal, Right side of Stock Up:	Pass _____ Fail _____	_____
Barrel Horizontal, Bottom of Stock Up:	Pass _____ Fail _____	_____
Barrel Horizontal, Bottom of Stock Down:	Pass _____ Fail _____	_____

SAAMI Specifications for Standard Rotation Test:

Rotation Test: Rest Firearm on the Butt end and allow Firearm to fall
Drop - onto 1" thick 85 durometer (Shore A) Rubber Matt
Firearm not ready to fire, Safe in "Safe" position, Fresh Primed Case
in Chamber, Magazine loaded to capacity with Dummy Rounds.
After each drop Fire Primed Case to verify firearm will still function.

"Rotation Test" (safety in "Safe" position) - one drop per orientation.

Note: for Firearms with the ISS system installed - The Firearms will be set with the

ISS system in the unlocked position for both orientations of the Rotation Test.

Orientation	ISS Unlocked	Comments
Firearm Vertical, Drop so left side of Stock is Up:	Pass _____ Fail _____	_____
Firearm Vertical, Drop so right side of Stock is Up:	Pass _____ Fail _____	_____

Notes: (continue on back of sheet if necessary)

Tester's Initials _____

Page 2 of 2
Z101\DROPTEST_REV3.DOC

ET07689