

GUN# B-5
 SERIAL # 71001340
 CAL- 30.06 SPRG.

REMINGTON M/710 DAT PHASE II
 DAILY TEST DATA SHEET

TRACKING # TLW0010
 PROJECT #241095

NAME	DATE	TEST ACTIVITY	COMMENTS	ROUNDS AT START-	
				RDS. FIRED	TOTAL RDS.
JWI SW	9/11/00	HEADSPACE	MIN. +.002		
JWI SW	9/11/00	PROOF, HEADSPACE	PROOF, INSPECT, HEADSPACE MIN. +.003 + PROOF STAMP	1	1
JA/BL/OL	9-11-00	Trigger Pulls			
	9-11-00	Sear/Trigger Engagement/Sear Lift			
	9-11-00	Indents			
MRT	9-12-00	MAG-NAFLX BOLT HEAD - NO INDICATIONS			
PKR	10/04/00	Replaced Bolt body with one from B-6			
JA/BL	10-5-00	Replaced Engagement screw w/ 60° cone screw			
JA/BL	10-5-00	Set Engagement - .0211	Trigger Pull - 3.91		
JA/BL	10-6-00	Sagmi Drop, Jar-off and Rotation test completed			
		Final measurements see S.A.M.E. JAR-OFF, Drop & Rotation Test Form			

Note: Bolt Handle
 broken during Detailed
 Measurements. (J. Carson)
 Gun Hard to close. Tapped
 w/ hammer & handle broke
 off.

THIS SHEET IS TO ACCOMPANY THE FI

Forms

ET08272

S.A.A.M.I. JAR-OFF, DROP & ROTATION TEST

Firecontrol No. _____ Firecontrol Type: _____ Date: 10-5-00
 Dry Cycles/Rounds Completed: _____ Stock Type _____ Engagement at Start .0211
 Model No. 710 Serial No. 71001340 B-5 Engagement at End .0201
 Trigger Pull at Start of Test (1) 4.0 (2) 3.75 (3) 4.0 (4) 4.0 (5) 4.0 (6) 3.75
 Average Trigger Pull at Start of Test: 3.91 Std. Dev. of Trigger Pull at Start of Test: _____
 Trigger Pull at End of Test (1) 4.5 (2) 4.0 (3) 4.0 (4) 3.75 (5) 3.75 (6) 3.75
 Average Trigger Pull at End of Test: 3.95 Std. Dev. of Trigger Pull at End of Test: _____

Tester Initials: _____

Additional Notes and Comments

Note: measurements between Jar-off and rotation Test

engagement - .0192

Trigger pull - 4.0

Reset - none

Note: measurements after standard Rotation Test

engagement - .0197

Trigger pull - 3.91

Reset - none

For additional details on the proper procedures to be used for this Test Procedure refer to:

ANSI / SAAMI Z299.5-1990

SAAMI Specifications for Standard Jar-Off TestJar-Off Test:

12-inch drop - onto 1" thick 85 durometer (Shore A) Rubber Matt

Firearm ready to fire, Safe in "Fire" position, Fresh Primed Case in Chamber, Magazine loaded to capacity with Dummy Rounds.

After each drop, fire Primed Case to verify firearm will still function.

12 inch drop (safety in "Fire" position) - one drop per orientation.

Note: for Firearms with the ISS system installed - The ISS will be set in the unlocked position for all six orientations of the Jar-Off Test

<u>Orientation</u>	<u>ISS Unlocked</u>	<u>Comments</u>
Barrel Vertical, Muzzle Up:	Pass <input checked="" type="checkbox"/> Fail _____	
Barrel Vertical, Muzzle Down:	Pass <input checked="" type="checkbox"/> Fail _____	
Barrel Horizontal, Left side of Stock Up:	Pass <input checked="" type="checkbox"/> Fail _____	
Barrel Horizontal, Right side of Stock Up:	Pass <input checked="" type="checkbox"/> Fail _____	
Barrel Horizontal, Bottom of Stock Up:	Pass <input checked="" type="checkbox"/> Fail _____	
Barrel Horizontal, Bottom of Stock Down:	Pass <input checked="" type="checkbox"/> Fail _____	

S.A.A.M.I. JAR-OFF, DROP & ROTATION TEST

SAAMI Specifications for Standard Drop Test:

Drop Test: 48-inch drop - onto 1" thick 85 durometer (Shore A) Rubber Matt
Firearm not ready to fire, Safe in "Safe" position, Fresh Primed Case
in Chamber, Magazine loaded to capacity with Dummy Rounds.
After each drop Fire Primed Case to verify firearm will still function.

48 inch drop (safety in "Safe" position) - one drop per orientation.

Note: for Firearms with the ISS system installed - The Firearms will be set with the
ISS system in the unlocked position for all six orientations of the Drop Test

Orientation	ISS Unlocked	Comments
Barrel Vertical, Muzzle Up:	Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/>	
Barrel Vertical, Muzzle Down:	Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/>	
Barrel Horizontal, Left side of Stock Up:	Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/>	
Barrel Horizontal, Right side of Stock Up:	Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/>	
Barrel Horizontal, Bottom of Stock Up:	Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/>	
Barrel Horizontal, Bottom of Stock Down:	Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/>	

SAAMI Specifications for Standard Rotation Test:

Rotation Test: Rest Firearm on the Butt end and allow Firearm to fall
Drop onto 1" thick 85 durometer (Shore A) Rubber Matt
Firearm not ready to fire, Safe in "Safe" position, Fresh Primed Case
in Chamber, Magazine loaded to capacity with Dummy Rounds.
After each drop Fire Primed Case to verify firearm will still function.

"Rotation Test" (safety in "Safe" position) - one drop per orientation.

Note: for Firearms with the ISS system installed - The Firearms will be set with the
ISS system in the unlocked position for both orientations of the Rotation Test.

Orientation	ISS Unlocked	Comments
Firearm Vertical, Drop so left side of Stock is Up:	Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/>	
Firearm Vertical, Drop so right side of Stock is Up:	Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/>	

Notes: (continue on back of sheet if necessary)

Tester's Initials ITG