

TRACKING # TLW0010
PROJECT #241095

NAME	DATE	TEST ACTIVITY	COMMENTS	ROUNDS AT START-	
				RDS. FIRED	TOTAL RDS.
JWI/SW	9/11/00	HEADSPACE	MIN. +.001		
JWI/SW	9/11/00	PROOF, HEADSPACE	PROOF, INSPECT HEADSPACE MIN. +.003 + PROOF STAMP	1	1
JA/BL/JC	9-11-00	Trigger Pulls			
	9-11-00	Sear/Trigger Engagement/Sear Lift			
	9-11-00	Indents			
MRT	9-12-00	MAGNAPLEX BOLT HEADS - NO INDICATIONS			
JA/BL	10-5-00	Replaced Engagement Screw w/60° cone Screw			
JA/BL	10-5-00	Set Engagement +.0203 Trigger Pull 3.87			
JA/BL	10-6-00	S.A.A.M.I. Drop, JAR-OFF and Rotation Test Completed			
		final measurements see S.A.A.M.I. JAR-OFF, Drop			
		Rotation Test Form			

THIS SHEET IS TO ACCOMPANY THE FIREARM AT ALL TIMES THROUGHOUT TESTING

Forms

BARBER - 5.22.06r0002450

19

ET08281

Confidential - ~~BARBER~~ ~~15-27-06-0001450~~ Order
Williams v. Remington

TLW 0319

Project No. 241095

S.A.A.M.I. JAR-OFF, DROP & ROTATION TEST

Firecontrol No. _____ Firecontrol Type: _____ Date: 10-5-00
 Dry Cycles/Rounds Completed: _____ Stock Type _____ Engagement at Start .0208
 Model No. 710 Serial No. 71001069 B-10 Engagement at End .0216
 Trigger Pull at Start of Test (1) 3.75 (2) 4.0 (3) 4.0 (4) 3.75 (5) 3.75 (6) 4.0
 Average Trigger Pull at Start of Test: 3.87 Std. Dev. of Trigger Pull at Start of Test: _____
 Trigger Pull at End of Test (1) 4.0 (2) 4.0 (3) 3.75 (4) 3.75 (5) 4.0 (6) 4.25
 Average Trigger Pull at End of Test: 3.95 Std. Dev. of Trigger Pull at End of Test: _____

Tester Initials: _____

Additional Notes and Comments

Note: measurements between Jar-off and rotation Test
 Engagement - .0199 Trigger Pull - 3.91 Reset - none 83
 Note: measurement after Standard Rotation test
 Engagement - .0202 Trigger Pull - 3.91 Reset - none

For additional details on the proper procedures to be used for this Test Procedure refer to:

ANSI / SAAMI Z299.5-1990

SAAMI Specifications for Standard Jar-Off Test:

Jar-Off Test: 12 inch drop - onto 1" thick 85 durometer (Shore A) Rubber Matt
 Firearm ready to fire. Safe in "Fire" position, Fresh Primed Case in
 Chamber, Magazine loaded to capacity with Dummy Rounds.
 After each drop, fire Primed Case to verify firearm will still function.

12 inch drop (safety in "Fire" position) - one drop per orientation.

Note: for Firearms with the ISS system installed - The ISS will be set in the unlocked
 position for all six orientations of the Jar-Off Test

Orientation	ISS Unlocked	Comments
Barrel Vertical, Muzzle Up:	Pass ☒ Fail _____	
Barrel Vertical, Muzzle Down:	Pass ☒ Fail _____	
Barrel Horizontal, Left side of Stock Up:	Pass ☒ Fail _____	
Barrel Horizontal, Right side of Stock Up:	Pass ☒ Fail _____	
Barrel Horizontal, Bottom of Stock Up:	Pass ☒ Fail _____	
Barrel Horizontal, Bottom of Stock Down:	Pass ☒ Fail _____	

ET08282

TLW 0319

Project No. 241095

S.A.A.M.I. JAR-OFF, DROP & ROTATION TEST*SAAMI Specifications for Standard Drop Test:*

Drop Test: 48-inch drop - onto 1" thick 85 durameter (Shore A) Rubber Matt
Firearm not ready to fire, Safe in "Safe" position, Fresh Primed Case
in Chamber, Magazine loaded to capacity with Dummy Rounds.
After each drop Fire Primed Case to verify firearm will still function.

48 inch drop (safety in "Safe" position) - one drop per orientation.

Note: for Firearms with the ISS system installed - The Firearms will be set with the
ISS system in the unlocked position for all six orientations of the Drop Test

Orientation	ISS Unlocked	Comments
Barrel Vertical, Muzzle Up:	Pass ☒ Fail ☐	
Barrel Vertical, Muzzle Down:	Pass ☒ Fail ☐	
Barrel Horizontal, Left side of Stock Up:	Pass ☒ Fail ☐	
Barrel Horizontal, Right side of Stock Up:	Pass ☒ Fail ☐	cracked insert
Barrel Horizontal, Bottom of Stock Up:	Pass ☒ Fail ☐	
Barrel Horizontal, Bottom of Stock Down:	Pass ☒ Fail ☐	

SAAMI Specifications for Standard Rotation Test:

Rotation Test: Rest Firearm on the Butt end and allow Firearm to fall
Drop - onto 1" thick 85 durameter (Shore A) Rubber Matt
Firearm not ready to fire, Safe in "Safe" position, Fresh Primed Case
in Chamber, Magazine loaded to capacity with Dummy Rounds.
After each drop Fire Primed Case to verify firearm will still function.

"Rotation Test" (safety in "Safe" position) - one drop per orientation.

Note: for Firearms with the ISS system installed - The Firearms will be set with the
ISS system in the unlocked position for both orientations of the Rotation Test.

Orientation	ISS Unlocked	Comments
Firearm Vertical, Drop so left side of Stock is Up:	Pass ☒ Fail ☐	
Firearm Vertical, Drop so right side of Stock is Up:	Pass ☒ Fail ☐	

Notes: (continue on back of sheet if necessary)

Tester's Initials JTC

Page 2 of 2
Z101NDROPTTEST_REV3.DOC

ET08283