

TLWJ300AT

MODEL 710 T&P POI RELATIVE TO POA BORE SIGHTING USING BUSHNELL SCOPE

GUN	SCOPE	AMMO	GROUP SIZE		POI RELATIVE TO POA	TOTAL DISTANCE (in.)
B-21	BUSHNELL	REM R30064 180GR	2.68	X	-2.49	
				Y	11.81	12.07
B-22	BUSHNELL	REM R30064 180GR	2.37	X	-7.25	
				Y	9.47	11.93
B-23	BUSHNELL	REM R30064 180GR	2.46	X	-8.52	
				Y	9.32	12.63
B-24	BUSHNELL	REM R30064 180GR	3.52	X	-16.11	
				Y	15.15	22.12
B-25	BUSHNELL	REM R30064 180GR	1.05	X	4.45	
				Y	-2.65	5.17
B-26	BUSHNELL	REM R30064 180GR	1.54	X	1.72	
				Y	17.22	17.30
B-27	BUSHNELL	REM R30064 180GR	2.34	X	-13.83	
				Y	9.50	16.78
B-28	BUSHNELL	REM R30064 180GR	2.62	X	-4.47	
				Y	12.49	13.26
B-29	BUSHNELL	REM R30064 180GR	1.89	X	3.50	
				Y	-2.28	4.17
B-30	BUSHNELL	REM R30064 180GR	2.387	X	-9.279	
				Y	9.978	13.63
					AVERAGE	12.9
					STD. DEV.	5.4

BARBER - 5.22.06r0002507

93

ET08338

Confidential - ~~Subsequent~~ - 5.22.06r0002507 Order
Williams v. Remington

PROJECT# 241095

TLW 0300AT

MODEL 710 T&P POI RELATIVE TO POA BORE SIGHTING USING BUSHNELL SCOPE

GUN	SCOPE	AMMO	GROUP SIZE	POI RELATIVE TO POA
B-21	BUSHNELL	REM R30064 180GR	2.682	X -2.489 Y 11.809
B-22	BUSHNELL	REM R30064 180GR	2.365	X -7.246 Y 9.473
B-23	BUSHNELL	REM R30064 180GR	2.463	X -8.52 Y 9.318
B-24	BUSHNELL	REM R30064 180GR	3.524	X -16.11 Y 15.153
B-25	BUSHNELL	REM R30064 180GR	1.047	X 4.446 Y -2.646
B-26	BUSHNELL	REM R30064 180GR	1.536	X 1.721 Y -17.219
B-27	BUSHNELL	REM R30064 180GR	2.338	X -13.83 Y 9.5
B-28	BUSHNELL	REM R30064 180GR	2.618	X -4.473 Y 12.487
B-29	BUSHNELL	REM R30064 180GR	1.886	X 3.497 Y -2.276
B-30	BUSHNELL	REM R30064 180GR	2.387	X -9.279 Y 9.978

ET08339