

PROJECT # 241995
BARBER 5:22:06r0002535
AMMO REMINGTON 30.06
180 GRAIN R30064

HEAT AND HUMIDITY TEST
GUN # C 23
SERIAL # 71001174

TRACKING # TLW 0300AI

AMMO REMINGTON 30.06 180 GRAIN R30064

LOT # K28GB3714

MALFUNCTIONS

MALFUNCTIONS

1 1
2 2
3 3
4 4
5 5 CYCLED SAFETY
6 6
7 7
8 8
9 9
10 10 CYCLED SAFETY
11 1
12 2
13 3
14 4
15 5 CYCLED SAFETY
16 6
17 7
18 8
19 9
20 10 FIRED 20 ROUNDS AT 100.4 DEGREE F. AND 89.6
21 1 HUMIDITY
22 2
23 3
24 4
25 5 CYCLED SAFETY
26 6
27 7
28 8
29 9
30 10 CYCLED SAFETY
31 1
32 2
33 3
34 4
35 5 CYCLED SAFETY
36 6
37 7
38 8
39 9
40 10 FIRED 20 ROUNDS AT 100.4 DEGREE F. AND 89.4
41 1 HUMIDITY
42 2
43 3
44 4
45 5 CYCLED SAFETY
46 6
47 7
48 8
49 9
50 10 CYCLED SAFETY

51 1
52 2
53 3
54 4
55 5 CYCLED SAFETY
56 6
57 7
58 8
59 9
60 10 FIRED 20 ROUNDS AT 100.4 DEGREE F. AND 89.6
61 1 HUMIDITY
62 2
63 3
64 4
65 5 CYCLED SAFETY
66 6
67 7
68 8
69 9
70 10 CYCLED SAFETY
71 1
72 2
73 3
74 4
75 5 CYCLED SAFETY
76 6
77 7
78 8
79 9
80 10 FIRED 20 ROUNDS AT 100.4 DEGREE F. AND 89.6
81 1 HUMIDITY
82 2
83 3
84 4
85 5 CYCLED SAFETY
86 6
87 7
88 8
89 9
90 10 CYCLED SAFETY
91 1
92 2
93 3
94 4
95 5 CYCLED SAFETY
96 6
97 7
98 8
99 9
100 10 FIRED 20 ROUNDS AT 100.4 DEGREE F. AND 89.8
HUMIDITY

83

ET08366

- # 1 PLACE GUN C 23 AND 100 ROUNDS AMMO IN ENVIRONMENTAL TEST CHAMBER FOR 14 HOURS AT 100.4 DEGREE F. AND 89.6 HUMIDITY.
- # 2 TOOK GUN C 23 AND 20 ROUNDS OF AMMO OUT OF ENVIRONMENTAL TEST CHAMBER TO THE SHOOTING ROOM AND SHOT 20 ROUNDS.
LOADING ONE ROUND IN CHAMBER AND FOUR ROUNDS IN MAGAZINE.
CYCLED SAFETY EVERY FIVE ROUNDS
PUT GUN C 23 BACK IN ENVIRONMENTAL TEST CHAMBER FOR 2 HOURS.
- # 3 AFTER 2 HOURS TOOK GUN C 23 AND 20 ROUNDS AMMO OUT OF ENVIRONMENTAL TEST CHAMBER TO SHOOTING ROOM AND SHOT 20 ROUNDS.
LOADING ONE ROUND IN CHAMBER AND FOUR ROUNDS IN MAGAZINE.
CYCLED SAFETY EVERY FIVE ROUNDS
PUT GUN C 23 BACK IN ENVIRONMENTAL TEST CHAMBER FOR 2 HOURS.
- # 4 AFTER 2 HOURS TOOK GUN C 23 AND 20 ROUNDS AMMO OUT OF ENVIRONMENTAL TEST CHAMBER TO SHOOTING ROOM AND SHOT 20 ROUNDS.
LOADING ONE ROUND IN CHAMBER AND FOUR ROUNDS IN MAGAZINE.
CYCLED SAFETY EVERY FIVE ROUNDS
PUT GUN C 23 BACK IN ENVIRONMENTAL TEST CHAMBER FOR 2 HOURS.
- # 5 AFTER 2 HOURS TOOK GUN C 23 AND 20 ROUNDS AMMO OUT OF ENVIRONMENTAL TEST CHAMBER TO SHOOTING ROOM AND SHOT 20 ROUNDS.
LOADING ONE ROUND IN CHAMBER AND FOUR ROUNDS IN MAGAZINE.
CYCLED SAFETY EVERY FIVE ROUNDS
PUT GUN C 23 BACK IN ENVIRONMENTAL TEST CHAMBER FOR 2 HOURS.
- # 6 AFTER 2 HOURS TOOK GUN C 23 AND 20 ROUNDS AMMO OUT OF ENVIRONMENTAL TEST CHAMBER TO SHOOTING ROOM AND SHOT 20 ROUNDS.
LOADING ONE ROUND IN CHAMBER AND FOUR ROUNDS IN MAGAZINE.
CYCLED SAFETY EVERY FIVE ROUNDS
- # 7 CLEANED AND INSPECTED OK STEVE WADE

83

CONFIDENTIAL

ET08367

DATE-12/4/00

SHOOTER-SW

Heat & Humidity Test

TLW0300AT

AMMO TYPE - 30.06 R30064 180 Gr.		LOT# - K38CB3714	
MALFUNCTIONS		MALFUNCTIONS	
1	1	51	3
2	2	52	4
3	3	53	1
4	4	54	2
5	1 ✓	55	3 ✓
6	2	56	4
7	3	57	1
8	4	58	2
9	1	59	3
10	2 ✓	60	4 ✓
11	3	61	1
12	4	62	2
13	1	63	3
14	2	64	4
15	3 ✓	65	1 ✓
16	4	66	2
17	1	67	3
18	2	68	4
19	3	69	1
20	4 ✓	70	2 ✓
21	1	71	3
22	2	72	4
23	3	73	1
24	4	74	2
25	1 ✓	75	3 ✓
26	2	76	4
27	3	77	1
28	4	78	2
29	1	79	3
30	2 ✓	80	4 ✓
31	3	81	1
32	4	82	2
33	1	83	3
34	2	84	4
35	3 ✓	85	1 ✓
36	4	86	2
37	1	87	3
38	2	88	4
39	3	89	1
40	4 ✓	90	2 ✓
41	1	91	3
42	2	92	4
43	3	93	1
44	4	94	2
45	1 ✓	95	3 ✓
46	2	96	4
47	3	97	1
48	4	98	2
49	1 ✓	99	3
50	2 ✓	100	4 ✓

ET08368