



REMINGTON ARMS COMPANY, INC.

SPORTING AMELIANUSTICHTANGETS-TRAPS ILION, NEW YORK 12227 TRAPSOR (313 SHAN)

The Sportster 4220 3, Time Tyler, Tr. 75711

June 9, 1981

Model 700 Rifle A6714070 Repair Order R-12970-700

Door Sir:

Г

Examination has been completed on the above Model 786, 22-250 caliber rifle, serial number A6714070, which allegedly fired when the belt is opened or closed.

Our experts thoroughly examined the rifle and trigger assembly and could not duplicate the incident you have described. All parts tolerances and dimensions were found to be normal, including east connector engagement. Also, factory seeks were intent on the trigger adjustment screw, indicating as alterations were made to the trigger outside of our Company.

Based on our findings, Resington ires Co., Inc., cannot accept any liability or responsibility for this incident. We can only assume that as the safety was pushed to the "fire" position, contact was made with the trigger. When the safety is in the "on safe" position, the sear is lifted off of the trigger connector and very little effort is required to pull the trigger reserverd unknowingly, thus taking the trigger out from under the sear. If the trigger is held in the reservard position while the safety lever is moved to the "fire" position, the sear having no trigger to rest on drops sway from the motch in the striker as soon as the disconnector is moved away by the safety lever, thus causing the striker to move forward and the gun to fire.

This happens so fast that the shooter does not realize he has pulled the trigger and he attributes the "accidential" firing to gun maifunction.