

Remington.**REMINGTON ARMS COMPANY, INC.**

SPORTING ARMS-AMMUNITION-TARGETS-TRAPS

ILION, NEW YORK 13357

TELEPHONE (315) 894-9961

February 26, 1985

Mr. William R. Weaver
Route 2, #7 Hidden Acres
Paris, Tennessee 38242

Dear Mr. Weaver:

Your letter of February 5, 1985 that was addressed to our Bridgeport, Connecticut facility, regarding the accidental discharge your brother experienced while unloading your Model 700 ADL 30-06 caliber rifle, serial number 6715549, has been forwarded to this office for handling.


We were indeed sorry to learn of the problem you related. The Model 700 ADL rifle should be unloaded as follows:

- 1) With muzzle pointed in a safe direction, move safety lever to the "off safe" position and raise bolt handle.
- 2) Move safety to "on safe" position and pull bolt rearward to extract round from chamber.
- 3) Move bolt forward until next cartridge is released from magazine and remove from action. It is not necessary to fully close the bolt.
- 4) Repeat #3 above until magazine is empty.

From the above, it can be seen that the entire unloading operation can be completed with the safety in the "on safe" position, except for removal of the chambered cartridge.

Thank you for your letter and for having afforded us this opportunity to clarify your area of concern and to be of service to you.

Sincerely,



J.A. Stekl, Supervisor
Product Service

JAS:tpg