

TLW 0010AU

Project No. 241095

EXTENDED ROTATION TEST

Gun
 Model No. B-27 Firecontrol Type: Standard Date: 9-29-00
 Dry Cycles/Rounds Completed: _____ Stock Type _____ Engagement at Start .0245
 Model No. 710 Serial No. 71001309 Engagement at End .0215
 Trigger Pull at Start of Test (1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____
 Average Trigger Pull at Start of Test: 4.87 Std. Dev. of Trigger Pull at Start of Test: _____
 Trigger Pull at End of Test (1) 4.5 (2) 4.5 (3) 4.75 (4) 4.75 (5) 4.5 (6) 5.0
 Average Trigger Pull at End of Test: 4.66 Std. Dev. of Trigger Pull at End of Test: _____

Tester Initials: SW/JW

Additional Notes and Comments

Gun with Scope

SAAMI Specifications for Standard Rotation Test do not apply to this test.

Extended Rotation Test: Rest Firearm on the Butt end and allow Firearm to fall
 Drop - onto Tile Floor backed by Concrete. NO RUBBER MATT
 Firearm not ready to fire, Safe in "Safe" position, Fresh Primed Case
 in Chamber, Magazine loaded to capacity with Dummy Rounds.
 After each drop Fire Primed Case to verify firearm will still function.

"Rotation Test" (safety in "Safe" position) - one drop per orientation.

Note: for Firearms with the ISS system installed - The Firearms will be set with the
 ISS system in the unlocked position for both orientations of the Rotation Test.

| Orientation | ISS Unlocked | Comments |
|--|---|----------|
| Firearm Vertical, Drop so left side of Stock is Up: | Pass <input checked="" type="checkbox"/> Fail _____ | _____ |
| Firearm Vertical, Drop so right side of Stock is Up: | Pass <input checked="" type="checkbox"/> Fail _____ | _____ |

Notes: (continue on back of sheet if necessary)

Tester's Initials _____