

GUN# B28 W/Scope
SERIAL # 71001311
CAL- 30.06 SPRG.

REMINGTON M/710 DAT PHASE II
DAILY TEST DATA SHEET

TRACKING # TLW0010
PROJECT #241095

NAME	DATE	TEST ACTIVITY	COMMENTS	ROUNDS AT START-	
				RDS. FIRED	TOTAL RDS.
JW/ SW	9/9/00	HEADSPACE	MIN. + .002		
JW/ SW	9/9/00	PROOF, HEADSPACE	PROOF, INSPECT, HEADSPACE MIN. + .002 + PROOF STAMP	1	1
JA/BL/JC	9/9/00	Trigger Pull			
JA/BL/JC	9/9/00	Sear/Trigger Engagement/Sear LIFT			
JC	9/9/00	Inspection			
JW/ SW	9-10-00	SAAMI DROP TEST	JAR OFF, DROP, ROTATION		
JA/BL/JW	9-11-00	Trigger Pull/Engagement	After SAAMI Drop (see TLW0010AR)		
JA/BL/JW	9-11-00	Inspection	Plastic insert cracked		
JW/ SW	9-12-00		Took plastic insert from gun 71001042 and installed in this one		
MRT	9-11-00	MAGNETIC BOLT	HEAD - NO INDICATION		
Jesse	9-11-00	Set Engagement	To .0189 Trigger Pull To 4 LBS		
JW/ SW	9-13-00	EXTENDED JAR OFF	6"-18"-24"-49", INSPECTED		
JW/ SW	9-14-00	TRIGGER PULL/ENGAGEMENT	AFTER EXTENDED JAR OFF		
JW/ SW	9-15-00	EXTENDED DROP TEST	BROKE ALL 4 SCOPE RAIL SCREWS ON 72" EXTENDED DROP TEST, BARREL HORIZONTAL, LEFT SIDE OF STOCK UP		
JW	9-26-00		REPLACED SCOPE RAIL SCREWS + SCOPE		
JW/ SW	9-28-00	EXTENDED DROP TEST	CONTINUED TEST @ 72" GUN FAILED ON BARREL HORIZONTAL, BOTTOM OF STOCK UP. SAFETY STILL ON - GUN FAILED FIRING PIN HEAD OVER ROSE SEAR, BENT FIRING PIN HEAD, CRACKED PLASTIC INSERT, FIRE CONTROL DROPPED DOWN FROM RECEIVER, BENT SCOPE - STOPPED TEST AS PER - Danny D. - Scott F. + Dale D.		

THIS SHEET IS TO ACCOMPANY THE FIREARM AT ALL TIMES THROUGHOUT TESTING

Forms

BARBER - 5.22.06 r0003112

Confidential - Subject: 522B6P003112e Order

ET18876

Williams v. Remington

TLW 0010 AU

Project No. 241095

EXTENDED DROP TESTING

Gun
 Firearm No. B-28 Firecontrol Type: Standard Date: 4/15/00
 Dry Cycles/Rounds Completed: _____ Stock Type Syn Engagement at Start 0209
 Model No. 710 Serial No. 71001311 Engagement at End _____
 Trigger Pull at Start of Test (1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____
 Average Trigger Pull at Start of Test: 4.0 Std. Dev. of Trigger Pull at Start of Test: _____
 Trigger Pull at End of Test (1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____
 Average Trigger Pull at End of Test: _____ Std. Dev. of Trigger Pull at End of Test: _____

Tester Initials: SW/JW

Additional Notes and Comments

Gun with scopeSpecifications for Extended Drop Test:

Extended Drop Test: 72 & 96-inch drop - onto 1" thick 85 durameter (Shore A Rubber Mat) Firearm ready to fire, Safe in "Safe" position, Fresh Primed Case in Chamber, Magazine loaded to capacity with Dummy Rounds. After each drop, fire Primed Case to verify firearm will still function.

all drops (safety in "Safe" position) - one drop per orientation.

Note for Firearms with the ISS system installed - The ISS will be set in the unlocked position for all six orientations of the Drop Test

72 INCH EXTENDED DROP TEST

<u>Orientation</u>	<u>ISS Unlocked</u>	<u>Comments</u>
Barrel Vertical, Muzzle Up:	Pass ☒ Fail _____	
Barrel Vertical, Muzzle Down:	Pass ☒ Fail _____	
Barrel Horizontal, Left side of Stock Up:	Pass ☒ Fail _____	Broken 4 rail mounting screws
Barrel Horizontal, Right side of Stock Up:	Pass ☒ Fail _____	Start 4/28/00
Barrel Horizontal, Bottom of Stock Up:	Pass _____ Fail ☒	SAFETY STILL ON - INSERT CRACKED
Barrel Horizontal, Bottom of Stock Down:	Pass _____ Fail _____	FIRING PIN HEAD BENT - BENT SCOPE GUN FIRED - FIRING PIN HEAD OVER ROSE SEAR - FIRE CONTROL DROPPED DOWN FROM RECEIVER STOPPED TEST ON THIS GUN

Page 1 of 2

Z101NDROPTST_REV3.DOC

ET18877