

TLW 0395

Project No. 241095

Page 1 of 2

JW

## S.A.A.M.I. JAR-OFF, DROP &amp; ROTATION TEST

Firecontrol No. \_\_\_\_\_ Firecontrol Type: Std. Date: 1-17-01Dry Cycles/Rounds Completed: \_\_\_\_\_ Stock Type Syn. Engagement at Start 0202Model No. 710 Serial No. 71002455 Engagement at End 0200Trigger Pull at Start of Test (1) 4.25 (2) 4.50 (3) 4.50 (4) 4.25 (5) 4.25 (6) 4.25Average Trigger Pull at Start of Test: 4.33 Std. Dev. of Trigger Pull at Start of Test: 83Trigger Pull at End of Test (1) 4.5 (2) 4.5 (3) 4.25 (4) 4.5 (5) 4.5 (6) 4.25Average Trigger Pull at End of Test: 4.42 Std. Dev. of Trigger Pull at End of Test: \_\_\_\_\_

Additional Notes and Comments

For additional details on the proper procedures to be used for this Test Procedure refer to:

ANSI / SAAMI Z299.5-1990

SAAMI Specifications for Standard Jar-Off Test:

Jar-Off Test: 12 inch drop - onto 1" thick 85 durometer (Shore A) Rubber Matt  
 Firearm ready to fire, Safe in "Fire" position, Fresh Primed Case in  
 Chamber, Magazine loaded to capacity with Dummy Rounds.  
 After each drop Fire Primed Case to verify firearm will still function.

12 inch drop (safety in "Fire" position) - one drop per orientation.

	Pass	Fail	Comments
Barrel Horizontal, Bottom of Stock Down :	✓		
Barrel Horizontal, Bottom of Stock Up :	✓		
Barrel Horizontal, Left side of Stock Up :	✓		
Barrel Horizontal, Right side of Stock Up :	✓		
Barrel Vertical, Muzzle Up :	✓		
Barrel Vertical, Muzzle Down :	✓		

ET19945

TLW 0395

Project No. 241095

Page 2 of 2

## S.A.A.M.I. JAR-OFF, DROP &amp; ROTATION TEST (cont'd)

## SAAMI Specifications for Standard Drop Test:

Drop Test: 48 inch drop - onto 1" thick 85 durameter (Shore A) Rubber Matt  
Firearm not ready to fire, Safe in "Safe" position, Fresh Primed Case  
in Chamber, Magazine loaded to capacity with Dummy Rounds.  
After each drop Fire Primed Case to verify firearm will still function.

48 inch drop (safety in "Safe" position) - one drop per orientation.

	Pass	Fail	Comments
Barrel Horizontal, Bottom of Stock Down :	Pass <input checked="" type="checkbox"/>	Fail <input type="checkbox"/>	
Barrel Horizontal, Bottom of Stock Up :	Pass <input checked="" type="checkbox"/>	Fail <input type="checkbox"/>	
Barrel Horizontal, Left side of Stock Up :	Pass <input checked="" type="checkbox"/>	Fail <input type="checkbox"/>	
Barrel Horizontal, Right side of Stock Up :	Pass <input checked="" type="checkbox"/>	Fail <input type="checkbox"/>	
Barrel Vertical, Muzzle Up :	Pass <input checked="" type="checkbox"/>	Fail <input type="checkbox"/>	
Barrel Vertical, Muzzle Down :	Pass <input checked="" type="checkbox"/>	Fail <input type="checkbox"/>	

## SAAMI Specifications for Standard Rotation Test:

Rotation Test: Rest Firearm on the Butt end and allow Firearm to Fall  
Drop - onto 1" thick 85 durameter (Shore A) Rubber Matt  
Firearm not ready to fire, Safe in "Safe" position, Fresh Primed Case  
in Chamber, Magazine loaded to capacity with Dummy Rounds.  
After each drop Fire Primed Case to verify firearm will still function.

"Rotation" (safety in "Safe" position) - one drop per orientation.

	Pass	Fail	Comments
Firearm Vertical, Drop so Left side of Stock is Up :	Pass <input checked="" type="checkbox"/>	Fail <input type="checkbox"/>	
Firearm Vertical, Drop so Right side of Stock is Up :	Pass <input checked="" type="checkbox"/>	Fail <input type="checkbox"/>	

Notes:

Tester Initials: JW + EP

ET19946