

New Action

C6225239

E 6374631

MODEL 700™ M24

Model 700 M24™

Action

Barrel Length

Capacity

Order No. 5716

*Includes 1 in chamber.

Remington®

CONTRACT # DAAA21-87-C-0086

GUN SERIAL # C6225239

OP. #	OP. NAME	READINGS	DATE	INITIAL
575 & 580	Assemble Action and Stock		7/9/92	RW
600	Proof		7/9/92	RW
607	Check Headspace		7/9/92	RW
610	Dis-assemble Gun		7/9/92	RW
612	Magnaflux Barrel Action			
	Magnaflux Bolt			
615	Rollmark Caliber			
617	Drill and Tap Sight Holes		7/9/92	RW
618	Polish Barrel			
620	Apply Coatings (Barrel Action)			
	Apply Coating (Bolt)			
625	Final Assembly A) Clean inside of Bolt Assembly			
	B) Inspect Rear Firing Pin Hole for Chamfer in Bolt Head			
	C) Inspect Ejector Hole for Chamfer			
	D) Oil Firing Pin Ass'y			
	E) Adjust Trigger Pull to Min Setting and Stake			

op. #	NAME	READINGS	DATE	INIT
	BARBER - M24 0011313			
625 cont.	F) Safety On Force			
	G) Safety Off Force			
	H) Trigger Pull Test & Retainability			
	I) Firing Pin Indent			
	J) Assemble Stock			
	K) Assemble Swivel Studs			
	L) Attach Front and Rear Sight Assemblies			
	M) Iron Sight Alignment			
	N) Detach Front & Rear Sights & place in numbered container			
	O) Attach Scope to Rifle			
	P) Detach & Attach Scope 20 Times			
640	Gallery Target & Test		7-28-92	A
	A) Time		"	A
	B) Malfunctions		"	A
	C) Pierced Primers		"	A
	D) Optical Clarity of Scope		"	A
645	Inspect for Live Ammo		7-28-92	A
655	Final Inspection			
	A) Headspace			
	B) Trigger Pull			
	C) Function			
660	Pack			

CENTROIDAL DISTANCE CALCULATIONS

FOR RIFLE # 06225239

29 JUL 1992

CENTROIDAL DISTANCES

0 TO 1	.30024
1 TO 2	.248497
1 TO 3	.62367
1 TO 4	.859745
1 TO 5	.0308058


54⁴ ----- FOR

THE AVERAGE X-COORDINATE FOR THIS RIFLE IS: -.0064
 THE AVERAGE Y-COORDINATE FOR THIS RIFLE IS: -.0008
 THE RESULTING AVERAGE POI RADIUS FOR THIS RIFLE IS: .0393243
 THE AMR FOR THIS RIFLE IS: 1.102

28 Jul 1992

FILE: /PATTERNING/CENTERFIRE_PATT/06225239

CENTERFIRE PATTERNS # 1



OF SHOTS- 10

IN CIR

1in = 1

2in = 5

3in = 6

HS= 1.588

VS= 4.154


GS= 4.292

PATTERN #	:	1	9	8
SHOTS (BEST OF)	:	10	9	8
MAXIMUM X	:	.812	.845	.752
MINIMUM X	:	-.776	-.743	-.619
MAXIMUM Y	:	1.952	1.707	1.651
MINIMUM Y	:	-2.203	-1.775	-1.562
CENTROID X	:	-.300	-.333	-.240
CENTROID Y	:	-.012	.233	.020
POA TO CENTROID in.	:	.300	.407	.241
MIN RADIUS	:	.354	.190	.305
MEAN RADIUS	:	1.254	1.138	1.021
MAX RADIUS	:	2.223	1.861	1.764
HORIZONTAL SPREAD	:	1.588	1.588	1.372
VERTICAL SPREAD	:	4.154	3.482	3.213
EXTREME SPREAD	:	4.292	3.515	3.224
NUMBER IN ONE INCH CIRCLE	=	1		
NUMBER IN TWO INCH CIRCLE	=	5		
NUMBER IN THREE INCH CIRCLE	=	6		

28 Jul 1992

FILE:/PATTERNING/CENTERFIRE_PATT/C6225239

CENTERFIRE PATTERNS # 2



OF SHOTS - 10

IN CIR

1 in - 2

2 in - 5

3 in = 8

HS= 2.575

VS= 2.663

GS= 3.094

CENTROID #

PATTERN #	:	10	9	8
SHOTS (BEST OF)	:	10	9	8
MAXIMUM X	:	1.429	.935	.988
MINIMUM X	:	-1.146	-.987	-.871
MAXIMUM Y	:	1.139	1.244	1.067
MINIMUM Y	:	-1.524	-1.419	-.842
CENTROID X	:	-.056	-.215	-.331
CENTROID Y	:	.023	-.082	.095
POA TO CENTROID in.	:	.060	.230	.345
MIN RADIUS	:	.395	.227	.194
MEAN RADIUS	:	1.096	1.001	.905
MAX RADIUS	:	1.713	1.699	1.263
HORIZONTAL SPREAD	:	2.575	1.922	1.859
VERTICAL SPREAD	:	2.663	2.663	1.989
EXTREME SPREAD	:	3.094	3.071	2.457
NUMBER IN ONE INCH CIRCLE	=		2	
NUMBER IN TWO INCH CIRCLE	=		5	
NUMBER IN THREE INCH CIRCLE	=		8	

28 Jul 1992

FILE:/PATTERNING/CENTERFIRE_PATT/06225239

CENTERFIRE PATTERNS # 3

POA

1in circle

2in circle

3in circle

CENTROID *

OF SHOTS- 10

IN CIR

1in = 0

2in = 4

3in = 8

HS= 3.071

VS= 2.416

GS= 3.315

PATTERN #

SHOTS (BEST OF)

MAXIMUM X

MINIMUM X

MAXIMUM Y

MINIMUM Y

CENTROID X

CENTROID Y

POA TO CENTROID in.

MIN RADIUS

MEAN RADIUS

MAX RADIUS

HORIZONTAL SPREAD

VERTICAL SPREAD

EXTREME SPREAD

NUMBER IN ONE INCH CIRCLE =

NUMBER IN TWO INCH CIRCLE =

NUMBER IN THREE INCH CIRCLE =

10

9

8

1.951

1.984

1.166

-1.120

-.904

-.656

1.283

1.322

1.371

-1.133

-1.094

-1.045

.140

-.076

-.324

-.454

-.493

-.542

.475

.499

.632

.542

.428

.388

1.213

1.083

.916

1.982

2.023

1.381

3.071

2.888

1.822

2.416

2.416

2.416

3.315

3.150

2.435

0

4

8


28 Jul 1932

FILE:/PATTERNING/CENTERFIRE_PATT/C6225239

CENTERFIRE PATTERNS

4

POA



OF SHOTS- 10

IN CIR

1in - 3

2in - 7

3in = 8

HS= 2.676

VS= 2.608

GS= 3.737

CENTROID *


PATTERN #	:	10	9	8
SHOTS (BEST OF)	:	10	9	8
MAXIMUM X	:	1.069	1.069	.883
MINIMUM X	:	-1.607	-1.489	-1.191
MAXIMUM Y	:	1.007	.829	.580
MINIMUM Y	:	-1.601	-.511	-.407
CENTROID X	:	.509	.391	.577
CENTROID Y	:	.279	.457	.353
POA TO CENTROID in.	:	.581	.601	.676
MIN RADIUS	:	.340	.425	.408
MEAN RADIUS	:	.931	.836	.690
MAX RADIUS	:	1.925	1.704	1.249
HORIZONTAL SPREAD	:	2.676	2.558	2.074
VERTICAL SPREAD	:	2.608	1.340	.987
EXTREME SPREAD	:	3.737	2.846	2.187
NUMBER IN ONE INCH CIRCLE	=		3	
NUMBER IN TWO INCH CIRCLE	=		7	
NUMBER IN THREE INCH CIRCLE	=		8	

28 Jul 1992

FILE: PATTERNING/CENTERFIRE_PATT/08225239

CENTERFIRE PATTERNS

5



OF SHOTS- 10

IN CIR

1 in = 4

2 in = 5

3 in = 7

HS= 1.564

VS= 3.875

GS= 3.884

PATTERN #

:

5

SHOTS (BEST OF)

:

10

9

8

MAXIMUM X

:

.968

.932

.853

MINIMUM X

:

-.596

-.632

-.562

MAXIMUM Y

:

2.056

2.027

1.829

MINIMUM Y

:

-1.819

-1.591

-1.263

CENTROID X

:

-.325

-.289

-.210

CENTROID Y

:

-.030

-.258

-.060

POA TO CENTROID in.:

.327

.388

.218

MIN RADIUS

:

.154

.182

.230

MEAN RADIUS

:

1.015

.889

.762

MAX RADIUS

:

2.082

2.084

1.913

HORIZONTAL SPREAD :

1.564

1.564

1.415

VERTICAL SPREAD :

3.875

3.618

3.092

EXTREME SPREAD :

3.884

3.621

3.115

NUMBER IN ONE INCH CIRCLE =

4

NUMBER IN TWO INCH CIRCLE =

5

NUMBER IN THREE INCH CIRCLE =

7

RD-6947-Rev 3

PAYMENT:

Mastercard / Visa (circle one)

Card #:

Exp. Date:

Signature:

RETURN:

☐ Clark Street Entrance☒ Via US Mail or UPS

(PLEASE PRINT CLEARLY)

FIREARMS DELIVERED TO PLANT

FILE N9 007080DATE 6/20/92

CUSTOMER NAME:

ADDRESS:

ZIP:

PHONE:

FIREARM

MODEL:

GAUGE:

SERIAL #

REMINGTON EMPLOYEE:

YES ☐NO ☒

EMPLOYEE #

DEPT. #

CHECK FOR AMMUNITION

CONDITION:

~~WOOD~~

GOOD

FAIR

POOR

FANCY

PLAIN

METAL

GOOD

FAIR

POOR

FANCY

PLAIN

BARREL

VT. RIB

PLAIN

DEER RSS

ACCESSORIES:

SCOPE:

YES

NO

(BRAND NAME/POWER)

SLING: YES

NO

SCOPE

GUN CASE:

YES

NO

(HARD - SOFT)

EXTRA BBL FOR GUN MENTIONED ABOVE:

OTHER (Note in this area items missing or added from orig. equipment)

CUSTOMER REQUEST:

SIGNATURE:

(Person delivering firearm to Plant)

DATE:

SIGNATURE:

(Security Officer)

DATE:

SIGNATURE:

(Firearm picked up by)

DATE:

Arm Service Copy

CENTROIDAL DISTANCE CALCULATIONS
FOR RIFLE # 6225239

CENTROIDAL DISTANCES

0 TO	1	.993419
1 TO	2	.286698
1 TO	3	.617768
1 TO	4	.375366
1 TO	5	.241448

+ <----POA
4
215
3

THE AVERAGE X-COORDINATE FOR THIS RIFLE IS: .532
THE AVERAGE Y-COORDINATE FOR THIS RIFLE IS: -.8804
THE RESULTING AVERAGE POI RADIUS FOR THIS RIFLE IS: 1.02865

THE AMR FOR THIS RIFLE IS: 1.012


11 Oct 1988

FILE:/PATTERNING/CENTERFIRE_PATT/6225239

CENTERFIRE PATTERNS

1

POA



OF SHOTS- 10

IN CIR

1 in - 1

2 in - 6

3 in - 10

HS- 2.199

VS- 1.962

GS- 2.494

PATTERN #	1	2	3
SHOTS (BEST OF)	10	9	8
MAXIMUM X	1.176	1.162	.840
MINIMUM X	-1.023	-1.037	-.892
MAXIMUM Y	1.371	.841	.787
MINIMUM Y	-.591	-.439	-.477
CENTROID X	.499	.513	.368
CENTROID Y	-.859	-1.011	-.957
POA TO CENTROID in.	.994	1.134	1.025
MIN RADIUS	.386	.250	.393
MEAN RADIUS	.923	.842	.807
MAX RADIUS	1.377	1.279	1.132
HORIZONTAL SPREAD	2.199	2.199	1.732
VERTICAL SPREAD	1.962	1.280	1.264
EXTREME SPREAD	2.494	2.494	2.090
NUMBER IN ONE INCH CIRCLE =	1		
NUMBER IN TWO INCH CIRCLE =	6		
NUMBER IN THREE INCH CIRCLE =	10		

11 Oct 1988


FILE:/PATTERNING-CENTERFIRE_PATT/83P5889

CENTERFIRE PATTERNS

2

POA

1 in circle



OF SHOTS- 10

IN CIR

1 in - 2

2 in - 3

3 in - 9

HS- 2.297

VS- 3.248

GS- 3.446

CENTROID

PATTERN #	:	2	9	8
SHOTS (BEST OF)	:	10	9	8
MAXIMUM X	:	.965	1.004	.910
MINIMUM X	:	-1.332	-1.293	-1.387
MAXIMUM Y	:	1.119	.883	.801
MINIMUM Y	:	-2.129	-1.360	-1.250
CENTROID X	:	.213	.174	.268
CENTROID Y	:	-.839	-.603	-.713
POA TO CENTROID in.	:	.866	.627	.762
MIN RADIUS	:	.329	.313	.400
MEAN RADIUS	:	1.066	.923	.879
MAX RADIUS	:	2.158	1.468	1.411
HORIZONTAL SPREAD	:	2.297	2.297	2.237
VERTICAL SPREAD	:	3.248	2.243	2.051
EXTREME SPREAD	:	3.446	2.427	2.427
NUMBER IN ONE INCH CIRCLE	=	2		
NUMBER IN TWO INCH CIRCLE	=	3		
NUMBER IN THREE INCH CIRCLE	=	9		

11 Oct 1988

FILE:/PATTERNING/CENTERFIRE_PATT 8225039

CENTERFIRE PATTERNS # 3

POA

1 in circle

2 in circle

3 in circle

CENTROID *

OF SHOTS - 10

IN CIR

1 in = 0

2 in = 4

3 in = 8

HS = 3.0008

VS = 3.574

GS = 4.671

PATTERN #	:	3		
SHOTS (BEST OF)	:	10	9	3
MAXIMUM X	:	1.383	1.260	1.076
MINIMUM X	:	-1.625	-1.471	-1.449
MAXIMUM Y	:	2.003	.798	.630
MINIMUM Y	:	-1.571	-1.349	-1.887
CENTROID X	:	.788	.634	.818
CENTROID Y	:	-1.405	-1.627	-1.459
POA TO CENTROID in.	:	1.611	1.747	1.672
MIN RADIUS	:	.645	.555	.613
MEAN RADIUS	:	1.270	1.143	.995
MAX RADIUS	:	2.434	1.996	1.495
HORIZONTAL SPREAD	:	3.008	2.731	2.525
VERTICAL SPREAD	:	3.574	2.147	1.517
EXTREME SPREAD	:	4.671	3.150	2.726
NUMBER IN ONE INCH CIRCLE	=		0	
NUMBER IN TWO INCH CIRCLE	=		4	
NUMBER IN THREE INCH CIRCLE	=		8	

11 Oct 1988

FILE:/PATTERNING/CENTERFIRE_PATT/6225239

CENTERFIRE PATTERNS

4

POA

1in circle

2in circle

3in circle

OF SHOTS - 10

IN CIR

1in - 1

2in - 4

3in = 8

HS= 2.947

VS= 2.522

GS= 3.147

CENTROID *

PATTERN #	:	4		
SHOTS (BEST OF)	:	10	9	8
MAXIMUM X	:	1.370	1.110	.932
MINIMUM X	:	-1.577	-1.425	-1.165
MAXIMUM Y	:	1.159	1.048	1.047
MINIMUM Y	:	-1.363	-1.474	-1.475
CENTROID X	:	.425	.273	.451
CENTROID Y	:	-.491	-.381	-.380
POA TO CENTROID in.	:	.650	.468	.590
MIN RADIUS	:	.173	.358	.258
MEAN RADIUS	:	1.113	1.037	.983
MAX RADIUS	:	1.695	1.554	1.508
HORIZONTAL SPREAD	:	2.947	2.535	2.097
VERTICAL SPREAD	:	2.522	2.522	2.522
EXTREME SPREAD	:	3.147	2.731	2.561
NUMBER IN ONE INCH CIRCLE	=		1	
NUMBER IN TWO INCH CIRCLE	=		4	
NUMBER IN THREE INCH CIRCLE	=		8	

11 Oct 1988

FILE:/PATTERNING/CENTERFIRE_PATT/6225239

CENTERFIRE PATTERNS

5

POA

1 in circle

2 in circle

3 in circle

OF SHOTS - 10

IN CIR

1 in - 4

2 in - 8

3 in - 10

HS - 1.845

VS - 2.090

GS - 2.695

CENTROID *

PATTERN #	5	9	8
SHOTS (BEST OF)	10	9	8
MAXIMUM X	.623	.487	.375
MINIMUM X	-1.222	-.672	-.611
MAXIMUM Y	1.202	1.117	.741
MINIMUM Y	-.888	-.973	-.834
CENTROID X	.735	.871	.810
CENTROID Y	-.808	-.723	-.862
POA TO CENTROID in.	1.092	1.132	1.183
MIN RADIUS	.197	.228	.107
MEAN RADIUS	.690	.594	.504
MAX RADIUS	1.441	1.218	.864
HORIZONTAL SPREAD	1.845	1.159	.986
VERTICAL SPREAD	2.090	2.090	1.575
EXTREME SPREAD	2.695	2.115	1.579
NUMBER IN ONE INCH CIRCLE =	4		
NUMBER IN TWO INCH CIRCLE =	8		
NUMBER IN THREE INCH CIRCLE =	10		

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50# ± .50#

3.00# ± .75#

4.00# ± 1.00#

SERIAL NO. C-6225739DATE 12 Sept. 88TESTER J. V. W.B.

	2.50# INITIAL	2.50# AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50#		COMMENTS
PULL #1	2.41	2.37	2.28	2.24	MIN. SETTING, NO AVG. OF 5 READINGS ACCEPT- ABLE LESS THAN 2#
PULL #2	2.41	2.35	2.18	2.27	
PULL #3	2.70	2.32	2.22	2.22	
PULL #4	2.49	2.28	2.24	2.18	
PULL #5	2.71	2.36	2.20	2.20	
TOTAL	12.72	11.68	11.12	11.11	
AVG.	2.544	2.336	2.26	2.22	

	3.00# INITIAL	3.00# AFTER 20 CYCLES		COMMENTS
PULL #1	3.26	3.10		
PULL #2	3.17	3.09		
PULL #3	3.07	3.13		
PULL #4	3.15	3.12		
PULL #5	3.20	3.14		
TOTAL	15.85	15.58		
AVG.	3.17	3.116		

	4.00# INITIAL	4.00# AFTER 20 CYCLES	MAX SETTING GREATER THAN 4#	RESET TO 4# FOR TARGET & ACCURACY
PULL #1	4.20	3.96		4.25
PULL #2	4.05	4.01		4.22
PULL #3	4.14	3.94		4.27
PULL #4	4.13	4.04		4.19
PULL #5	4.17	4.01		4.21
TOTAL	20.69	19.96		21.14
AVG.	4.14	3.99		4.23

M-24

CONTRACT # DAAA21-87-C-0086

GUN SERIAL # *C6225239*

OPERATION		DATE	INT
#	NAME		
575-580	ASSEMBLY	<i>4/</i>	<i>FB</i>
600	PROOF	<i>2/2/88</i>	<i>AW</i>
615	MAGNAFLUX BARREL	<i>2/18/88</i>	<i>PJC</i>
	MAGNAFLUX BOLT	<i>2/25/88</i>	<i>PJC</i>
620	COATING	<i>3/21/88</i>	<i>TJA</i>
625-630	FINAL ASSEMBLY		
635	TEST		
640	TARGET		
	FIRING PIN INDENT		
660	PACK		

J

Scope # 1172

M-24

CONTRACT # DAAA21-87-C-0086

GUN SERIAL # C6225239

OP. #	OP. NAME	READINGS	DATE	INITIAL
575 & 580	Assemble Action and stock			
600	Proof			
607	Check Headspace			
610	Dis-assemble gun			
612	Magnaflux Barrel Action			
	Magnaflux Bolt			
615	Rollmark Caliber			
617	Drill & Tap Sight Holes			
618	Polish Barrel			
620	Apply Coatings (Barrel Action)			
	Apply Coatings (Bolt)			
625	Final Assembly A) Clean inside of Bolt Assembly		9/12/88	RW
	B) Inspect Rear Firing Pin Hole for Chamfer in Bolt Head		9/12/88	RW
	C) Inspect Ejector Hole for Chamfer		9/12/88	RW

OVER

OP. #		READINGS	DATE	INITIAL
625 cont.	D) Oil Firing Pin Ass'y		9/12/88	RW
	E) Adjust Trigger Pull to Min. Setting and Stake		12 Sept 88	Sw u.B.
	F) Safety on Force	$5\frac{3}{4}$ $5\frac{3}{4}$ $5\frac{3}{4}$	12 Sept 88	J.V. u.B.
	G) Safety off Force	3 3 3	12 Sept 88	J.V. u.B.
	H) Trigger Pull Test & Retainability		12 Sept 88	J.V. u.B.
	I) Firing Pin Indent	.071 .0715 .071	12 Sept 88	J.V. u.B.
	J) Assemble Stock		9/15/88	RW
	K) Assemble Swivel Studs		10-12-88	YS
	L) Attach Front & Rear Sight Assemblies		9/15/88	RW
	M) Iron Sight Alignment		9/15/88	RW
	N) Detach Front & Rear Sights & place in numbered container		9/15/88	RW
	O) Attach Scope to Rifle		10/5/88	RW
	P) Detach & Attach Scope 20 times		10-5-88	YS
640	Gallery Target & Test	41 R 114 L	10/11/88	DT.
	A) Optical Clarity of Scope		10/11/88	JL
645	Inspect for Live Ammo		10/11/88	JL
655	Final Inspection		10-12-88	YS
	A) Headspace		10-14-88	YS
	B) Trigger Pull		10-12-88	YS
	C) Function		10-12-88	YS
660	Pack		10-20-88	JL

9

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80