

C6587576

MODEL 700™ M24

Model SMS™

Action

Barrel Length

Capacity

Order No. 5716

*Includes 1 in chamber.

Remington

BARBER - M24 0023018
Arms Services Repair & Estimate System

File Add Repair Estimate Repair Expedite Repair Inquiry Repair Tools CSR Tools Reports Table Maintenance System Maintenance Help

Repair Inquiry
Repair Number: **RE00143913**Serial: C6587576 Model M24 SWS Center Fire
Caliber: 7.62 NATO

Repairman:

Status:

Closed 4/1/2008 1:32:18 PM

Verify Repair

Address Information

Customer:

☒ Received From

Return To

☐ Received FromName: **HEADQUARTERS AND HEADQUARTERS CO**Name: **HEADQUARTERS AND HEADQUARTERS CO**Address 1: **2ND BN 9TH INF REG**Address 1: **2ND BN 9TH INF REG**Address 2: **UNIT #15101**

PO Box:

Address 2: **UNIT #15101**

PO Box:

City: **APD**City: **APD**State: **ICA**Zip Code: **96224**Country: **US**State: **ICA**Zip Code: **96224**Country: **US**

FFL:

Contact / Condition
Problems
Estimate
History / Status
Shipping / Billing
Contact Information
Phone: **NN**

Fax:

Email:

Comments:

Received Condition

Fair

Condition
Notes:CSR
Notes:
Accessories Received

Code	Desc	Qty
A007	With Stud	3
A045	Bi Pod	1
A057	Fit and Rear Sgt Base	1
D000	SCOPE AND SCOPE	1

Repair Search

Refresh

Close

maglet

4/2/2008

9:42 AM

NUM

Serial Number: **C6587576**
Model: **M24 SWS****RE00143913**

SNIPER WEAPON SYSTEM - UNIQUE STATISTICAL INFORMATION

FIREARM SERIAL NUMBER / DATASET NAME: C6587576.___0
FILE DATE AND TIME: 04/16/2008 14:00

THE FOLLOWING DATA IS ALL REPORTED IN UNITS OF INCHES

The Average X Centroid of the Five Target Set:	-0.103
The Average Y Centroid of the Five Target Set:	-0.134
The Average Point of Impact of the Five Target Set:	0.169
The Average Mean Radius of the Five Target Set:	0.875
The Distance from POA to Centroid Target #1:	0.224
The Distance from Centroid Target #2 to Centroid Target #1:	0.235
The Distance from Centroid Target #3 to Centroid Target #1:	0.220
The Distance from Centroid Target #4 to Centroid Target #1:	0.123
The Distance from Centroid Target #5 to Centroid Target #1:	0.058

BARBER - M24 0023020

SERIAL NUMBER: C6587576. __0

TARGET NUMBER: 1

FILE DATE: 04/16/2008

FILE TIME: 14:00

POINT#	X	Y
1:	1.681	0.194
2:	0.581	0.897
3:	0.080	0.202
4:	0.235	-0.390
5:	0.135	-0.244
6:	-0.011	-0.202
7:	-0.419	-0.850
8:	0.473	-1.957
9:	-1.466	0.071
10:	-1.923	0.133

X CENTROID: -0.063

Y CENTROID: -0.215

POA TO CENTROID: 0.224

HORZ SPREAD: 3.604

VERT SPREAD: 2.854

GROUP SPREAD: 3.605

MIN RADIUS: 0.054


MAX RADIUS: 1.892

MEAN RADIUS: 0.999

IN 1 IN DIAMETER: 4

IN 2 IN DIAMETER: 5

in 3 IN DIAMETER: 7



TARGET APPROX 1/2 SCALE

BARBER - M24 0023021

SERIAL NUMBER: C6587576.____0

TARGET NUMBER: 2

FILE DATE: 04/16/2008

FILE TIME: 14:00

X CENTROID: -0.210

Y CENTROID: -0.031

POA TO CENTROID: 0.212

HORZ SPREAD: 2.629

VERT SPREAD: 1.392

GROUP SPREAD: 2.639

MIN RADIUS: 0.344

MAX RADIUS: 1.392


MEAN RADIUS: 0.824

IN 1 IN DIAMETER: 3

IN 2 IN DIAMETER: 7

in 3 IN DIAMETER: 10

POINT#	X	Y
1:	1.097	-0.509
2:	0.626	-0.555
3:	0.003	-0.757
4:	0.068	-0.414
5:	-0.542	0.127
6:	-0.272	0.308
7:	0.188	0.635
8:	-0.658	0.571
9:	-1.080	0.562
10:	-1.532	-0.277



TARGET APPROX 1/2 SCALE

BARBER - M24 0023022

SERIAL NUMBER: C6587576. __ 0

TARGET NUMBER: 3

FILE DATE: 04/16/2008

FILE TIME: 14:00

POINT#	X	Y
1:	0.785	-0.767
2:	0.422	-0.431
3:	0.670	0.126
4:	0.580	0.401
5:	0.460	0.726
6:	0.033	-0.065
7:	-0.254	-0.053
8:	-0.770	0.110
9:	-0.991	0.601
10:	-1.313	-0.610

X CENTROID: -0.038

Y CENTROID: 0.004

POA TO CENTROID: 0.038

HORZ SPREAD: 2.098

VERT SPREAD: 1.493

GROUP SPREAD: 2.220

MIN RADIUS: 0.099


MAX RADIUS: 1.415

MEAN RADIUS: 0.769

IN 1 IN DIAMETER: 2

IN 2 IN DIAMETER: 7

in 3 IN DIAMETER: 10



TARGET APPROX 1/2 SCALE

BARBER - M24 0023023

SERIAL NUMBER: C6587576. __0

TARGET NUMBER: 4

FILE DATE: 04/16/2008

FILE TIME: 14:00

POINT#	X	Y
1:	0.699	-0.343
2:	0.329	-0.183
3:	0.614	0.112
4:	-0.102	-0.498
5:	-0.352	-0.787
6:	0.051	0.584
7:	-1.330	0.387
8:	-1.202	-0.045
9:	-1.161	0.940
10:	0.666	-1.896

X CENTROID: -0.179

Y CENTROID: -0.173

POA TO CENTROID: 0.249

HORZ SPREAD: 2.029

VERT SPREAD: 2.836

GROUP SPREAD: 3.374

MIN RADIUS: 0.334


MAX RADIUS: 1.919

MEAN RADIUS: 0.972

IN 1 IN DIAMETER: 1

IN 2 IN DIAMETER: 6

in 3 IN DIAMETER: 9




TARGET APPROX 1/2 SCALE

BARBER - M24 0023024

SERIAL NUMBER: C6587576. __0
 TARGET NUMBER: 5
 FILE DATE: 04/16/2008
 FILE TIME: 14:00

POINT#	X	Y
1:	0.372	-0.561
2:	0.437	-0.274
3:	-0.001	-0.577
4:	-0.848	-0.242
5:	-1.010	-0.658
6:	0.424	0.257
7:	0.319	0.382
8:	0.227	0.496
9:	0.088	0.660
10:	-0.236	-2.039

X CENTROID: -0.023
 Y CENTROID: -0.256
 POA TO CENTROID: 0.257
 HORZ SPREAD: 1.447
 VERT SPREAD: 2.699
 GROUP SPREAD: 2.718
 MIN RADIUS: 0.322
 MAX RADIUS: 1.796
 MEAN RADIUS: 0.809
 # IN 1 IN DIAMETER: 3
 # IN 2 IN DIAMETER: 8
 # in 3 IN DIAMETER: 9



TARGET APPROX 1/2 SCALE

M-24 INSPECTION CHECKLIST
CONTRACT #: DAAE-20-02-C-0149

R & E NUMBER 00143913SERIAL NUMBER C6587576LOG-IN DATE 4-1-08

OPERATION #	OPERATION NAME	DATE	INITIAL
500	DIS-ASSEMBLE GUN	4-3-08	L.P.D.
505	RE-BARREL	4-3-08	L.P.D.
560	ASSEMBLE	4-3-08	RTZ
600	PROOF	4-7-08	TRW
605	CHECK HEADSPACE	4-7-08	TRW
610	DIS-ASSEMBLE GUN	4-8-08	L.P.D.
612	MAGNAFLUX	4/9/08	ccw
510	DRILL AND TAP	4/9/08	Fm
615	ROLLMARK CALIBER	4-9-08	CW
618	ROTO-BLAST	4-9-08	DG
620	APPLY COATINGS	4-11-08	CW
625	FINAL ASSEMBLY	4-15-08	RTZ
640	FUNCTION TEST AND	PASS FAIL 4-16-08	TRW
650	TARGET	PASS FAIL 4-16-08	TRW
	MALFUNCTION	CORRECTION	
	MALFUNCTION	CORRECTION	
	MALFUNCTION	CORRECTION	
	MALFUNCTION	CORRECTION	
670	FINAL INSPECTION	4-16-08	RP
	A) HEADSPACE	PASS FAIL 4-17-08	TRW
	B) TRIGGER PULL	2.47 2.33 2.37 2.36 2.40 4-17-08	TRW
680	F) SAFETY ON FORCE	8.0 8.0 7.5 4-17-08	TRW
	G) SAFETY OFF FORCE	2.25 3.0 2.75 4-17-08	TRW
	I) FIRING PIN INDENT	.0205 .020 .020 4-17-08	TRW
690	PACK	12/18/08	Fm

Safe hits Stock

12-10-98

OK AC

Remington
REG. U.S. PAT. & TM. OFF.


VERY IMPORTANT:
 Instruction Book
 enclosed to assure
 safe use of this
 firearm.

MODEL 700™ M24

SERIAL NO.
 C6587576


ORDER NO.
 5716

MADE IN ILION, N.Y. U.S.A. Reg. U.S. Pat. & Tm. Off. Marca Registrada. Marque Deposee.



5716 C6587576

LPC



0 47700 25716 7

CONTRACT # DAAA21-87-C-0086

GUN SERIAL # C 6587576

OP. #	OP. NAME	READINGS	DATE	INIT
575 & 580	Assemble Action and Stock		10/22/90	Kel
600	Proof		10/22/90	Kel
607	Check Headspace		10/22/90	Kel
610	Dis-assemble Gun		10/22/90	Kel
612	Magnaflux Barrel Action		10/24/90	KR
	Magnaflux Bolt		10/24/90	KR
615	Rollmark Caliber		10/24/90	Ed
617	Drill and Tap Sight Holes		10/25/90	FB
618	Polish Barrel RB		10/26/90	WB
620	Apply Coatings (Barrel Action)		11/7/90	JA
	Apply Coating (Bolt)		11/7/90	JA
625	Final Assembly A) Clean inside of Bolt Assembly		11/7/90	KS
	B) Inspect Rear Firing Pin Hole for Chamfer in Bolt Head		11/7/90	KS
	C) Inspect Ejector Hole for Chamfer		11/7/90	KS
	D) Oil Firing Pin Ass'y		11/7/90	KS
	E) Adjust Trigger Pull to Min Setting and Stake		12/3/90	JA

OP. #	OP. NAME	READINGS			DATE	INIT
625 cont.	F) Safety On Force	5 1/2	5 1/2	5 1/2	12/4/90	WB
	G) Safety Off Force	2 1/2	2 1/2	2 1/2	12/4/90	WB
	H) Trigger Pull Test & Retainability				12/3/90	JL
	I) Firing Pin Indent	.021	.021	.021	12/4/90	WB
	J) Assemble Stock				12/3/90	KS
	K) Assemble Swivel Studs				12-10-90	928
	L) Attach Front and Rear Sight Assemblies				12/7/90	KS
	M) Iron Sight Alignment				12/7/90	KS
	N) Detach Front & Rear Sights & place in numbered container				12/7/90	KS
	O) Attach Scope to Rifle				12/7/90	KS
	P) Detach & Attach Scope 20 Times				12/7/90	KS
640	Gallery Target & Test				12/8/90	KS
	A) Time					KS
	B) Malfunctions					KS
	C) Pierced Primers					KS
	D) Optical Clarity of Scope					KS
645	Inspect for Live Ammo				12/8/90	122
655	Final Inspection					
	A) Headspace				12-10-90	928
	B) Trigger Pull	239	240	246	245	249
	C) Function				12-10-90	928
660	Pack				12/14/90	KS

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50# ± .50#

3.00# ± .75#

4.00# ± 1.00#

SERIAL NO. C6587576

DATE 12/3/90

TESTER JJ

	2.50# INITIAL	2.50# AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50#		COMMENTS
PULL #1	2.45	2.41	2.48	239	MIN. SETTING, NO AVG. OF 5 READINGS ACCEPT- ABLE LESS THAN 2#
PULL #2	2.48	2.49	2.46	240	
PULL #3	2.44	2.31	2.49	246	
PULL #4	2.45	2.39	2.50	245	
PULL #5	2.46	2.38	2.45	249	
TOTAL					
AVG.					

	3.00# INITIAL	3.00# AFTER 20 CYCLES		COMMENTS
PULL #1	3.44	3.30		
PULL #2	3.44	3.26		
PULL #3	3.50	3.23		
PULL #4	3.24	3.26		
PULL #5	2.27	3.31		
TOTAL				
AVG.				

	4.00# INITIAL	4.00# AFTER 20 CYCLES	MAX SETTING GREATER THAN 4#	RESET TO 4# FOR TARGET & ACCURACY
PULL #1	4.39	4.31		4.35
PULL #2	4.41	4.36		4.39
PULL #3	4.38	4.34		4.36
PULL #4	4.32	4.36		4.32
PULL #5	4.40	4.29		4.35
TOTAL				
AVG.				

CENTROIDAL DISTANCE CALCULATIONS
FOR RIFLE # C6587576
8 Dec 1990

CENTROIDAL DISTANCES

0 TO	1	.223379
1 TO	2	.310644
1 TO	3	.395081
1 TO	4	.284285
1 TO	5	.39036


1/2 <----POA
3

THE AVERAGE X-COORDINATE FOR THIS RIFLE IS: -.0506
THE AVERAGE Y-COORDINATE FOR THIS RIFLE IS: -.1566
THE RESULTING AVERAGE POI RADIUS FOR THIS RIFLE IS: .164572
THE AMR FOR THIS RIFLE IS: 1.174

8 Dec 1990

FILE:/PATTERNING/CENTERFIRE_PATT/C6587576

CENTERFIRE PATTERNS # 1



OF SHOTS- 10

IN CIR

1 in = 1

2 in = 3

3 in = 6

HS= 3.394

VS= 3.086

GS= 3.557

PATTERN #	1	2	3
SHOTS (BEST OF)	10	9	8
MAXIMUM X	1.884	1.733	1.468
MINIMUM X	-1.510	-1.661	-1.444
MAXIMUM Y	1.754	1.606	1.587
MINIMUM Y	-1.332	-0.829	-0.848
CENTROID X	-0.223	-0.072	-0.289
CENTROID Y	0.013	0.161	0.180
POA TO CENTROID in.	0.223	0.176	0.340
MIN RADIUS	0.423	0.327	0.471
MEAN RADIUS	1.269	1.197	1.103
MAX RADIUS	1.900	1.752	1.657
HORIZONTAL SPREAD	3.394	3.394	2.912
VERTICAL SPREAD	3.086	2.435	2.435
EXTREME SPREAD	3.557	3.418	3.033
NUMBER IN ONE INCH CIRCLE =	1		
NUMBER IN TWO INCH CIRCLE =	3		
NUMBER IN THREE INCH CIRCLE =	6		

8 Dec 1998

FILE:/PATTERNING/CENTERFIRE_PATT/C6587576

CENTERFIRE PATTERNS # 2

POA

1 in circle

2 in circle

3 in circle

OF SHOTS- 10

IN CIR

1 in = 0

2 in = 3

3 in = 8

HS= 2.565

VS= 2.791

GS= 2.934

CENTROID #

PATTERN #	:	2		
SHOTS (BEST OF)	:	10	9	8
MAXIMUM X	:	1.102	.939	.857
MINIMUM X	:	-1.463	-1.378	-1.460
MAXIMUM Y	:	1.292	1.189	.989
MINIMUM Y	:	-1.499	-1.602	-1.318
CENTROID X	:	.069	.232	.314
CENTROID Y	:	-.093	.010	.210
POA TO CENTROID in.	:	.116	.232	.377
MIN RADIUS	:	.607	.421	.339
MEAN RADIUS	:	1.164	1.052	.922
MAX RADIUS	:	1.730	1.731	1.505
HORIZONTAL SPREAD	:	2.565	2.317	2.317
VERTICAL SPREAD	:	2.791	2.791	2.307
EXTREME SPREAD	:	2.934	2.848	2.604
NUMBER IN ONE INCH CIRCLE	=		0	
NUMBER IN TWO INCH CIRCLE	=		3	
NUMBER IN THREE INCH CIRCLE	=		8	

8 Dec 1998

FILE:/PATTERNING/CENTERFIRE_PATT/C6587576

CENTERFIRE PATTERNS # 3

POA

1 in circle

2 in circle

3 in circle

CENTROID *

OF SHOTS - 10

IN CIR

1 in = 1

2 in = 6

3 in = 9

HS = 3.799

VS = 1.646

GS = 3.802

PATTERN #	:	3		
SHOTS (BEST OF)	:	10	9	8
MAXIMUM X	:	1.257	.975	1.078
MINIMUM X	:	-2.542	-.776	-.673
MAXIMUM Y	:	.877	.876	.960
MINIMUM Y	:	-.769	-.770	-.686
CENTROID X	:	-.231	.051	-.052
CENTROID Y	:	-.382	-.381	-.465
POA TO CENTROID in.	:	.447	.384	.468
MIN RADIUS	:	.396	.476	.421
MEAN RADIUS	:	.997	.800	.743
MAX RADIUS	:	2.542	1.170	1.172
HORIZONTAL SPREAD	:	3.799	1.751	1.751
VERTICAL SPREAD	:	1.646	1.646	1.646
EXTREME SPREAD	:	3.802	1.899	1.899
NUMBER IN ONE INCH CIRCLE	=		1	
NUMBER IN TWO INCH CIRCLE	=		6	
NUMBER IN THREE INCH CIRCLE	=		9	

8 Dec 1998

FILE:/PATTERNING/CENTERFIRE_PATT/C6587576

CENTERFIRE PATTERNS # 4

POA

1 in circle

2 in circle

3 in circle

OF SHOTS- 10

IN CIR

1 in = 1

2 in = 3

3 in = 5

HS= 4.739

VS= 2.689

GS= 4.741

CENTROID #

PATTERN #	:	4		
SHOTS (BEST OF)	:	10	9	8
MAXIMUM X	:	1.828	1.505	1.131
MINIMUM X	:	-2.911	-1.876	-1.688
MAXIMUM Y	:	1.490	1.440	1.396
MINIMUM Y	:	-1.199	-1.249	-1.293
CENTROID X	:	.014	.337	.149
CENTROID Y	:	-.144	-.094	-.050
POA TO CENTROID in.	:	.145	.350	.158
MIN RADIUS	:	.379	.434	.478
MEAN RADIUS	:	1.390	1.165	1.121
MAX RADIUS	:	2.946	1.951	1.784
HORIZONTAL SPREAD	:	4.739	3.381	2.819
VERTICAL SPREAD	:	2.689	2.689	2.689
EXTREME SPREAD	:	4.741	3.386	2.909
NUMBER IN ONE INCH CIRCLE	=		1	
NUMBER IN TWO INCH CIRCLE	=		3	
NUMBER IN THREE INCH CIRCLE	=		5	

8 Dec 1998

FILE:/PATTERNING/CENTERFIRE_PATT/C6587576

CENTERFIRE PATTERNS # 5

POA

1in circle

2in circle

3in circle

OF SHOTS- 10

IN CIR

1in = 1

2in = 4

3in = 8

HS= 2.595

VS= 2.455

GS= 3.084

CENTROID #

PATTERN #	:	5		
SHOTS (BEST OF)	:	10	9	8
MAXIMUM X	:	1.581	1.729	.879
MINIMUM X	:	-1.014	-.866	-.649
MAXIMUM Y	:	1.008	.867	.822
MINIMUM Y	:	-1.447	-1.588	-1.634
CENTROID X	:	.118	-.030	-.246
CENTROID Y	:	-.177	-.036	.009
POA TO CENTROID in.	:	.213	.047	.247
MIN RADIUS	:	.177	.241	.289
MEAN RADIUS	:	1.051	.920	.768
MAX RADIUS	:	1.839	1.768	1.672
HORIZONTAL SPREAD	:	2.595	2.595	1.529
VERTICAL SPREAD	:	2.455	2.455	2.455
EXTREME SPREAD	:	3.084	2.767	2.505
NUMBER IN ONE INCH CIRCLE	=		1	
NUMBER IN TWO INCH CIRCLE	=		4	
NUMBER IN THREE INCH CIRCLE	=		8	