

C6648990

MODEL 700TM M24

Model **SMS** TM

Action

Barrel Length

Capacity

Order No. **5715**

*Includes 1 in chamber.



Remington® **MODEL 700™ H24**

DU PONT
REG. U.S. PAT. & TM. OFF.

VERY IMPORTANT:
Instruction Book
enclosed to assure
safe use of this
firearm.


SERIAL NO.
C6648990

ORDER NO.
5716

MADE IN ILION, N.Y. U.S.A. Reg. U.S. Pat. & Tm. Off. Marca Registrada Marque Deposee.



LPC



GFM

CONTRACT # DAAA21-87-C-0086

GUN SERIAL #

C6648990

OP. #	OP. NAME	READINGS	DATE	INIT
575 & 580	Assemble Action and Stock		7/24/91	KL
600	Proof		7/24/91	KL
607	Check Headspace		7/24/91	KL
610	Dis-assemble Gun		7/24/91	KL
612	Magnaflux Barrel Action		AUG 7 1991	KR
	Magnaflux Bolt		AUG 7 1991	KR
615	Rollmark Caliber		AUG 7 1991	LS
617	Drill and Tap Sight Holes		AUG 7 1991	LB
618	Polish Barrel		AUG 13 1991	WB
620	Apply Coatings (Barrel Action)		8-27-91	DA
	Apply Coating (Bolt)			
625	Final Assembly A) Clean inside of Bolt Assembly		9/4/91	KL
	B) Inspect Rear Firing Pin Hole for Chamfer in Bolt Head		9/4/91	KL
	C) Inspect Ejector Hole for Chamfer		9/4/91	KL
	D) Oil Firing Pin Ass'y		9/4/91	KL
	E) Adjust Trigger Pull to Min Setting and Stake		9/7/91	KL

op. #	BARBER - M24 0030368	READINGS					DATE	INIT
625 cont.	F) Safety On Force	5	5	5			9/7/91	SL
	G) Safety Off Force	3	3	3			9/7/91	SL
	H) Trigger Pull Test & Retainability						9/7/91	SL
	I) Firing Pin Indent	.0205	.0205	.021			9/7/91	SL
	J) Assemble Stock						9/10/91	KL
	K) Assemble Swivel Studs						9-12-91	D/H
	L) Attach Front and Rear Sight Assemblies						9/10/91	KL
	M) Iron Sight Alignment						9/10/91	KL
	N) Detach Front & Rear Sights & place in numbered container						9/10/91	KL
	O) Attach Scope to Rifle						9/10/91	KL
	P) Detach & Attach Scope 20 Times						9/10/91	KL
640	Gallery Target & Test						9-11-91	NF
	A) Time						"	NF
	B) Malfunctions						"	NF
	C) Pierced Primers						"	NF
	D) Optical Clarity of Scope						"	NF
645	Inspect for Live Ammo						9-11-91	NF
655	Final Inspection							
	A) Headspace						9-12-91	D/H
	B) Trigger Pull	2.20	2.18	2.18	2.22	2.25	9-12-91	SL
	C) Function						9-12-91	D/H
660	Pack						9-17-91	D/H

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS2.50# + .50#
3.00# + .75#
4.00# + 1.00#SERIAL NO. C6648990DATE 9-7-91TESTER JM

	2.50# INITIAL	2.50# AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50#		COMMENTS
PULL #1	2.41	2.36	2.25	2.20	MIN. SETTING, NO AVG. OF 5 READINGS ACCEPT- ABLE LESS THAN 2#
PULL #2	2.26	2.28	2.33	2.18	
PULL #3	2.36	2.31	2.44	2.18	
PULL #4	2.38	2.43	2.30	2.22	
PULL #5	2.31	2.30	2.30	2.25	
TOTAL					
AVG.					

	3.00# INITIAL	3.00# AFTER 20 CYCLES		COMMENTS
PULL #1	3.66	3.33		
PULL #2	3.61	3.51		
PULL #3	3.44	3.31		
PULL #4	3.44	3.52		
PULL #5	3.45	3.49		
TOTAL				
AVG.				

	4.00# INITIAL	4.00# AFTER 20 CYCLES	MAX SETTING GREATER THAN 4#	RESET TO 4# FOR TARGET & ACCURACY
PULL #1	4.22	4.32		4.37
PULL #2	4.51	4.29		4.27
PULL #3	4.21	4.23		4.31
PULL #4	4.40	4.28		4.26
PULL #5	4.28	4.30		4.33
TOTAL				
AVG.				

CENTROIDAL DISTANCE CALCULATIONS
FOR RIFLE # C6648990
12 Sep 1991

CENTROIDAL DISTANCES

0 TO	1	.194487
1 TO	2	.234002
1 TO	3	.208268
1 TO	4	.31939
1 TO	5	.0584637

←----FOR


THE AVERAGE X-COORDINATE FOR THIS RIFLE IS: -.1264
THE AVERAGE Y-COORDINATE FOR THIS RIFLE IS: -.0098
THE RESULTING AVERAGE POI RADIUS FOR THIS RIFLE IS: .126779

THE AVERAGE POI RADIUS FOR THIS RIFLE IS: .9766

11 Sep 1991

FILE:/PATTERNING/CENTERFIRE_PATT/C8540390

CENTERFIRE PATTERNS # 1



OF SHOTS- 10

IN CIR

1in = 4

2in = 7

3in = 10

HS= 1.774

VS= 2.583

GS= 2.670


CENTROID #

PATTERN #	1	2	3
SHOTS (BEST OF)	10	9	8
MAXIMUM X	.869	.769	.728
MINIMUM X	-.905	-.747	-.788
MAXIMUM Y	1.162	1.132	.971
MINIMUM Y	-1.421	-1.292	-.617
CENTROID X	-.112	-.012	.029
CENTROID Y	-.159	-.288	-.127
FOR TO CENTROID in.	.195	.288	.130
MIN RADIUS	.056	.138	.180
MEAN RADIUS	.759	.657	.563
STD RADIUS	1.473	1.356	1.250
HORIZONTAL SPREAD	1.774	1.516	1.516
VERTICAL SPREAD	2.583	2.424	1.588
EXTREME SPREAD	2.670	2.460	2.021
NUMBER IN ONE INCH CIRCLE	= 4		
NUMBER IN TWO INCH CIRCLE	= 7		
NUMBER IN THREE INCH CIRCLE	= 10		

11 Sep 1991

FILE:/PATTERNING/CENTERFIRE_PATT/C6848990

CENTERFIRE PATTERNS # 2



OF SHOTS= 10

IN CIR

1in = 2

2in = 4

3in = 7

HS= 3.065

VS= 2.035

GS= 3.647

CENTROID *


PATTERN #	10	9	8
SHOTS (BEST OF)	10	9	8
MAXIMUM X	1.388	1.202	1.241
MINIMUM X	-1.677	-1.353	-1.203
MAXIMUM Y	.967	.880	.767
MINIMUM Y	-1.068	-.961	-1.074
CENTROID X	-.111	.075	-.075
CENTROID Y	.075	-.032	.081
POA TO CENTROID in.	.134	.082	.110
MIN RADIUS	.339	.349	.365
MEAN RADIUS	1.119	1.033	.940
MAX RADIUS	1.936	1.660	1.613
HORIZONTAL SPREAD	3.065	2.555	2.444
VERTICAL SPREAD	2.035	1.841	1.841
EXTREME SPREAD	3.647	2.714	2.714
NUMBER IN ONE INCH CIRCLE =	2		
NUMBER IN TWO INCH CIRCLE =	4		
NUMBER IN THREE INCH CIRCLE =	7		

11 Sep 1991

FILE:/PATTERNING/CENTERFIRE_PATT/C6648990

CENTERFIRE PATTERNS # 3

POR



OF SHOTS- 10

IN CIR

1in = 2

2in = 4

3in = 8

HS= 4.123

VS= 2.387

GS= 4.199


CENTROID *

PATTERN #	10	9	8
SHOTS (BEST OF)	10	9	8
MAXIMUM X	1.642	1.366	1.351
MINIMUM X	-2.481	-1.294	-1.123
MAXIMUM Y	1.254	1.257	1.162
MINIMUM Y	-1.133	-1.130	-1.225
CENTROID X	-0.089	.187	.016
CENTROID Y	.049	.046	.141
POR TO CENTROID in.	.162	.193	.142
MIN RADIUS	.293	.219	.363
MEAN RADIUS	1.222	1.068	1.001
MAX RADIUS	2.482	1.587	1.516
HORIZONTAL SPREAD	4.123	2.660	2.474
VERTICAL SPREAD	2.387	2.387	2.387
EXTREME SPREAD	4.199	3.146	2.943
NUMBER IN ONE INCH CIRCLE =	2		
NUMBER IN TWO INCH CIRCLE =		4	
NUMBER IN THREE INCH CIRCLE =		6	

11 Sep 1991

FILE:/PATTERNING/CENTERFIRE_PATT/C6648390

CENTERFIRE PATTERNS # 4



OF SHOTS- 10

IN CIR

1in = 3

2in = 6

3in = 7

HS= 3.163

VS= 2.417

GS= 3.457

CENTROID #


PATTERN #	4	9	8
SHOTS (BEST OF)	10	9	8
MAXIMUM X	2.044	1.148	1.037
MINIMUM X	-1.119	-0.892	-0.806
MAXIMUM Y	1.231	1.213	1.888
MINIMUM Y	-1.186	-1.204	-1.052
CENTROID X	-1.151	-0.378	-0.267
CENTROID Y	1.158	1.176	0.024
POA TO CENTROID in.	1.218	1.417	1.268
MIN RADIUS	1.148	1.356	1.226
MEAN RADIUS	1.947	1.829	1.737
MAX RADIUS	2.051	1.664	1.477
HORIZONTAL SPREAD	3.163	2.040	1.843
VERTICAL SPREAD	2.417	2.417	1.940
EXTREME SPREAD	3.457	3.163	2.260
NUMBER IN ONE INCH CIRCLE =	3		
NUMBER IN TWO INCH CIRCLE =	6		
NUMBER IN THREE INCH CIRCLE =	7		

11 Sep 1991

FILE:/PATTERNING/CENTERFIRE_PATT/C6B48990

CENTERFIRE PATTERNS # 5

POB



OF SHOTS = 10

IN CIR

1in = 2

2in = 7

3in = 9

HS = 1.654

VS = 2.572

GS = 2.617

CENTROID *

PATTERN #

5

SHOTS (BEST OF)	10	9	8
MAXIMUM X	1.006	1.061	1.191
MINIMUM X	-.648	-.593	-.463
MAXIMUM Y	.819	.625	.602
MINIMUM Y	-1.753	-.687	-.609
CENTROID X	-.169	-.224	-.354
CENTROID Y	-.172	.022	-.056
POB TO CENTROID in.	.241	.225	.358
MIN RADIUS	.289	.308	.242
MEAN RADIUS	.836	.783	.686
MAX RADIUS	1.822	1.208	1.195
HORIZONTAL SPREAD	1.654	1.654	1.654
VERTICAL SPREAD	2.572	1.312	1.211
EXTREME SPREAD	2.617	1.891	1.730
NUMBER IN ONE INCH CIRCLE	= 2		
NUMBER IN TWO INCH CIRCLE	= 7		
NUMBER IN THREE INCH CIRCLE	= 9		