

C6611678

MODEL 700™ M24

Model **SMS**™

Action

Barrel Length

Capacity

Order No. **5716**

*Includes 1 in chamber.

Remington



Remington [®]		DUPONT REG. U.S. PAT. & TM. OFF.	VERY IMPORTANT: Instruction Book enclosed to assure safe use of this firearm.
MODEL 700TM M24		SERIAL NO. C6611678	ORDER NO. 5716
MADE IN ILION, N.Y. U.S.A. Reg. U.S. Pat & Tm. Off, Marca Registrada Marque Deposee.			



5716 C6611678

20

CONTRACT # DAAA21-87-C-0086

GUN SERIAL # C6611678

OP. #	OP. NAME	READINGS	DATE	INIT
575 & 580	Assemble Action and Stock	3 25	91	RW
600	Proof	3 25	91	RW
607	Check Headspace	3 25	91	RW
610	Dis-assemble Gun	25	91	RW
612	Magnaflux Barrel Action	3 28	91	KR
	Magnaflux Bolt	3 28	91	Y
615	Rollmark Caliber	3 28	91	GL
617	Drill and Tap Sight Holes	APR	3 1991	LB
618	Polish Barrel	APR	3 1991	WB
620	Apply Coatings (Barrel Action)		4-11-91	SA
	Apply Coating (Bolt)			SA
625	Final Assembly A) Clean inside of Bolt Assembly		5/10/91	RW
	B) Inspect Rear Firing Pin Hole for Chamfer in Bolt Head		5/10/91	RW
	C) Inspect Ejector Hole for Chamfer		5/10/91	RW
	D) Oil Firing Pin Ass'y		5/10/91	RW
	E) Adjust Trigger Pull to Min Setting and Stake		5-20-91	PH

op. #	BARBER - M24 0034208 OFF. NAME	READINGS					DATE	INIT
625 cont.	F) Safety On Force	7	7	7			5-21-91	DH
	G) Safety Off Force	4	3	3			5-21-91	DH
	H) Trigger Pull Test & Retainability						5-20-91	DH
	I) Firing Pin Indent	.020	.021	.020			5-21-91	DH
	J) Assemble Stock						5/22/91	RW
	K) Assemble Swivel Studs						6-1-91	DH
	L) Attach Front and Rear Sight Assemblies						5/22/91	RW
	M) Iron Sight Alignment						5/22/91	RW
	N) Detach Front & Rear Sights & place in numbered container						5/22/91	RW
	O) Attach Scope to Rifle						5/22/91	RW
	P) Detach & Attach Scope 20 Times						5/22/91	RW
640	Gallery Target & Test						5/23/91	KT
	A) Time							KT
	B) Malfunctions							KT
	C) Pierced Primers							KT
	D) Optical Clarity of Scope							KT
645	Inspect for Live Ammo						5/23/91	KT
655	Final Inspection							
	A) Headspace						6-1-91	DH
	B) Trigger Pull	2.50	2.44	2.44	2.40	2.28	6/1/91	DH
	C) Function						6-1-91	DH
660	Pack						6-20-91	DF

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50# ± .50#

3.00# ± .75#

4.00# ± 1.00#

SERIAL NO. C6611678

DATE 5-20-91

TESTER DH

	2.50# INITIAL	2.50# AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50#		COMMENTS
PULL #1	2.42	2.35	2.33	2.50	MIN. SETTING, NO AVG. OF 5 READINGS ACCEPT- ABLE LESS THAN 2#
PULL #2	2.40	2.36	2.13	2.44	
PULL #3	2.35	2.20	2.24	2.44	
PULL #4	2.30	2.26	2.21	2.40	
PULL #5	2.36	2.20	2.27	2.28	
TOTAL					
AVG.					

	3.00# INITIAL	3.00# AFTER 20 CYCLES		COMMENTS
PULL #1	3.36	3.34		
PULL #2	3.27	3.32		
PULL #3	3.31	3.32		
PULL #4	3.29	3.38		
PULL #5	3.31	3.30		
TOTAL				
AVG.				

	4.00# INITIAL	4.00# AFTER 20 CYCLES	MAX SETTING GREATER THAN 4#	RESET TO 4# FOR TARGET & ACCURACY
PULL #1	4.12	4.14		4.03
PULL #2	4.16	4.12		4.05
PULL #3	4.00	3.82		4.04
PULL #4	3.95	4.09		4.08
PULL #5	4.01	4.04		3.98
TOTAL				
AVG.				

CENTROIDAL DISTANCE CALCULATIONS
FOR RIFLE # C6611678
23 May 1991

CENTROIDAL DISTANCES

0 TO	1	.306111
1 TO	2	.440638
1 TO	3	.0963016
1 TO	4	.169729
1 TO	5	.303534


45
46 <----POA

THE AVERAGE X-COORDINATE FOR THIS RIFLE IS: .1468
THE AVERAGE Y-COORDINATE FOR THIS RIFLE IS: -.0882
THE RESULTING AVERAGE POI RADIUS FOR THIS RIFLE IS: .167179
THE AMR FOR THIS RIFLE IS: .8772

23 May 1991

FILE:/PATTERNING/CENTERFIRE_PATT/C8611678

CENTERFIRE PATTERNS # 1



OF SHOTS= 10

IN CIR

1 in = 3

2 in = 6

3 in = 9

HS= 2.055

VS= 1.684


GS= 2.096

PATTERN #	1	2	3
SHOTS (BEST OF)	10	9	8
MAXIMUM X	1.259	.872	.822
MINIMUM X	-.796	-.656	-.706
MAXIMUM Y	.766	.664	.540
MINIMUM Y	-.918	-.999	-.729
CENTROID X	.202	.062	.112
CENTROID Y	-.230	-.128	-.004
POA TO CENTROID in.	.306	.143	.112
MIN RADIUS	.332	.166	.089
MEAN RADIUS	.736	.597	.506
MAX RADIUS	1.558	1.075	1.015
HORIZONTAL SPREAD	2.055	1.528	1.528
VERTICAL SPREAD	1.684	1.663	1.269
EXTREME SPREAD	2.096	1.790	1.739
NUMBER IN ONE INCH CIRCLE =	3		
NUMBER IN TWO INCH CIRCLE =	6		
NUMBER IN THREE INCH CIRCLE =	9		

23 May 1991

FILE:/PATTERNING/CENTERFIRE_PATT/C8611678

CENTERFIRE PATTERNS # 2



OF SHOTS= 10

IN CIR

1in = 2

2in = 5

3in = 5

HS= 2.520

VS= 3.789

GS= 3.811

PATTERN #	:	2		
SHOTS (BEST OF)	:	10	9	8
MAXIMUM X	:	1.003	1.020	1.089
MINIMUM X	:	-1.517	-1.500	-1.373
MAXIMUM Y	:	1.557	1.309	1.120
MINIMUM Y	:	-2.232	-1.517	-1.125
CENTROID X	:	-.067	-.084	-.211
CENTROID Y	:	.119	.367	.556
POA TO CENTROID in.	:	.137	.376	.595
MIN RADIUS	:	.163	.295	.293
MEAN RADIUS	:	1.156	1.022	.923
MAX RADIUS	:	2.237	1.828	1.373
HORIZONTAL SPREAD	:	2.520	2.520	2.462
VERTICAL SPREAD	:	3.789	2.926	2.245
EXTREME SPREAD	:	3.811	3.116	2.502
NUMBER IN ONE INCH CIRCLE	=		2	
NUMBER IN TWO INCH CIRCLE	=		5	
NUMBER IN THREE INCH CIRCLE	=		5	

23 May 1991

FILE:/PATTERNING/CENTERFIRE_PATT/08611678

CENTERFIRE PATTERNS

3

POA

1 in circle

2 in circle

3 in circle

CENTROID *

OF SHOTS = 10

IN CIR

1 in = 5

2 in = 8

3 in = 10

HS = 1.299

VS = 1.930

GS = 2.104

PATTERN #	3
SHOTS (BEST OF)	10
MAXIMUM X	.662
MINIMUM X	-.637
MAXIMUM Y	.702
MINIMUM Y	-1.228
CENTROID X	.295
CENTROID Y	-.255
POA TO CENTROID in.	.390
MIN RADIUS	.254
MEAN RADIUS	.651
MAX RADIUS	1.241
HORIZONTAL SPREAD	1.299
VERTICAL SPREAD	1.930
EXTREME SPREAD	2.104
NUMBER IN ONE INCH CIRCLE =	5
NUMBER IN TWO INCH CIRCLE =	8
NUMBER IN THREE INCH CIRCLE =	10

23 May 1991

FILE:/PATTERNING/CENTERFIRE_PATT/C6811678

CENTERFIRE PATTERNS

4

POA

1in circle

2in circle

3in circle

CENTROID #

OF SHOTS- 10

IN CIR

1in = 1

2in = 5

3in = 8

HS= 2.066

VS= 2.576

GS= 2.937

PATTERN #

4

SHOTS (BEST OF)	10	9	8
MAXIMUM X	.963	.913	1.026
MINIMUM X	-1.103	-1.153	-1.040
MAXIMUM Y	.770	.570	.439
MINIMUM Y	-1.805	-1.049	-.865
CENTROID X	.084	.134	.021
CENTROID Y	-.108	.092	.223
POA TO CENTROID in.	.137	.162	.224
MIN RADIUS	.258	.056	.173
MEAN RADIUS	.949	.799	.697
MAX RADIUS	1.860	1.384	1.136
HORIZONTAL SPREAD	2.066	2.066	2.066
VERTICAL SPREAD	2.576	1.619	1.304
EXTREME SPREAD	2.937	2.252	2.252
NUMBER IN ONE INCH CIRCLE =		1	
NUMBER IN TWO INCH CIRCLE =		5	
NUMBER IN THREE INCH CIRCLE =		9	

23 May 1991

FILE:/PATTERNING/CENTERFIRE_PATT/08611678

CENTERFIRE PATTERNS # 5

POA

1 in circle

2 in circle

3 in circle

OF SHOTS = 10

IN CIR

1 in = 2

2 in = 6

3 in = 9

HE = 2.361

VS = 2.557

GS = 2.736

CENTROID #

PATTERN #	5
SHOTS (BEST OF)	10
MAXIMUM X	1.076
MINIMUM X	-1.285
MAXIMUM Y	1.575
MINIMUM Y	-1.982
CENTROID X	.220
CENTROID Y	.073
POA TO CENTROID in.	.232
MIN RADIUS	.259
MEAN RADIUS	.894
MAX RADIUS	1.907
HORIZONTAL SPREAD	2.361
VERTICAL SPREAD	2.557
EXTREME SPREAD	2.736
NUMBER IN ONE INCH CIRCLE =	2
NUMBER IN TWO INCH CIRCLE =	6
NUMBER IN THREE INCH CIRCLE =	9