

CAL: 300 WIN MAG

TRACKING # TLW 1407
PROJECT # 241314

Logform

ET21076

BARBER - 5.22.06r0004076

CONFIDENTIAL

Remington Arms Company Inc.
Research & Development Technical Center
315 West Ring Road
Elizabethtown, KY 42701

Clean & Inspect Checklist

Model: 710 Magnum

Project: 241314

Rifle: A-5

TLW #: TLW1303

Date: 3 15 04Inspector: BLRound Level: 701

- ☒ Measure Headspace min: .005
- ☒ Inspect Take Down Screws for loosening. Top screw 1/8 turn - Center screw 1/8 turn 83
- ☒ Sear Engagement: 1st. .0293 2nd. .0291 3rd. .0291 Ave. .02916 spec. .025" to .030"
- ☐ Reset Sear Engagement if Required: 1st. _____ 2nd. _____ 3rd. _____ Ave. _____
- ☒ Trigger Pull: 1st. 4.584 2nd. 4.683 3rd. 4.805 Ave. 4.691 spec- 4.5 lb. to 5.5 lb.
- ☐ Reset Trigger Pull if Required: 1st. _____ 2nd. _____ 3rd. _____ Ave. _____
- ☒ Inspect cam surface, locking lugs and bolt stop for signs of excessive wear: Cam surface, Locking Lugs some signs of wear
- ☒ Inspect stock for any signs of cracking or other failure: Stock cracked at center screw hole
- ☒ Other items of note: Torque Top screw at 55 in lb - Center screw 45 in lb

TLW1216

Remington Confidential

ET21077