

CAL: 300 WIN MAG

M710 MAGNUM TRIAL AND PILOT TEST 1.1

TRACKING # TLW 1407
PROJECT # 241314

[illegible]

Logform

—**Don**
—**Wally**

BAKBEK - 3.22.06r0004036

Confidential - ~~Sharber~~ 502P060664036 Order
Williams v. Remington

ET21096

CONFIDENTIAL

Remington Arms Company Inc.
Research & Development Technical Center
315 West Ring Road
Elizabethtown, KY 42701

Clean & Inspect Checklist

Model: 710 Magnum

Project: 241314

Rifle: A-15

TLW #: TLW1303

Date: 3 18 104Inspector: BLRound Level: 701

- ☒ Measure Headspace min. .005
- ☒ Inspect Take Down Screws for loosening. Top screw 1/2 turn - Center screw 1/4 turn 83
- ☒ Sear Engagement: 1st. .0349 2nd. .038 3rd. .0342 Ave. .0343 spec. .025" to .030"
- ☒ Reset Sear Engagement if Required: 1st. .0295 2nd. .0290 3rd. .0284 Ave. .0293
- ☐ Trigger Pull: 1st. 5.285 2nd. 5.428 3rd. 5.342 Ave. 5.352 spec- 4.5 lb. to 5.5 lb.
- ☐ Reset Trigger Pull if Required: 1st. 2nd. 3rd. Ave.
- ☒ Inspect cam surface, locking lugs and bolt stop for signs of excessive wear: cam surface, locking lugs, some sign of wear
bolt stop excessive wear
- ☒ Inspect stock for any signs of cracking or other failure: cracked stock at center screw hole

☐ Other items of

note:

TLW1216

Remington Confidential

ET21097