

CAL: 300 WIN MAG

PROJECT # 241314

NAME	DATE	TEST ACTIVITY	COMMENTS	ROUNDS AT START-0	
				RDS. FIRED	TOTAL RDS.
JW / BL	2/16/2004	OUT OF BOX	INSPECTION OK		
SW / BL	2/16/2004	HEADSPACE BEFORE	PROOF MIN + .003		
SW / BL	2/16/2004	PROOF ROUND		1	1
SW / BL	2/16/2004	HEADSPACE AFTER	PROOF MIN + .004		
SW/JW/BL	2/16/04	INDENTS			
SW / BL	2/17/04	SEAR LIFT	SEE DATA SHEET		
SW / BL	2/17/04	ENGAGEMENT			
SW, BL	2/17/04	TRIGGER PULL			
JS	2/19/04	200rd JACK funct.		200	201
BL	2/27/04	500Rd Ext Endur Test		500	701
BL	3/9/04	Clean/Inspection	See Inspection Sheet		

ET2112

CONFIDENTIAL

Remington Arms Company Inc.
Research & Development Technical Center
315 West Ring Road
Elizabethtown, KY 42701

Clean & Inspect Checklist

Model: 710 Magnum

Project: 241314

Rifle: A-23

TLW #: TLW1303

Date: 3 19 104

Inspector: BL

Round Level: 701

- ☒ Measure Headspace min+.004
- ☒ Inspect Take Down Screws for loosening. Center screw 1/8 turn 83
- ☒ Sear Engagement: 1st. .0323 2nd. .0346 3rd. .0344 Ave. .03376 spec-.025" to .030"
- ☒ Reset Sear Engagement if Required: 1st. .0296 2nd. .0291 3rd. .0293 Ave. _____
- ☒ Trigger Pull: 1st. 3.182 2nd. 3.107 3rd. 3.078 Ave. 3.122 spec- 4.5 lb. to 5.5 lb.
- ☒ Reset Trigger Pull if Required: 1st. 4.599 2nd. 4.522 3rd. 4.546 Ave. 4.556
- ☒ Inspect cam surface, locking lugs and bolt stop for signs of excessive wear: Cam surface, locking lugs some sign of wear
- ☐ Inspect stock for any signs of cracking or other failure. _____
- ☐ Other items of note: _____

TLW1216

Remington Confidential

ET21113