-	TLW 1407P	
4	Project No. 241314	
S.A.A.M.I. JAR	R-OFF, DROP & ROTATION TEST	
DROP TEST		
	econtrol Type: 340. Date: 2/24/04	
Dry Cycles/Rounds Completed:	Stock Type Syn Engagement at Start	
Engagement at Start (1) .0353 (2).03		
Engagement at End (1) 10 282 (2) 103		
Model No. 10 Serial No.		
Average Trigger Pull at Start of Test: 4.5	(2) <u>4. 567 (3) 4. 491 (4) 4. 504 (5) 4. 45 4</u> 5 1 5 Std. Dev. of Trigger Pull at Start of Test:	
	(2) 5.001 (3) 5.001 (4) 4.929 (5) 4.917	
Average Trigger Pull at End of Test: 4.9		
	Tester Initials: 5	
Additio	onal Notes and Comments	
For additional details on the prop	per procedures to be used for this Test Procedure refer to:	
	NSF/SÄAMI Z299:5-1990	
SAAMI Specifications for Standard Drop Test:		
	onto 1" thick 85 Durometer (Shore A) Rubber Matt eady to fire, Safe in "Safe" position, Fresh Primed Case	
	Magazine loaded to capacity with Dummy Rounds.	
	op Fire Primed Case to verify firearm will still function.	
48 inch drop (safety i	in "Safe" position) - one drop per orientation.	
	• • •	
	SS system installed – The Firearms will be set with the	
Mileboure # 7 F	ed position for all six orientations of the Drop Test	
Orientation ISS Un	nlocked Comments	
	ass V Fail	
	ass V Fail	
	Pass V Fail	
Barrel Horizontal, Right side of Stock Up: Pa	Pass V Fail	
Barrel Horizontal, Bottom of Stock Up: Pa	Pass Fail BENT SCOPE	
Barrel Horizontal, Bottom of Stock Down: Pa	Pass V Fail	
Notes: (continue on back of sheet if necessary)		
	Page 3 of 3	
·	Z101\DROPTEST_REV5.DOC	