

BARBER - M24 0046201

UPC



C6702826

ORDER NO. 25705
BARREL LENGTH 24"
CAPACITY * 6
*INCLUDES 1 IN CHAMBER

BARBER - M24 0046203

Remington Test Lab, Ilion, N.Y.

Centroidal distance calculations for Rifle # C6702826
11 Nov 1997

THE AVERAGE X-COORDINATE FOR THIS RIFLE IS: .106
THE AVERAGE Y-COORDINATE FOR THIS RIFLE IS: -.139667
THE RESULTING AVERAGE POI RADIUS FOR THIS RIFLE IS: .175336

THE AMR FOR THIS RIFLE IS: .8043

CENTROIDAL DISTANCES

Ø TO 1 .444599
1 TO 2 .784115
1 TO 3 .487543

3 1<----POA

2

REMINGTON CENTERFIRE ACCURACY TEST

REMINGTON TEST LAB, ILION, N.Y.


PATTERN #: ☐ 1 ☐

POA TO CENTROID: .444
MIN RADIUS : .382
MEAN RADIUS : .728
MAX RADIUS : 1.322
CENTROID X : .442
CENTROID Y : .048

11 Nov 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/C5782826

CENTERFIRE PATTERN # 1



OF SHOTS= 5

IN CIRCLE

HS= 1.45

2

VS= 1.47

4

GS= 2.03

5

REMINGTON CENTERFIRE ACCURACY TEST


REMINGTON TEST LAB, ILION, N.Y.

PATTERN #: 2
 POA TO CENTROID: .544
 MIN RADIUS : .181
 MEAN RADIUS : .945
 MAX RADIUS : 2.030
 CENTROID X : -.079
 CENTROID Y : -.538

11 Nov 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/C6702826

CENTERFIRE PATTERN # 2



OF SHOTS= 5

IN CIRCLE

HS= .96
 VS= 3.23
 GS= 3.23

2
 2
 4

REMINGTON CENTERFIRE ACCURACY TEST


REMINGTON TEST LAB, ILION, N.Y.

PATTERN #: 3
 POA TO CENTROID: .084
 MIN RADIUS : .424
 MEAN RADIUS : .740
 MAX RADIUS : 1.116
 CENTROID X : -.045
 CENTROID Y : .071

11 Nov 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/C6702026

CENTERFIRE PATTERN # 3



OF SHOTS= 5

IN CIRCLE

HS= 1.68
 VS= 1.15
 GS= 1.91

1
 4
 5

ISRAELI GUNS

CONTRACT # DAAE20-97-C-0182

GUN SERIAL # C6702826

OP. #	OPERATION NAME	READINGS	DATE	INITIAL
575 & 580	ASSEMBLE ACTION AND STOCK			
600	PROOF			
607	CHECK HEADSPACE			
610	DIS-ASSEMBLE GUN			
612	MAGNAFLUX BARREL ACTION			
	MAGNAFLUX BOLT			
615	ROLLMARK CALIBER			
617	DRILL AND TAP SIGHT HOLES			
618	POLISH BARREL			
620	APPLY COATINGS (BARREL ACTION)			
	(BOLT)			
625	FINAL ASSEMBLY A) CLEAN INSIDE OF BOLT ASSEMBLY			
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD			
	C) INSPECT EJECTOR HOLE FOR CHAMFER			
	D) OIL FIRING PIN ASSEMBLY			
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE			

OP. #	OPERATION NAME	READINGS	DATE	INITIAL
625	F) SAFETY ON FORCE	<u>4</u> <u>4</u> <u>4</u>	10-10-97	CR
CONT.	G) SAFETY OFF FORCE	<u>3</u> <u>3</u> <u>3</u>	10-10-97	CR
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT	<u>.021</u> <u>.021</u> <u>.022</u>	10-10-97	CR
	J) ASSEMBLE STOCK		10-7-97	RW
	K) ASSEMBLE SWIVEL STUDS		12-3-97	CK
	L) ATTACH FRONT AND REAR SIGHT ASSY'S		10-7-97	RW
	M) IRON SIGHT ALIGNMENT		10-7-97	RW
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER		10-7-97	RW
640	GALLERY TEST AND TARGET	485 R 62	11/11/97	FA
	A) MALFUNCTIONS		11/11/97	FT
	B) PIERCED PRIMERS		11/11/97	19
645	INSPECT FOR LIVE AMMO		11/11/97	P.B.
655	FINAL INSPECTION A) HEADSPACE		12-3-97	CK
	B) TRIGGER PULL	<u>2.33</u> <u>2.34</u> <u>2.35</u> <u>2.30</u> <u>2.29</u>	11/13/97	TRP
	C) FUNCTION		12-3-97	CK

SWS TRIGGER PULL TEST

BARBER - M24 0046209

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50# ± .50#

3.00# ± .75#

4.00# ± 1.00#

SERIAL NO. C6702826DATE 10-4-97TESTER RP

	2.50# INITIAL	2.50# AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50#		COMMENTS
PULL #1	2.50	2.33		2.54	MIN. SETTING, NO AVG. OF 5 READINGS ACCEPT- ABLE LESS THAN 2#
PULL #2	2.68	2.34		2.67	
PULL #3	2.41	2.53		2.36	
PULL #4	2.55	2.36		2.30	
PULL #5	2.64	2.35		2.40	
TOTAL	12.78	11.91		12.27	
AVG.	2.55	2.38		2.45	

	3.00# INITIAL	3.00# AFTER 20 CYCLES		COMMENTS
PULL #1	3.36	3.18		
PULL #2	3.47	3.14		
PULL #3	3.20	3.06		
PULL #4	3.52	3.45		
PULL #5	3.10	3.16		
TOTAL	16.65	15.99		
AVG.	3.33	3.19		


	4.00# INITIAL	4.00# AFTER 20 CYCLES	MAX SETTING GREATER THAN 4#	RESET TO 4# FOR TARGET & ACCURACY
PULL #1	4.25	4.24		4.31
PULL #2	4.43	4.08		4.47
PULL #3	4.49	4.17		4.44
PULL #4	4.23	4.17		4.17
PULL #5	4.52	4.12		4.47
TOTAL	21.92	20.78		21.83
AVG.	4.38	4.15		4.36

MODEL 700™ M24
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO 6*

GREEN ENVELOPE CONTAINING:

- INSTRUCTION BOOK
- PRODUCT OWNER'S CARD
- MUSEUM/COUNTRY STORE FLIER
- REMINGTON AUTHORIZED GUNSMITHS

46 FORM



Do Not Use

VERY IMPORTANT!
INSTRUCTION BOOK
ENCLOSED TO ASSURE
SAFE USE OF THIS
FIREARM

Remington®

MODEL 700™ M24
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO 6*

Reg. U.S. Pat. & Tm. Off. Marca Registrada. Marque Deposee.

SERIAL NO.
C6702826

46 ORDER NO.
25705

04XR

5705 C6702826

ORDER 25705

MODEL 700™ M24

UPC



ORDER 25705

MODEL 700™ M24

UPC



SERIAL NO.

