

UPC



C6702966

ORDER NO. 25705

BARREL LENGTH 24"

CAPACITY * 6

*INCLUDES 1 IN CHAMBER

BARBER - M24 0047222

Remington Test Lab, Ilion, N.Y.

Centroidal distance calculations for Rifle # C6702966
16 Oct 1997

THE AVERAGE X-COORDINATE FOR THIS RIFLE IS: $-.0333333$
THE AVERAGE Y-COORDINATE FOR THIS RIFLE IS: $.114333$
THE RESULTING AVERAGE POI RADIUS FOR THIS RIFLE IS: $.119093$

THE AMR FOR THIS RIFLE IS: $.888$

CENTROIDAL DISTANCES

0	TO	1	.399546
1	TO	2	.646845
1	TO	3	.330123


1 3
+ <----POA
2

PATTERN #: ☐ 1 ☐
 POA TO CENTROID: .400
 MIN RADIUS : .359
 MEAN RADIUS : .913
 MAX RADIUS : 1.915
 CENTROID X : -.286
 CENTROID Y : .279

16 Oct 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/C6702966

CENTERFIRE PATTERN # 1



OF SHOTS= 5

IN CIRCLE

HS= 2.99

3

VS= 1.38

3

GS= 3.29

4

REMINGTON CENTERFIRE ACCURACY TEST

REMINGTON TEST LAB, ILION, N.Y.

PATTERN #: ☐ 2 ☐

POA TO CENTROID: .250

MIN RADIUS : .411

MEAN RADIUS : .857

MAX RADIUS : 1.496


CENTROID X : .142

CENTROID Y : -.206

16 Oct 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/C6702966

CENTERFIRE PATTERN # 2



OF SHOTS= 5

IN CIRCLE

HS= 2.08

1

VS= 1.49

4

GS= 2.34

5

REMINGTON CENTERFIRE ACCURACY TEST

REMINGTON TEST LAB, ILION, N.Y.

PATTERN #: ☐ 3 ☐

POA TO CENTROID: .273

MIN RADIUS : .423

MEAN RADIUS : .894

MAX RADIUS : 1.360


CENTROID X : .044

CENTROID Y : .270

16 Oct 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/C6702966

CENTERFIRE PATTERN # 3



OF SHOTS= 5

IN CIRCLE

HS= 1.99

1

VS= 1.63

3

GS= 2.57

5

ISRAELI GUNS

CONTRACT # DAAE20-97-C-0182

GUN SERIAL # C 6702966

OP. #	OPERATION NAME	READINGS	DATE	INITIAL
575 & 580	ASSEMBLE ACTION AND STOCK			
600	PROOF			
607	CHECK HEADSPACE			
610	DIS-ASSEMBLE GUN			
612	MAGNAFLUX BARREL ACTION			
	MAGNAFLUX BOLT			
615	ROLLMARK CALIBER			
617	DRILL AND TAP SIGHT HOLES			
618	POLISH BARREL			
620	APPLY COATINGS (BARREL ACTION)			
	(BOLT)			
625	FINAL ASSEMBLY A) CLEAN INSIDE OF BOLT ASSEMBLY			
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD			
	C) INSPECT EJECTOR HOLE FOR CHAMFER			
	D) OIL FIRING PIN ASSEMBLY			
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE			

OP. #	OPERATION NAME	READINGS	DATE	INITIAL
625	F) SAFETY ON FORCE	<u>6</u> <u>5</u> <u>6</u>	10-7-97	CR
CONT.	G) SAFETY OFF FORCE	<u>4</u> <u>3</u> <u>3</u>	10-7-97	CR
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT	<u>.020</u> <u>.022</u> <u>.021</u>	10-7-97	CR
	J) ASSEMBLE STOCK		10-7-97	RW
	K) ASSEMBLE SWIVEL STUDS		10/8/97	TKP
	L) ATTACH FRONT AND REAR SIGHT ASSY'S		10-7-97	RW
	M) IRON SIGHT ALIGNMENT		10-7-97	RW
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER		10-7-97	RW
640	GALLERY TEST AND TARGET	L64 R86	10/16/97	P.B.
	A) MALFUNCTIONS		10/16/97	P.B.
	B) PIERCED PRIMERS		10/16/97	P.B.
645	INSPECT FOR LIVE AMMO		10/16/97	KR
655	FINAL INSPECTION A) HEADSPACE		10/18/97	RF
	B) TRIGGER PULL	<u>2.60</u> <u>2.59</u> <u>2.59</u> <u>2.65</u> <u>2.64</u>	10/16/97	TM
	C) FUNCTION		10/16/97	F1

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50# ± .50#

3.00# ± .75#

4.00# ± 1.00#

SERIAL NO. C6702966DATE 10-2-97TESTER CK

	2.50# INITIAL	2.50# AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50#		COMMENTS
PULL #1	2.33	2.33		2.40	MIN. SETTING, NO AVG. OF 5 READINGS ACCEPT- ABLE LESS THAN 2#
PULL #2	2.31	2.62		2.47	
PULL #3	2.44	2.39		2.46	
PULL #4	2.56	2.44		2.45	
PULL #5	2.59	2.39		2.53	
TOTAL	12.23	12.17		12.31	
AVG.	2.446	2.434		2.462	

	3.00# INITIAL	3.00# AFTER 20 CYCLES		COMMENTS
PULL #1	2.81	3.11		
PULL #2	3.18	3.06		
PULL #3	3.12	3.11		
PULL #4	3.09	3.09		
PULL #5	3.07	3.08		
TOTAL	15.27	15.45		
AVG.	3.054	3.09		


	4.00# INITIAL	4.00# AFTER 20 CYCLES	MAX SETTING GREATER THAN 4#	RESET TO 4# FOR TARGET & ACCURACY
PULL #1	3.93	3.85		3.88
PULL #2	3.94	3.93		3.94
PULL #3	3.98	3.86		3.93
PULL #4	3.97	4.01		3.85
PULL #5	3.99	3.82		3.80
TOTAL	19.81	19.47		19.5
AVG.	3.962	3.894		3.9

MODEL 700™ M24
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO 6*


GREEN ENVELOPE CONTAINS:
- INSTRUCTION BOOK
- PRODUCT OWNER'S CARD
- MUSEUM/COUNTRY STORE FLIER
- REMINGTON AUTHORIZED GUNSMITHS

46 FORM

proof of purchase



owner registration sticker



Do Not Use

VERY IMPORTANT: INSTRUCTION BOOK ENCLOSED TO ASSURE SAFE USE OF THIS WEAPON.

Remington®

MODEL 700™ M24
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO 6*

REG. U.S. Pat. & Tm. Off. Marca Registrada. Marque Deposee

SERIAL NO. C6702966
46
ORDER NO. 25705
01XR

5705 C6702966

ORDER 25705

MODEL 700™ M24

UPC



ORDER 25705

MODEL 700™ M24

UPC



SERIAL NO.



C6702966