

GL845815

M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO
WITH BIPOD

proof of purchase




owner registration sticker



ORDER NO.	86470
BARREL LENGTH	24"
CAPACITY	6

G6845815

UPC



BM FORM

GUN SERIAL #

G 6845815

OP #	OPERATION NAME	READINGS	DATE	INITIAL
420	ASSEMBLE ACTION		5-5-09	RP
430	ASSEMBLE TO STOCK		5-5-09	SP
440	PROOF		5-5-09	RP
460	CHECK HEADSPACE	MAGNA-FLUX	5-5-09	RP
470	DIS-ASSEMBLE ACTION		5-5-09	RP
472	SERIALIZE BOLT HANDLE		5-6-09	RIZ
480	MAGNAFLUX BBL ACTION	OPERATOR (D)	5/8/09	(R)
490	MAGNAFLUX BOLT			
500	ROLLMARK CALIBER		5/12/09	RT
510	DRILL AND TAP SIGHT HOLES		5-6-09	SP
520	GOFF BLAST BBL / REC		5/12/09	RSM
540	APPLY COATINGS (BARREL ACTION)		5/22	
545	(BOLT)			
560	RE-ASSEMBLE ACTION			
	A) CLEAN INSIDE OF BOLT ASSEMBLY		5-26-09	SP
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		5-26-09	SP
	C) INSPECT EJECTOR HOLE FOR CHAMFER	INSPECT FOR LIVE AMMO	5-26-09	SP
	D) OIL FIRING PIN ASSEMBLY		5-29-09	LJ
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE	2.50 LBS +/- .5 LBS		

F004 REV 5/2006

OP #	OPERATION NAME	READINGS	DATE	INITIAL
560	F) SAFETY ON FORCE 2 LBS MIN 10 LBS MAX	<u>4.0</u> <u>4.0</u> <u>4.0</u>	6-22-09	LN
CONT.	G) SAFETY OFF FORCE 2 LBS MIN	<u>5.0</u> <u>5.0</u> <u>5.0</u>	6-22-09	LN
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT .020 MIN	<u>.023</u> <u>.023</u> <u>.023</u>	6-22-09	LN
	J) ASSEMBLE STOCK		5-29-09	LN
	K) ASSEMBLE SWIVEL STUDS		6-22-09	LN
	L) ATTACH FRONT AND REAR SIGHT ASSY'S			
	M) IRON SIGHT ALIGNMENT			
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER			
640 & 650	FUNCTION TEST AND TARGET	<u>PASS</u> FAIL <u>PASS</u> FAIL	6-9-09	LN
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
660	INSPECT FOR LIVE AMMO		6-9-09	RF
670	FINAL INSPECTION A) HEADSPACE		6-22-09	LN
	B) TRIGGER PULL +/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	<u>2.56</u> <u>2.55</u> <u>2.50</u> <u>2.57</u> <u>2.51</u>	6-18-09	LN
	C) FUNCTION		6-22-09	LN
690	PACK		7/17/09	Fm

F004 REV 5/2006

CONFIDENTIAL-SUBJECT TO PROTECTIVE ORDER
KINZER V. REMINGTON


BARBER - M24 0053581

M2400053620

Trigger Profile [lbs,inch]

Profile: SWS
 GunType: Rifle
 Make: Remington
 Note: R.P. 5/14/09

Model: M/24
 Serial No: Form #F005
 Trigger: 2.5 lbs. ini. +/- .50 lbs.




#	Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
1	2.451	0.018	0.00	0.029	0.031		Set Trigger
2	2.534	0.019	0.00	0.030	0.033		Set Trigger
3	2.440	0.019	0.00	0.031	0.032		Set Trigger
4	2.462	0.019	0.00	0.030	0.032		Set Trigger
5	2.349	0.019	0.00	0.029	0.031		Set Trigger

Avg 2.44

Trigger Profile [lbs,inch]

Profile SWS
 GunType: Rifle
 Make: Remington
 Note: R.P. 5/14/09

Model: M/24
 Serial No: Form #F005
 Trigger: 2.5 lbs. after 50 cycles +/- .50 lbs.




#	Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
1	2.459	0.021	0.00	0.030	0.035		Set Trigger
2	2.509	0.018	0.00	0.030	0.032		Set Trigger
3	2.489	0.018	0.00	0.030	0.032		Set Trigger
4	2.494	0.019	0.00	0.029	0.033		Set Trigger
5	2.442	0.017	0.00	0.029	0.030		Set Trigger

Aug 2.47

Trigger Profile [lbs,inch]

Profile: SWS
 GunType: Rifle
 Make: Remington
 Note: R.P. 5/14/09

Model: M/24
 Serial No: Form #F005
 Trigger: 3.0 lbs. ini. +/- .75 lbs.




#	Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
1	3.012	0.021	0.003	0.035	0.043		Set Trigger
2	3.142	0.019	0.00	0.034	0.043		Set Trigger
3	3.166	0.019	0.00	0.034	0.043		Set Trigger
4	3.127	0.020	0.00	0.034	0.045		Set Trigger
5	3.136	0.020	0.00	0.034	0.044		Set Trigger

Avg 3.11

Trigger Profile [lbs,inch]

Profile: SWS
GunType: Rifle
Make: Remington
Note: R.P. 5/14/09

Model: M/24
Serial No: Form #F005
Trigger: 3.0 lbs. after 20 cycles +/- .75 lbs.




#	Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
1	3.100	0.019	0.00	0.034	0.043		Set Trigger
2	3.103	0.019	0.00	0.034	0.043		Set Trigger
3	2.987	0.019	0.00	0.034	0.041		Set Trigger
4	3.079	0.019	0.00	0.034	0.042		Set Trigger
5	3.055	0.019	0.00	0.034	0.042		Set Trigger

Avg 3.06

Trigger Profile [lbs,inch]

Profile SWS
 GunType: Rifle
 Make: Remington
 Note: R.P. 5/14/09

Model: M/24
 Serial No: Form #F005
 Trigger: 4.0 lbs. ini. +/- 1.0 lbs.




#	Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
1	4.013	0.021	0.00	0.030	0.062		Set Trigger
2	4.084	0.022	0.00	0.030	0.064		Set Trigger
3	4.174	0.022	0.00	0.030	0.064		Set Trigger
4	4.198	0.023	0.00	0.030	0.065		Set Trigger
5	4.218	0.022	0.00	0.030	0.065		Set Trigger

Avg 4.13

Trigger Profile [lbs,inch]

Profile: SWS
 GunType: Rifle
 Make: Remington
 Note: R.P. 5/14/09

Model: M/24
 Serial No: Form #F005
 Trigger: 4.0 lbs. after 20 cycles +/- 1.0 lbs.




#	Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
1	4.205	0.023	0.00	0.030	0.067		Set Trigger
2	4.131	0.023	0.00	0.030	0.066		Set Trigger
3	4.120	0.023	0.00	0.030	0.065		Set Trigger
4	4.172	0.022	0.00	0.030	0.064		Set Trigger
5	4.139	0.022	0.00	0.030	0.063		Set Trigger

Avg 4.15

Trigger Profile [lbs,inch]

Profile SWS
 GunType: Rifle
 Make: Remington
 Note: R.P. 5/14/09

Model: M/24
 Serial No: Form #F005
 Trigger: reset to 2.5 lbs. +/- .50 lbs. for final test




#	Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
1	2.401	0.018	0.00	0.030	0.032		Set Trigger
2	2.392	0.021	0.00	0.030	0.034		Set Trigger
3	2.396	0.020	0.00	0.030	0.032		Set Trigger
4	2.433	0.021	0.00	0.030	0.034		Set Trigger
5	2.469	0.020	0.00	0.030	0.034		Set Trigger

Avg 2.41

Trigger Profile [lbs,inch]

Profile SWS
 GunType: Rifle
 Make: Remington
 Note: R.P. 5/14/09

Model: M/24
 Serial No: Form #F005
 Trigger: set to 4.0 lbs. +/- 1.0 lbs. for target & accuracy



#	Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
1	4.026	0.024	0.00	0.030	0.064		Set Trigger
2	4.075	0.022	0.00	0.030	0.062		Set Trigger
3	4.162	0.022	0.00	0.030	0.063		Set Trigger
4	4.101	0.023	0.00	0.030	0.065		Set Trigger
5	4.091	0.022	0.00	0.030	0.064		Set Trigger

Avg 4.09