

## CONFIDENTIAL

Remington Arms Company Inc.  
Research & Development Technical Center  
315 West Ring Road  
Elizabethtown, KY 42701

# Trial & Pilot Clean & Inspect Checklist

Model: 710 Magnum

Project: 241314

Rifle: A-16

TLW #: TLW1303

Date: 01 / 19 / 04Inspector: JS/BL

Round Level: \_\_\_\_\_

☒ Measure Headspace min +.005
☒ Sear Engagement: 1<sup>st</sup>. .0291 2<sup>nd</sup>. .0304 3<sup>rd</sup>. .0283
Ave. .0292 spec- .020" to .025"
☒ Trigger Pull: 1<sup>st</sup>. 4.556 2<sup>nd</sup>. 4.485 3<sup>rd</sup>. 4.507
Ave. 4.516 spec- 4 lb. to 5.5 lb.
☒ Check Take-Down Screws and Re-tighten if necessary.

☒ Inspect extractor & bolt face area. Bolt face has some wear
☒ Inspect cam surface, locking lugs and bolt stop for signs of excessive wear: locking lugs - Bolt stop worn
☒ Inspect stock for any signs of cracking or other failure.

☒ Other items of
note: magazine box protruding

TLW1303

Remington Confidential

ET21304