

G6774405

M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO
WITH BIPOD

proof of purchase



owner registration sticker



BM FORM


ORDER NO. **86470**

BARREL LENGTH 24"

CAPACITY 6

G6774405

UPC



GUN SERIAL # G 6774405

OP #	OPERATION NAME	READINGS	DATE	INITIAL
420	ASSEMBLE ACTION		7-29-08	SPD
430	ASSEMBLE TO STOCK		7-29-08	SP
440	PROOF		7-29-08	SPD
460	CHECK HEADSPACE		7-29-08	SPD
470	DIS-ASSEMBLE ACTION		7-29-08	SPD
472	SERIALIZE BOLT HANDLE	MAGNA - FLUX AUG 01 2008 OPERATOR <u>BH</u>	7-31-08	KTL
475	DRILL AND TAP SIGHT HOLES		7-31-08	SP
480	MAGNAFLUX BBL ACTION		8/1/08	BH
490	MAGNAFLUX BOLT			
500	ROLLMARK CALIBER		8/1/08	RT
520	GOFF BLAST BBL / REC		8-4-08	DC
542	APPLY COATINGS (BARREL ACTION)		8 8	
545	(BOLT)			
560	RE-ASSEMBLE ACTION			
	A) CLEAN INSIDE OF BOLT ASSEMBLY		8-11-08	SP
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		8-11-08	SP
	C) INSPECT EJECTOR HOLE FOR CHAMFER		8-11-08	SP
	D) OIL FIRING PIN ASSEMBLY		8-11-08	SPD
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE 2.50 LBS +/- .5 LBS			
F004 REV 5/2006				

OP #	OPERATION NAME	READINGS	DATE	INITIAL
560	F) SAFETY ON FORCE 2 LBS MIN 10 LBS MAX	<u>6</u> <u>6</u> <u>6</u>	8-14	TL
CONT.	G) SAFETY OFF FORCE 2 LBS MIN	<u>7</u> <u>7</u> <u>7</u>	8-14	TL
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT .020 MIN	<u>.025</u> <u>.025</u> <u>.025</u>	8-14	TL
	J) ASSEMBLE STOCK		8-11-08	J.P.H.
	K) ASSEMBLE SWIVEL STUDS		8-25	TL
	L) ATTACH FRONT AND REAR SIGHT ASSY'S			
	M) IRON SIGHT ALIGNMENT			
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER			
640 & 650	FUNCTION TEST AND TARGET	<u>PASS</u> FAIL <u>PASS</u> FAIL	8-13-08	TL
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION NA		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
660	INSPECT FOR LIVE AMMO		8-13-08	TRW
670	FINAL INSPECTION A) HEADSPACE		8-25	TL
	B) TRIGGER PULL +/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	<u>3.46</u> <u>2.50</u> <u>2.43</u> <u>2.47</u> <u>2.24</u>	8-14-08	Fm
	C) FUNCTION		8-25	TL
690	PACK		8/24/08	Fm

F004 REV 5/2006

INITIAL & CYCLE TESTS

2.50 LBS (plus or minus 0.50 LBS)

3.00 LBS (plus or minus 0.75 LBS)

4.00 LBS (plus or minus 1.00 LBS)

DATE 7-25-08

TESTER S. Day

	2.50 LBS INITIAL	2.50 LBS AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50 LBS		COMMENTS
PULL #1	2.72	2.46		2.78	
PULL #2	2.53	2.45		2.72	
PULL #3	2.61	2.59		2.67	
PULL #4	2.32	2.52		2.62	
PULL #5	2.41	2.48		2.55	
TOTAL	1259	1250		1334	
AVERAGE	251	2.50		2.66	

	3.00 LBS INITIAL	3.00 LBS AFTER 20 CYCLES		COMMENTS
PULL #1	3.17	3.19		
PULL #2	3.20	3.12		
PULL #3	3.04	3.10		
PULL #4	3.03	3.00		
PULL #5	3.06	3.03		
TOTAL	1550	1544		
AVERAGE	3.10	3.08		

	4.00 LBS INITIAL	4.00 LBS AFTER 20 CYCLES	MAX SETTING GREATER THAN 4 LBS	RESET TO 4 LBS FOR TARGET & ACCURACY
PULL #1	4.13	4.03		4.07
PULL #2	3.99	4.30		4.05
PULL #3	4.13	4.13		4.04
PULL #4	4.03	4.04		4.02
PULL #5	4.14	4.05		3.93
TOTAL	2042	2055		2011
AVERAGE	4.08	4.11		4.02