

56774445

**M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)**  
**BOLT ACTION CENTERFIRE RIFLE**  
**24" BARREL 7.62 NATO**  
**WITH BIPOD**

proof of purchase



owner registration sticker



BM FORM


ORDER NO. **86470**

BARREL LENGTH **24"**

CAPACITY **6**

**G6774445**

**UPC**



## BARBER - M24 0056959 INSPECTION CHECKLIST-NEW GUNS

GUN SERIAL #

G677 4445

| OP # | OPERATION NAME                                                 | READINGS            | DATE    | INITIAL |
|------|----------------------------------------------------------------|---------------------|---------|---------|
| 420  | ASSEMBLE ACTION                                                |                     | 7-31-08 | SP      |
| 430  | ASSEMBLE TO STOCK                                              |                     | 7-31-08 | SP      |
| 440  | PROOF                                                          |                     | 7-31-08 | SP      |
| 460  | CHECK HEADSPACE                                                |                     | 7-31-08 | SP      |
| 470  | DIS-ASSEMBLE ACTION                                            |                     | 7-31-08 | SP      |
| 472  | SERIALIZE BOLT HANDLE                                          | MAGNA - FLUX        | 8-1-08  | SP      |
| 475  | DRILL AND TAP<br>SIGHT HOLES                                   | AUG 05 2008         | 8-6-08  | SP      |
| 480  | MAGNAFLUX BBL ACTION                                           | OPERATOR BM         | 8/6     | BM      |
| 490  | MAGNAFLUX BOLT                                                 |                     |         |         |
| 500  | ROLLMARK CALIBER                                               |                     | 8/6/08  | RT      |
| 520  | GOFF BLAST BBL / REC                                           |                     | 8/7/08  | BM      |
| 542  | APPLY COATINGS<br>(BARREL ACTION)                              |                     | 8/6     |         |
| 545  | (BOLT)                                                         |                     |         |         |
| 560  | RE-ASSEMBLE ACTION                                             |                     |         |         |
|      | A) CLEAN INSIDE OF<br>BOLT ASSEMBLY                            |                     | 8-18-08 | SP      |
|      | B) INSPECT REAR FIRING<br>PIN HOLE FOR CHAMFER<br>IN BOLT HEAD |                     | 8-18-08 | SP      |
|      | C) INSPECT EJECTOR<br>HOLE FOR CHAMFER                         |                     | 8-18-08 | SP      |
|      | D) OIL FIRING PIN ASSEMBLY                                     |                     | 8-22-08 | BSW     |
|      | E) ADJUST TRIGGER PULL<br>TO MIN. SETTING AND<br>STAKE         | 2.50 LBS +/- .5 LBS |         |         |

F004 REV 5/2006


| OP #         | OPERATION NAME                                                                           | READINGS                                                    | DATE     | INITIAL |
|--------------|------------------------------------------------------------------------------------------|-------------------------------------------------------------|----------|---------|
| 560          | <b>BARBER - M24 00569960</b><br>F) SAFETY ON FORCE <span>2 LBS MIN<br/>10 LBS MAX</span> | <u>3.5</u> <u>3.5</u> <u>3.5</u>                            | 9-17-08  | TL      |
| CONT.        | G) SAFETY OFF FORCE <span>2 LBS MIN</span>                                               | <u>5.5</u> <u>6</u> <u>6</u>                                | 9-17-08  | TL      |
|              | H) TRIGGER PULL TEST<br>AND RETAINABILITY                                                |                                                             |          |         |
|              | I) FIRING PIN INDENT <span>.020 MIN</span>                                               | <u>.023</u> <u>.023</u> <u>.023</u>                         | 9-17-08  | TL      |
|              | J) ASSEMBLE STOCK                                                                        |                                                             | 8-22-08  | lgn     |
|              | K) ASSEMBLE SWIVEL<br>STUDS                                                              |                                                             | 9-17-08  | TL      |
|              | L) ATTACH FRONT AND<br>REAR SIGHT ASSY'S                                                 |                                                             |          |         |
|              | M) IRON SIGHT<br>ALIGNMENT                                                               |                                                             |          |         |
|              | N) DETACH FRONT AND<br>REAR SIGHTS AND PLACE<br>IN NUMBERED CONTAINER                    |                                                             |          |         |
| 640 &<br>650 | FUNCTION TEST AND<br>TARGET                                                              | <div>PASS FAIL</div> <div>PASS FAIL</div>                   | 9-5-08   | TRW     |
|              | MALFUNCTION                                                                              | CORRECTION                                                  | N/A      |         |
|              | MALFUNCTION                                                                              | CORRECTION                                                  |          |         |
|              | MALFUNCTION                                                                              | CORRECTION                                                  |          |         |
|              | MALFUNCTION                                                                              | CORRECTION                                                  |          |         |
| 660          | INSPECT FOR LIVE AMMO                                                                    |                                                             | 9-5-08   | Fm      |
| 670          | FINAL INSPECTION<br>A) HEADSPACE                                                         |                                                             | 9-17-08  | TL      |
|              | B) TRIGGER PULL <span>+/- .5 LBS<br/>MIN 2.50 LBS<br/>MAX 4.0 LBS</span>                 | <u>2.63</u> <u>2.56</u> <u>2.58</u> <u>2.55</u> <u>2.47</u> | 9-9-08   | RGR     |
|              | C) FUNCTION                                                                              |                                                             | 9-17-08  | TL      |
| 690          | PACK                                                                                     |                                                             | 10/24/08 | Fm      |

F004 REV 5/2006

## Trigger Profile [ lbs,inch ]

Profile: SWS  
 GunType: Rifle  
 Make: Remington  
 Note: C Schults 08/16/2008

Model: M/24  
 Serial No: Form #F005  
 Trigger: 2.5 lbs. ini. +/- .50 lbs.




| # | Peak Force | Travel To Actuate | Initial Take-up | Overtravel | Energy To Actuate | Lock Time | Action Type |
|---|------------|-------------------|-----------------|------------|-------------------|-----------|-------------|
| 1 | 2.523      | 0.051             | 0.039           | 0.033      | 0.037             |           | Set Trigger |
| 2 | 2.572      | 0.053             | 0.039           | 0.033      | 0.039             |           | Set Trigger |
| 3 | 2.461      | 0.051             | 0.038           | 0.033      | 0.038             |           | Set Trigger |
| 4 | 2.529      | 0.052             | 0.039           | 0.033      | 0.039             |           | Set Trigger |
| 5 | 2.619      | 0.052             | 0.038           | 0.033      | 0.040             |           | Set Trigger |

Avg 2.54

## Trigger Profile [ lbs,inch ]

Profile: SWS  
 GunType: Rifle  
 Make: Remington  
 Note: C Schults 08/16/2008

Model: M/24  
 Serial No: Form #F005  
 Trigger: 2.5 lbs. after 50 cycles+/- .50 lbs.




| # | Peak Force | Travel To Actuate | Initial Take-up | Overtravel | Energy To Actuate | Lock Time | Action Type |
|---|------------|-------------------|-----------------|------------|-------------------|-----------|-------------|
| 1 | 2.565      | 0.046             | 0.032           | 0.033      | 0.038             |           | Set Trigger |
| 2 | 2.552      | 0.046             | 0.032           | 0.033      | 0.039             |           | Set Trigger |
| 3 | 2.522      | 0.046             | 0.033           | 0.033      | 0.038             |           | Set Trigger |
| 4 | 2.489      | 0.045             | 0.033           | 0.034      | 0.036             |           | Set Trigger |
| 5 | 2.589      | 0.046             | 0.033           | 0.033      | 0.038             |           | Set Trigger |

Avg. 2.54

## Trigger Profile [ lbs,inch ]

**Profile:** SWS  
**GunType:** Rifle  
**Make:** Remington  
**Note:** C Schults 08/16/2008

**Model:** M/24  
**Serial No:** Form #F005  
**Trigger:** 3.0 lbs. ini. +/- .75 lbs.




| # | Peak Force | Travel To Actuate | Initial Take-up | Overtravel | Energy To Actuate | Lock Time | Action Type |
|---|------------|-------------------|-----------------|------------|-------------------|-----------|-------------|
| 1 | 3.197      | 0.045             | 0.031           | 0.031      | 0.048             |           | Set Trigger |
| 2 | 3.124      | 0.045             | 0.031           | 0.032      | 0.048             |           | Set Trigger |
| 3 | 3.160      | 0.044             | 0.030           | 0.031      | 0.048             |           | Set Trigger |
| 4 | 3.146      | 0.045             | 0.030           | 0.031      | 0.049             |           | Set Trigger |
| 5 | 3.208      | 0.045             | 0.030           | 0.031      | 0.049             |           | Set Trigger |

Aug. 3-16

## Trigger Profile [ lbs,inch ]

Profile: SWS  
GunType: Rifle  
Make: Remington  
Note: C Schults 08/16/2008

Model: M/24  
Serial No: Form #F005  
Trigger: 3.0 lbs. after 20 cycles+/- .75 lbs.




| # | Peak Force | Travel To Actuate | Initial Take-up | Overtravel | Energy To Actuate | Lock Time | Action Type |
|---|------------|-------------------|-----------------|------------|-------------------|-----------|-------------|
| 1 | 3.176      | 0.042             | 0.028           | 0.031      | 0.046             |           | Set Trigger |
| 2 | 3.098      | 0.043             | 0.028           | 0.030      | 0.048             |           | Set Trigger |
| 3 | 3.137      | 0.044             | 0.028           | 0.030      | 0.049             |           | Set Trigger |
| 4 | 3.128      | 0.043             | 0.028           | 0.030      | 0.048             |           | Set Trigger |
| 5 | 3.085      | 0.042             | 0.028           | 0.030      | 0.045             |           | Set Trigger |

Aug-3-12

## Trigger Profile [ lbs,inch ]

Profile: SWS  
GunType: Rifle  
Make: Remington  
Note: C Schults 08/16/2008

Model: M/24  
Serial No: Form #F005  
Trigger: 4.0 lbs. ini. +/- 1.0 lb.




| # | Peak Force | Travel To Actuate | Initial Take-up | Overtravel | Energy To Actuate | Lock Time | Action Type |
|---|------------|-------------------|-----------------|------------|-------------------|-----------|-------------|
| 1 | 4.331      | 0.044             | 0.026           | 0.028      | 0.069             |           | Set Trigger |
| 2 | 4.299      | 0.042             | 0.026           | 0.028      | 0.065             |           | Set Trigger |
| 3 | 4.309      | 0.043             | 0.026           | 0.028      | 0.068             |           | Set Trigger |
| 4 | 4.333      | 0.042             | 0.026           | 0.028      | 0.067             |           | Set Trigger |
| 5 | 4.340      | 0.042             | 0.026           | 0.028      | 0.066             |           | Set Trigger |

Aug 4-32

## Trigger Profile [ lbs,inch ]

Profile: SWS  
 GunType: Rifle  
 Make: Remington  
 Note: C Schults 08/16/2008

Model: M/24  
 Serial No: Form #F005  
 Trigger: 4.0 lbs. after 20 cycles+/- 1.0 lb.




| # | Peak Force | Travel To Actuate | Initial Take-up | Overtravel | Energy To Actuate | Lock Time | Action Type |
|---|------------|-------------------|-----------------|------------|-------------------|-----------|-------------|
| 1 | 4.520      | 0.057             | 0.041           | 0.030      | 0.075             |           | Set Trigger |
| 2 | 4.342      | 0.057             | 0.041           | 0.030      | 0.073             |           | Set Trigger |
| 3 | 4.387      | 0.057             | 0.041           | 0.030      | 0.074             |           | Set Trigger |
| 4 | 4.362      | 0.056             | 0.041           | 0.031      | 0.071             |           | Set Trigger |
| 5 | 4.375      | 0.057             | 0.040           | 0.030      | 0.075             |           | Set Trigger |

Aug. 4:39

## Trigger Profile [ lbs,inch ]

Profile: SWS  
 GunType: Rifle  
 Make: Remington  
 Note: C Schults 08/16/2008

Model: M/24  
 Serial No: Form #F005  
 Trigger: reset to 2.5 lbs. +/- .50 lbs. for final test




| # | Peak Force | Travel To Actuate | Initial Take-up | Overtravel | Energy To Actuate | Lock Time | Action Type |
|---|------------|-------------------|-----------------|------------|-------------------|-----------|-------------|
| 1 | 2.553      | 0.053             | 0.040           | 0.034      | 0.041             |           | Set Trigger |
| 2 | 2.656      | 0.053             | 0.040           | 0.034      | 0.041             |           | Set Trigger |
| 3 | 2.598      | 0.054             | 0.040           | 0.034      | 0.041             |           | Set Trigger |
| 4 | 2.607      | 0.053             | 0.039           | 0.034      | 0.041             |           | Set Trigger |
| 5 | 2.568      | 0.053             | 0.040           | 0.034      | 0.041             |           | Set Trigger |

Avg. 2.59

## Trigger Profile [ lbs,inch ]

Profile: SWS  
 GunType: Rifle  
 Make: Remington  
 Note: C Schults 08/16/2008

Model: M/24  
 Serial No: Form #F005  
 Trigger: set to 4.0 lbs. +/- 1.0 lb. for target & accuracy



| # | Peak Force | Travel To Actuate | Initial Take-up | Overtravel | Energy To Actuate | Lock Time | Action Type |
|---|------------|-------------------|-----------------|------------|-------------------|-----------|-------------|
| 1 | 4.160      | 0.051             | 0.036           | 0.031      | 0.066             |           | Set Trigger |
| 2 | 4.223      | 0.052             | 0.036           | 0.030      | 0.069             |           | Set Trigger |
| 3 | 4.193      | 0.052             | 0.036           | 0.030      | 0.069             |           | Set Trigger |
| 4 | 4.242      | 0.052             | 0.036           | 0.030      | 0.070             |           | Set Trigger |
| 5 | 4.235      | 0.052             | 0.036           | 0.031      | 0.068             |           | Set Trigger |

Aug. 4.21