

66778852

M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO
WITH BIPOD

proof of purchase




owner registration sticker



BM FORM

ORDER NO.	86470
BARREL LENGTH	24"
CAPACITY	6

G6778852



INSPECTION CHECKLIST-NEW GUNS

GUN SERIAL #

G 6778852

OP #	OPERATION NAME	READINGS	DATE	INITIAL
420	ASSEMBLE ACTION		8-26-08	SP
430	ASSEMBLE TO STOCK		8-26-08	SP
440	PROOF		8-26-08	SP
460	CHECK HEADSPACE		8-26-08	SP
470	DIS-ASSEMBLE ACTION		8-26-08	SP
472	SERIALIZE BOLT HANDLE		8-29-08	BSN
475	DRILL AND TAP SIGHT HOLES	MAGNA - FLUX SEP 10 2008 OPERATOR <u>BSN</u>	9-5-08	SP
480	MAGNAFLUX BBL ACTION		9-10-08	BSN
490	MAGNAFLUX BOLT			
500	ROLLMARK CALIBER		9/10/08	RT
520	GOFF BLAST BBL / REC			
542	APPLY COATINGS (BARREL ACTION)		9/14	~
545	(BOLT)			
560	RE-ASSEMBLE ACTION			
	A) CLEAN INSIDE OF BOLT ASSEMBLY		9-17-08	SP
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		9-17-08	SP
	C) INSPECT EJECTOR HOLE FOR CHAMFER		9-17-08	SP
	D) OIL FIRING PIN ASSEMBLY		9-18-08	BSN
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE	2.50 LBS +/- .5 LBS		

F004 REV 5/2006

OP #	OPERATION NAME	READINGS	DATE	INITIAL
560	F) SAFETY ON FORCE 2 LBS MIN 10 LBS MAX	<u>3</u> <u>3</u> <u>3</u>	9-24-08	TL
CONT.				
	G) SAFETY OFF FORCE 2 LBS MIN	<u>5.5</u> <u>5.5</u> <u>5.5</u>	9-24-08	TL
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT .020 MIN	<u>.025</u> <u>.024</u> <u>.024</u>	9-24-08	TL
	J) ASSEMBLE STOCK		9-18-08	RBN
	K) ASSEMBLE SWIVEL STUDS		9-24-08	TL
	L) ATTACH FRONT AND REAR SIGHT ASSY'S			
	M) IRON SIGHT ALIGNMENT			
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER			
640 & 650	FUNCTION TEST AND TARGET	<u>PASS</u> FAIL <u>PASS</u> FAIL	9-18-08	FM
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION <i>N/A</i>		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
660	INSPECT FOR LIVE AMMO		9-18-08	AA
670	FINAL INSPECTION A) HEADSPACE		9-24-08	TL
	B) TRIGGER PULL +/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	<u>2.66</u> <u>2.87</u> <u>2.83</u> <u>2.59</u> <u>2.74</u>	9-19-08	TRW
	C) FUNCTION		9-24-08	TL
690	PACK		10/13/08	Fry

F004 REV 5/2006

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

1.00 LBS. 1.00 LBS. AFTER 20 CYCLES
 2.00 LBS. 2.00 LBS. AFTER 20 CYCLES
 3.00 LBS. 3.00 LBS. AFTER 20 CYCLES

DATE 9-16-08

TESTER T98

	2.00 LBS INITIAL	2.00 LBS AFTER 20 CYCLES	FINAL TEST & TO RESET 2.00 LBS		COMMENTS
PULL #1	237	223		262	
PULL #2	232	215		254	
PULL #3	213	202		270	
PULL #4	221	216		263	
PULL #5	221	220		263	
TOTAL	1124	1076		1312	
AVERAGE	224	215		262	

	3.00 LBS INITIAL	3.00 LBS AFTER 20 CYCLES		COMMENTS
PULL #1	327	326		
PULL #2	315	311		
PULL #3	300	303		
PULL #4	310	309		
PULL #5	323	313		
TOTAL	1575	1562		
AVERAGE	315	312		

	4.00 LBS INITIAL	4.00 LBS AFTER 20 CYCLES	MAX SETTING GREATER THAN 4 LBS	RESET TO 4 LBS FOR TARGET & ACCURACY
PULL #1	487	471		463
PULL #2	482	460		459
PULL #3	478	467		480
PULL #4	481	463		472
PULL #5	460	466		468
TOTAL	2388	2324		2342
AVERAGE	477	464		468