C6345717

MODEL 700™ M24

Model SWS™

Action

Barrel Length

Capacity

Order No. 5716

*Includes 1 in chamber.

Remington®

04/24/08 12:24:17

Arms Services Repair & Estimate System

File Add Repair Estimate Repair Expedite Repair Inquiry Repair Tools CSR Tools Reports Table Maintenance System Maintenance Help

Repair Inquiry

Repair Number: RE00144815

Verify Repair

Serial: C6348717 Model M24 SWS Center Fire
Caliber: 7.62 NATO

Repairman:

Status: Closed 4/24/2008 10:57:55 AM

Address Information

Customer:		Return To:	
	Received From		Received From
Name:	B/210TH BSB		B/210TH BSB
Address 1:	2 BCT		2 BCT
Address 2:	10 TH MTN DIV		10 TH MTN DIV
PO Box:		PO Box:	
City:	FORT DRUM		FORT DRUM
State:	NY	State:	NY
Zip Code:	13602	Zip Code:	13602
Country:	US	Country:	US

FFL:

Contact / Condition | Problems | Estimate | History / Status | Shipping / Billing

Contact Information

Phone: NN

Fax:

Email:

Comments:

Received Condition

Fair

Condition Notes:

CSR Notes:

Accessories Received

Code	Desc	Qty
A007	With Stud	3
A008	With Swivel	3
A010	Hard Case	1
A026	Scope	1
A057	Frt and Rear Sgt Base	1

nagletj 4/24/2008 12:24 PM NUM

Start | 4 Micros... | The Asso... | 2 Micros... | SAP Logo... | Arms Ser...

SNIPER WEAPON SYSTEM - UNIQUE STATISTICAL INFOMATION

FIREARM SERIAL NUMBER / DATASET NAME: C6348717.__0
FILE DATE AND TIME: 05/27/2008 05:37

THE FOLLOWING DATA IS ALL REPORTED IN UNITS OF INCHES

The Average X Centroid of the Five Target Set:	-0.029
The Average Y Centroid of the Five Target Set:	-0.103
The Average Point of Impact of the Five Target Set:	0.107
The Average Mean Radius of the Five Target Set:	0.773
The Distance from POA to Centroid Target #1:	0.299
The Distance from Centroid Target #2 to Centroid Target #1:	0.340
The Distance from Centroid Target #3 to Centroid Target #1:	0.277
The Distance from Centroid Target #4 to Centroid Target #1:	0.235
The Distance from Centroid Target #5 to Centroid Target #1:	0.305

SERIAL NUMBER: C6348717.__0
TARGET NUMBER: 2
FILE DATE: 05/27/2008
FILE TIME: 05:37

X CENTROID:	-0.119
Y CENTROID:	-0.032
POA TO CENTROID:	0.123
HORZ SPREAD:	1.782
VERT SPREAD:	2.743
GROUP SPREAD:	2.991
MIN RADIUS:	0.270
MAX RADIUS:	1.702
MEAN RADIUS:	0.859
# IN 1 IN DIAMETER:	5
# IN 2 IN DIAMETER:	6
# in 3 IN DIAMETER:	9

POINT#	X	Y
1:	-0.549	-1.394
2:	-1.084	-1.434
3:	-0.273	-0.451
4:	0.698	-0.205
5:	-0.485	0.131
6:	0.603	1.036
7:	-0.448	1.309
8:	0.244	0.264
9:	-0.011	0.325
10:	0.115	0.103



TARGET APPROX 1/2 SCALE

SERIAL NUMBER: C6348717.__0
TARGET NUMBER: 3
FILE DATE: 05/27/2008
FILE TIME: 05:37

X CENTROID:	0.020
Y CENTROID:	-0.016
POA TO CENTROID:	0.026
HORZ SPREAD:	1.417
VERT SPREAD:	1.710
GROUP SPREAD:	1.715
MIN RADIUS:	0.233
MAX RADIUS:	1.026
MEAN RADIUS:	0.561
# IN 1 IN DIAMETER:	5
# IN 2 IN DIAMETER:	9
# in 3 IN DIAMETER:	10

POINT#	X	Y
1:	0.266	-1.012
2:	-0.044	-0.427
3:	0.248	-0.067
4:	0.354	-0.017
5:	0.658	-0.034
6:	-0.443	-0.036
7:	-0.759	-0.166
8:	-0.006	0.360
9:	-0.198	0.546
10:	0.129	0.698



TARGET APPROX 1/2 SCALE

SERIAL NUMBER: C6348717.__0
TARGET NUMBER: 4
FILE DATE: 05/27/2008
FILE TIME: 05:37

X CENTROID:	-0.057
Y CENTROID:	-0.119
POA TO CENTROID:	0.132
HORZ SPREAD:	1.861
VERT SPREAD:	1.388
GROUP SPREAD:	1.930
MIN RADIUS:	0.089
MAX RADIUS:	1.102
MEAN RADIUS:	0.705
# IN 1 IN DIAMETER:	3
# IN 2 IN DIAMETER:	9
# in 3 IN DIAMETER:	10

POINT#	X	Y
1:	0.705	-0.712
2:	0.328	-0.667
3:	0.691	-0.242
4:	0.394	0.628
5:	0.196	0.255
6:	-0.116	-0.053
7:	-0.404	-0.383
8:	-0.802	-0.496
9:	-1.156	-0.199
10:	-0.404	0.676



TARGET APPROX 1/2 SCALE

SERIAL NUMBER: C6348717.__0
TARGET NUMBER: 5
FILE DATE: 05/27/2008
FILE TIME: 05:37

X CENTROID:	-0.111
Y CENTROID:	-0.075
POA TO CENTROID:	0.134
HORZ SPREAD:	2.046
VERT SPREAD:	1.350
GROUP SPREAD:	2.189
MIN RADIUS:	0.263
MAX RADIUS:	1.242
MEAN RADIUS:	0.706
# IN 1 IN DIAMETER:	3
# IN 2 IN DIAMETER:	9
# in 3 IN DIAMETER:	10

POINT#	X	Y
1:	-0.506	0.488
2:	-0.927	0.409
3:	-1.313	0.238
4:	0.560	0.406
5:	0.195	0.193
6:	0.733	-0.541
7:	0.420	-0.463
8:	-0.199	-0.337
9:	-0.129	-0.862
10:	0.057	-0.277



TARGET APPROX 1/2 SCALE

M-24 INSPECTION CHECKLIST

CONTRACT #: DAAE-20-02-C-0149

R & E NUMBER 144815

SERIAL NUMBER C6348717

LOG-IN DATE 4-24-08

OPERATION #	OPERATION NAME		DATE	INITIAL
500	DIS-ASSEMBLE GUN		4-28-08	RTZ
505	RE-BARREL			
560	ASSEMBLE		4-30-08	TRW
600	PROOF		4-30-08	TRW
605	CHECK HEADSPACE		4-30-08	TRW
610	DIS-ASSEMBLE GUN		4-30-08	S.P.D.
612	MAGNAFLUX	MAGNA - FLUX MAY 3 = 2008 OPERATOR	5/1/08	
510	DRILL AND TAP		5-1-08	TRW
615	ROLLMARK CALIBER		5-1-08	CW
618	ROTO-BLAST		5-1-08	DG
620	APPLY COATINGS		5-5-08	
625	FINAL ASSEMBLY		5-23-08	RTZ
640	FUNCTION TEST AND	(PASS) FAIL	5/23/08	SD
650	TARGET	(PASS) FAIL	5-23-08	SD
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION N/A		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION	5-23-08	RP
670	FINAL INSPECTION		5/28/08	FM
	A) HEADSPACE	(PASS) FAIL	5/28/08	FM
	B) TRIGGER PULL (+/- .5 LBS, MIN 2.50 LBS, MAX 4.0 LBS)	2.73 2.75 2.77 2.70 2.75	5-27-08	TRW
680	F) SAFETY ON FORCE (2 LBS MIN, 10 LBS MAX)	5 5 5	5/28/08	FM
	G) SAFETY OFF FORCE (2 LBS MIN)	2 2 2	5/28/08	FM
	I) FIRING PIN INDENT .020	.022 .021 .021	5/28/08	FM
690	PACK		5/28/08	FM


Arms Service
File Add Repair Estimate Repair Expedite Repair Inquiry Repair Tools CSR Tools Reports Table Maintenance System Maintenance Help
Repair Inquiry
Repair Number RE00092984
Verify Repair
Serial: C634871 7 Model: M24 SWS Center Fire Caliber: 7.62 NATO Produced: 12/13/1989
Repairman:
Status: Closed 2/11/2005 7:30:55 AM
Address Information
Customer
Received From
Name: DEF DIST DEPOT ANNISTON
Address 1:
Address 2:
PO Box:
City: ANNISTON
State: AL Zip Code: 362014199 Country: US
Return To:
Received From
DEF DIST DEPOT ANNISTON
PO Box:
ANNISTON
State: AL Zip Code: 362014199 Country: US
FFL:
Contact / Condition
Problems
Estimate
History / Status
Shipping / Billing
Contact Information
Phone:
Fax:
Email:
Comments:
Received Condition
Good
Condition Notes:
CSR Notes:
Accessories Received
Code Desc Qty
A007 With Stud 3
A010 Hard Case 1
A017 Scope Base 1
A026 Scope 1
A057 Frt and Rear Sgt Base 1
Repair Search
Refresh
Close
nagler 2/14/2005 9:11 AM CAPS NUM INS SCRL
start
Arms Service

Serial Number: C634871 7
Model: M24 SWS
RE00092984

SNIPER WEAPON SYSTEM - UNIQUE STATISTICAL INFOMATION

FIREARM SERIAL NUMBER / DATASET NAME: C6348717.__0
FILE DATE AND TIME: 03/24/2005 09:04

THE FOLLOWING DATA IS ALL REPORTED IN UNITS OF INCHES

The Average X Centroid of the Five Target Set:	-0.088
The Average Y Centroid of the Five Target Set:	0.127
The Average Point of Impact of the Five Target Set:	0.154
The Average Mean Radius of the Five Target Set:	1.002
The Distance from POA to Centroid Target #1:	0.261
The Distance from Centroid Target #2 to Centroid Target #1:	0.455
The Distance from Centroid Target #3 to Centroid Target #1:	0.325
The Distance from Centroid Target #4 to Centroid Target #1:	0.665
The Distance from Centroid Target #5 to Centroid Target #1:	0.442

SERIAL NUMBER: C6348717.__0
TARGET NUMBER: 1
FILE DATE: 03/24/2005
FILE TIME: 09:04

X CENTROID:	-0.108
Y CENTROID:	-0.237
POA TO CENTROID:	0.261
HORZ SPREAD:	2.415
VERT SPREAD:	2.245
GROUP SPREAD:	2.674
MIN RADIUS:	0.302
MAX RADIUS:	1.553
MEAN RADIUS:	0.905
# IN 1 IN DIAMETER:	3
# IN 2 IN DIAMETER:	6
# in 3 IN DIAMETER:	9

POINT#	X	Y
1:	0.559	-1.206
2:	-0.161	-1.171
3:	0.984	0.096
4:	0.051	0.019
5:	-0.125	0.195
6:	-0.556	0.630
7:	-0.159	1.039
8:	-0.046	0.162
9:	-0.196	-1.086
10:	-1.431	-1.051



TARGET APPROX 1/2 SCALE

SERIAL NUMBER: C6348717.__0
TARGET NUMBER: 2
FILE DATE: 03/24/2005
FILE TIME: 09:04

X CENTROID:	-0.147
Y CENTROID:	0.216
POA TO CENTROID:	0.262
HORZ SPREAD:	2.666
VERT SPREAD:	2.321
GROUP SPREAD:	2.688
MIN RADIUS:	0.827
MAX RADIUS:	1.603
MEAN RADIUS:	1.122
# IN 1 IN DIAMETER:	0
# IN 2 IN DIAMETER:	5
# in 3 IN DIAMETER:	8

POINT#	X	Y
1:	0.717	0.327
2:	1.339	0.816
3:	0.304	1.094
4:	-0.492	1.250
5:	-0.680	0.849
6:	-1.327	1.163
7:	-0.044	-0.833
8:	-0.288	-0.747
9:	-0.431	-0.687
10:	-0.573	-1.071



TARGET APPROX 1/2 SCALE

SERIAL NUMBER: C6348717.__0
TARGET NUMBER: 3
FILE DATE: 03/24/2005
FILE TIME: 09:04

X CENTROID:	0.048
Y CENTROID:	0.048
POA TO CENTROID:	0.067
HORZ SPREAD:	1.312
VERT SPREAD:	2.184
GROUP SPREAD:	2.187
MIN RADIUS:	0.386
MAX RADIUS:	1.156
MEAN RADIUS:	0.764
# IN 1 IN DIAMETER:	1
# IN 2 IN DIAMETER:	8
# in 3 IN DIAMETER:	10

POINT#	X	Y
1:	0.822	-0.296
2:	0.491	-0.328
3:	0.022	-1.108
4:	-0.326	-0.672
5:	-0.281	-0.155
6:	-0.490	-0.076
7:	0.451	0.613
8:	0.297	0.979
9:	-0.101	1.076
10:	-0.410	0.445



TARGET APPROX 1/2 SCALE

SERIAL NUMBER: C6348717.__0
TARGET NUMBER: 4
FILE DATE: 03/24/2005
FILE TIME: 09:04

X CENTROID:	-0.003
Y CENTROID:	0.419
POA TO CENTROID:	0.419
HORZ SPREAD:	2.588
VERT SPREAD:	2.622
GROUP SPREAD:	3.018
MIN RADIUS:	0.230
MAX RADIUS:	1.513
MEAN RADIUS:	1.104
# IN 1 IN DIAMETER:	1
# IN 2 IN DIAMETER:	3
# in 3 IN DIAMETER:	8

POINT#	X	Y
1:	1.161	0.117
2:	0.881	-0.809
3:	0.287	-0.095
4:	0.226	-0.815
5:	-0.585	-0.029
6:	-1.427	0.581
7:	-0.862	1.655
8:	0.175	1.579
9:	0.186	1.807
10:	-0.068	0.198



TARGET APPROX 1/2 SCALE

SERIAL NUMBER: C6348717.__0
TARGET NUMBER: 5
FILE DATE: 03/24/2005
FILE TIME: 09:04

X CENTROID:	-0.230
Y CENTROID:	0.188
POA TO CENTROID:	0.297
HORZ SPREAD:	2.481
VERT SPREAD:	3.443
GROUP SPREAD:	4.153
MIN RADIUS:	0.526
MAX RADIUS:	2.565
MEAN RADIUS:	1.115
# IN 1 IN DIAMETER:	0
# IN 2 IN DIAMETER:	4
# in 3 IN DIAMETER:	8

POINT#	X	Y
1:	0.763	-0.608
2:	0.645	-1.138
3:	-0.156	-0.505
4:	-0.228	-0.338
5:	0.803	0.289
6:	0.247	0.487
7:	-0.145	0.822
8:	-1.204	0.683
9:	-1.352	-0.121
10:	-1.678	2.305



TARGET APPROX 1/2 SCALE

M-24 INSPECTION CHECKLIST
CONTRACT #: DAAE-20-02-D-0127

R & E NUMBER	92984		
SERIAL NUMBER	C6348717		
LOG-IN DATE	2-11-05		
INSPECT AND VERIFY:			
OPERATION #	OPERATION NAME	DATE	INITIAL
550	DIS-ASSEMBLE GUN	2-18-05	RTL
560 A	RE-BARREL	2-22-05	RTL
B	DRILL AND TAP	2-28-05	TRW
575	ASSEMBLE	2-23-05	RTL
600	PROOF	2-24-05	AC
605	CHECK HEADSPACE	2-24-05	AC
610	DIS-ASSEMBLE GUN	2-24-05	RTL
612	MAGNAFLUX		
615	ROLLMARK CALIBER	3-1-05	CW
618	ROTO-BLAST	3-3-05	LB
620	APPLY COATINGS	3/16/05	
625 A	FINAL ASSEMBLY	3-23-05	RTL
B	TRIGGER PULL TEST		
C	SAFETY "ON" FORCE	3-28-05	
D	SAFETY "OFF" FORCE	3-28-05	AC
E	FIRING PIN INDENT	3-28-05	AC
640	TARGET	3-24-05	TRW
655	FINAL INSPECT	3-28-05	AC
660	PACK	4-25-05	DM
		SHIP DATE	
	QAR INSPECTION DATE		

MAGNA-FLUX INSPECTED MAR 0 4 2005 OPERATOR

CONTRACT # DAAA21-87-C-0086

GUN SERIAL # C6348717

OP. #	OP. NAME	READINGS	DATE	INIT
575 & 580	Assemble Action and Stock	9 26	89	RW
600	Proof	9 26	89	RW
607	Check Headspace	9 26	89	RW
610	Dis-assemble Gun	9 26	89	RW
612	Magnaflux Barrel Action	9/29/89		KCR
	Magnaflux Bolt	9/29/89		KCR
615	Rollmark Caliber	9/29/89		LA
7	Drill and Tap Sight Holes	9 29	89	LB
618	Polish Barrel LB	9 29	89	BT
620	Apply Coatings (Barrel Action)		10-1-89	KSH
	Apply Coating (Bolt)		10-1-89	KSH
625	Final Assembly A) Clean inside of Bolt Assembly		10/12/89	RW
	B) Inspect Rear Firing Pin Hole for Chamfer in Bolt Head		10/12/89	RW
	C) Inspect Ejector Hole for Chamfer		10/12/89	RW
	D) Oil Firing Pin Ass'y		10/12/89	RW
	E) Adjust Trigger Pull to Min Setting and Stake		10/17/89	DB

CONFIDENTIAL-SUBJECT TO PROTECTIVE ORDER

op. #	OP. NAME	READINGS			DATE	INIT
625 cont.	F) Safety On Force	6	6	6	10/17/89	JH
	G) Safety Off Force	3	3	3	10/17/89	JH
	H) Trigger Pull Test & Retainability				17Oct89	JSS
	I) Firing Pin Indent	.020	.022	.021	10/17/89	JH
	J) Assemble Stock				10/18/89	RW
	K) Assemble Swivel Studs				19Oct89	JSS
	L) Attach Front and Rear Sight Assemblies				12/11/89	RW
	M) Iron Sight Alignment				12/11/89	RW
	N) Detach Front & Rear Sights & place in numbered container				12/11/89	RW
	O) Attach Scope to Rifle				18Oct89	JSS
	P) Detach & Attach Scope 20 Times				18Oct89	JSS
640	Gallery Target & Test				10-18-89	DH
	A) Time				10-18-89	DH
	B) Malfunctions				10-18-89	DH
	C) Pierced Primers				10-18-89	DH
	D) Optical Clearity of Scope				10-18-89	DH
645	Inspect for Live Ammo				10-18-89	DH
655	Final Inspection A) Headspace				19Oct89	JSS
	B) Trigger Pull	258	259	245	253 247	19Oct89 JSS
	C) Function				19Oct89	JSS
660	Pack				15Dec89	JSS

SWS TRIGGER PULL TEST

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS
2.50# ± .50#
3.00# ± .75#
4.00# ± 1.00#

SERIAL NO. 6348719

DATE 3-13-90

TESTER

	2.50# INITIAL	2.50# AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50#		COMMENTS
PULL #1	2.50	2.29	2.46		MIN. SETTING, NO AVG. OF 5 READINGS ACCEPTABLE LESS THAN 2#
PULL #2	2.54	2.55	2.45		
PULL #3	2.54	2.46	2.40		
PULL #4	2.55	2.40	2.43		
PULL #5	2.50	2.43	2.51		
TOTAL	12.63	12.13	12.25		
AVG.	2.526	2.426	2.45		

	3.00# INITIAL	3.00# AFTER 20 CYCLES		COMMENTS
PULL #1	3.16	3.37		
PULL #2	3.44	3.50		
PULL #3	3.41	3.45		
PULL #4	3.40	3.47		
PULL #5	3.51	3.40		
TOTAL	16.92	17.19		
AVG.	3.384	3.438		

	4.00# INITIAL	4.00# AFTER 20 CYCLES	MAX SETTING GREATER THAN 4#	RESET TO 4# FOR TARGET & ACCURACY
PULL #1	4.29	4.48		
PULL #2	4.31	4.40		
PULL #3	4.40	4.31		
PULL #4	4.46	4.31		
PULL #5	4.41	4.40		
TOTAL	21.87	21.90		
AVG.	4.374	4.382		

CENTROIDAL DISTANCE CALCULATIONS
FOR RIFLE # C6348717
18 Oct 1989

CENTROIDAL DISTANCES

0	TO	1	.592611
1	TO	2	.316811
1	TO	3	.630451
1	TO	4	.291433
1	TO	5	.300613



THE AVERAGE X-COORDINATE FOR THIS RIFLE IS: .511
THE AVERAGE Y-COORDINATE FOR THIS RIFLE IS: -.076
THE RESULTING AVERAGE POI RADIUS FOR THIS RIFLE IS: .516621

THE AMR FOR THIS RIFLE IS: .9772



PATTERN #	:	1		
SHOTS (BEST OF)	:	10	9	8
MAXIMUM X	:	.938	.982	1.079
MINIMUM X	:	-1.328	-1.284	-1.187
MAXIMUM Y	:	1.481	.911	.786
MINIMUM Y	:	-1.164	-.999	-1.029
CENTROID X	:	.562	.518	.421
CENTROID Y	:	.188	.023	.148
POA TO CENTROID in.	:	.592	.518	.446
MIN RADIUS	:	.261	.297	.277
MEAN RADIUS	:	.962	.909	.843
MAX RADIUS	:	1.534	1.284	1.307
HORIZONTAL SPREAD	:	2.266	2.266	2.266
VERTICAL SPREAD	:	2.645	1.910	1.815
EXTREME SPREAD	:	2.666	2.463	2.336
NUMBER IN ONE INCH CIRCLE	=		2	
NUMBER IN TWO INCH CIRCLE	=		4	
NUMBER IN THREE INCH CIRCLE	=		9	



PATTERN #	:	2		
SHOTS (BEST OF)	:	10	9	8
MAXIMUM X	:	1.549	.676	.546
MINIMUM X	:	-1.210	-1.038	-.629
MAXIMUM Y	:	1.020	.732	.597
MINIMUM Y	:	-1.192	-1.079	-.660
CENTROID X	:	.307	.135	.265
CENTROID Y	:	.000	-.113	.022
POA TO CENTROID in.	:	.307	.176	.266
MIN RADIUS	:	.208	.389	.253
MEAN RADIUS	:	.751	.648	.501
MAX RADIUS	:	1.854	1.497	.708
HORIZONTAL SPREAD	:	2.759	1.714	1.175
VERTICAL SPREAD	:	2.212	1.811	1.257
EXTREME SPREAD	:	3.536	2.108	1.258
NUMBER IN ONE INCH CIRCLE	=		3	
NUMBER IN TWO INCH CIRCLE	=		8	
NUMBER IN THREE INCH CIRCLE	=		8	



PATTERN #	:	3		
SHOTS (BEST OF)	:	10	9	8
MAXIMUM X	:	.899	.774	.631
MINIMUM X	:	-1.125	-1.144	-.631
MAXIMUM Y	:	1.204	1.257	1.154
MINIMUM Y	:	-1.118	-.984	-1.087
CENTROID X	:	.792	.917	1.060
CENTROID Y	:	-.399	-.533	-.430
POA TO CENTROID in.	:	.887	1.061	1.144
MIN RADIUS	:	.205	.165	.076
MEAN RADIUS	:	.882	.788	.675
MAX RADIUS	:	1.647	1.409	1.157
HORIZONTAL SPREAD	:	2.023	1.918	1.261
VERTICAL SPREAD	:	2.322	2.241	2.241
EXTREME SPREAD	:	2.762	2.398	2.242
NUMBER IN ONE INCH CIRCLE	=		3	
NUMBER IN TWO INCH CIRCLE	=		5	
NUMBER IN THREE INCH CIRCLE	=		9	



PATTERN #	:	4		
SHOTS (BEST OF)	:	10	9	8
MAXIMUM X	:	1.429	1.123	1.139
MINIMUM X	:	-.873	-.714	-.698
MAXIMUM Y	:	1.095	1.206	1.017
MINIMUM Y	:	-1.627	-1.515	-.918
CENTROID X	:	.460	.301	.284
CENTROID Y	:	-.085	-.196	-.007
POA TO CENTROID in.	:	.468	.360	.285
MIN RADIUS	:	.855	.700	.724
MEAN RADIUS	:	1.107	1.006	.937
MAX RADIUS	:	1.749	1.520	1.141
HORIZONTAL SPREAD	:	2.302	1.837	1.837
VERTICAL SPREAD	:	2.721	2.721	1.985
EXTREME SPREAD	:	3.009	2.757	2.035
NUMBER IN ONE INCH CIRCLE	=		0	
NUMBER IN TWO INCH CIRCLE	=		6	
NUMBER IN THREE INCH CIRCLE	=		8	



PATTERN #	:	5		
SHOTS (BEST OF)	:	10	9	8
MAXIMUM X	:	1.586	1.365	1.048
MINIMUM X	:	-1.989	-1.470	-1.300
MAXIMUM Y	:	.785	.779	.777
MINIMUM Y	:	-.815	-.821	-.823
CENTROID X	:	.434	.655	.485
CENTROID Y	:	-.084	-.078	-.076
POA TO CENTROID in.	:	.442	.660	.491
MIN RADIUS	:	.764	.785	.780
MEAN RADIUS	:	1.184	1.078	1.033
MAX RADIUS	:	1.990	1.506	1.340
HORIZONTAL SPREAD	:	3.575	2.835	2.348
VERTICAL SPREAD	:	1.600	1.600	1.600
EXTREME SPREAD	:	3.575	2.856	2.496
NUMBER IN ONE INCH CIRCLE	=		0	
NUMBER IN TWO INCH CIRCLE	=		3	
NUMBER IN THREE INCH CIRCLE	=		8	

CONFIDENTIAL-SUBJECT TO PROTECTIVE ORDER

BARBER - M24 00062235

Remington®

DUPONT
REG. U.S. PAT. & TM. OFF.

VERY IMPORTANT: Instruction Book enclosed to assure safe use of this firearm.

MODEL 700™ M24

SERIAL NO. C6348717

ORDER NO. 5716

MADE IN ILION, N.Y. U.S.A. Reg. U.S. Pat & Tm. Off, Marca Registrada Marque Deposee.

01

5716 C6348717

UPC

0 47700 25716 7

BARBER - M24 00062274