

## CONFIDENTIAL

Remington Arms Company Inc.  
Research & Development Technical Center  
315 West Ring Road  
Elizabethtown, KY 42701

## Trial &amp; Pilot Clean &amp; Inspect Checklist

Model: 710 Magnum

Project: 241314

Rifle: 4-30

TLW #: TLW1303

Date: 01 / 20 / 04Inspector: JS/BLRound Level: 222☒ Measure Headspace min  $\pm$  .004☒ Sear Engagement: 1<sup>st</sup>. 0292 2<sup>nd</sup>. 0279 3<sup>rd</sup>. 0277Ave. 0282 spec- .020" to .025"☒ Trigger Pull: 1<sup>st</sup>. 4.801 2<sup>nd</sup>. 4.858 3<sup>rd</sup>. 4.733Ave. 4.791 spec- 4 lb. to 5.5 lb.☒ Check Take-Down Screws and Re-tighten if necessary.☒ Inspect extractor & bolt face area. Some wear on bolt face☒ Inspect cam surface, locking lugs and bolt stop for signs of excessivewear: Locking lugs some wear, Bolt stop worn☒ Inspect stock for any signs of cracking or other failure.☒ Other items ofnote: magazine Box protruding

TLW1303

Remington Confidential

ET21370