

G6784552

M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO
WITH BIPOD

proof of purchase




owner registration sticker



ORDER NO.	86470
BARREL LENGTH	24"
CAPACITY	6

G6784552

UPC



BM FORM

GUN SERIAL # G6784552

OP #	OPERATION NAME	READINGS	DATE	INITIAL
420	ASSEMBLE ACTION		9-19-08	SP
430	ASSEMBLE TO STOCK		9-19-08	SP
440	PROOF		9-19-08	SP
460	CHECK HEADSPACE		9-19-08	SP
470	DIS-ASSEMBLE ACTION		9-19-08	SP
472	SERIALIZE BOLT HANDLE		9-20-08	SP
475	DRILL AND TAP SIGHT HOLES	MAGNA-FLUX SEP 22 2008	9-20-08	SP
480	MAGNAFLUX BBL ACTION	OPERATOR <u>BM</u>	9-22-08	BM
490	MAGNAFLUX BOLT		9/19/08	OR
500	ROLLMARK CALIBER		9/22/08	RT
520	GOFF BLAST BBL / REC		9/22/08	DS
542	APPLY COATINGS (BARREL ACTION)		9-27	
545	(BOLT)			
560	RE-ASSEMBLE ACTION			
	A) CLEAN INSIDE OF BOLT ASSEMBLY		9-29-08	SP
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		9-29-08	SP
	C) INSPECT EJECTOR HOLE FOR CHAMFER		9-29-08	SP
	D) OIL FIRING PIN ASSEMBLY		10-9-08	PM
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE 2.50 LBS +/- .5 LBS			

F004 REV 5/2006

OP #	OPERATION NAME	READINGS	DATE	INITIAL
560	F) SAFETY ON FORCE 2 LBS MIN 10 LBS MAX	<u>50</u> <u>50</u> <u>50</u>	10-23-08	L. D.
CONT.				
	G) SAFETY OFF FORCE 2 LBS MIN	<u>60</u> <u>50</u> <u>50</u>	10-23-08	L. D.
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT .020 MIN	<u>.024</u> <u>.023</u> <u>.023</u>	10-23-08	L. D.
	J) ASSEMBLE STOCK		10-9-08	LSW
	K) ASSEMBLE SWIVEL STUDS		10-23-08	L. D.
	L) ATTACH FRONT AND REAR SIGHT ASSY'S			
	M) IRON SIGHT ALIGNMENT			
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER			
640 & 650	FUNCTION TEST AND TARGET	<u>PASS</u> FAIL <u>PASS</u> FAIL	10-13-08	L. D.
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
660	INSPECT FOR LIVE AMMO		10-13-08	TL
670	FINAL INSPECTION A) HEADSPACE		10-23-08	L. D.
	B) TRIGGER PULL +/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	<u>2.75</u> <u>2.75</u> <u>2.78</u> <u>2.74</u> <u>2.75</u>	10-20-08	TL
	C) FUNCTION		10-23-08	L. D.
690	PACK		12-10-08	TL

F004 REV 5/2006

BARBER - M24 0067637

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50 LBS (plus or minus 0.50 LBS)

3.00 LBS (plus or minus 0.75 LBS)

4.00 LBS (plus or minus 1.00 LBS)

DATE

TESTER

TAT
10-15

	2.50 LBS INITIAL	2.50 LBS AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50 LBS	COMMENTS
PULL #1	259	244	245	
PULL #2	268	254	236	
PULL #3	252	263	232	
PULL #4	255	248	229	
PULL #5	268	253	230	
TOTAL	1302	1262	1172	
AVERAGE	260	252	234	

	3.00 LBS INITIAL	3.00 LBS AFTER 20 CYCLES	COMMENTS
PULL #1	324	312	
PULL #2	320	314	
PULL #3	331	304	
PULL #4	317	307	
PULL #5	316	306	
TOTAL	1608	1543	
AVERAGE	322	309	

	4.00 LBS INITIAL	4.00 LBS AFTER 20 CYCLES	MAX SETTING GREATER THAN 4 LBS	RESET TO 4 LBS FOR TARGET & ACCURACY
PULL #1	432	419		440
PULL #2	415	410		438
PULL #3	424	399		442
PULL #4	416	418		436
PULL #5	416	414		424
TOTAL	2103	2060		2180
AVERAGE	421	412		436