

G6784563

M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO

- INSTRUCTION BOOK 3518

proof of purchase



owner registration sticker



BM FORM


ORDER NO. **25716**

BARREL LENGTH **24"**

CAPACITY **6**

G6784563

UPC



GUN SERIAL # G 678 4563

OP #	OPERATION NAME	READINGS	DATE	INITIAL
420	ASSEMBLE ACTION		9-29-08	SPD.
430	ASSEMBLE TO STOCK		9-29-08	SP
440	PROOF		9-29-08	SPD.
460	CHECK HEADSPACE		9-29-08	SPD.
470	DIS-ASSEMBLE ACTION		9-29-08	SPD.
472	SERIALIZE BOLT HANDLE	FLUX	9-30-08	RTZ
475	DRILL AND TAP SIGHT HOLES	007 02 100	9-30-08	SP
480	MAGNAFLUX BBL ACTION	OPERAT (R)	10/2/08	(R)
490	MAGNAFLUX BOLT			
500	ROLLMARK CALIBER		10/2/08	RT
520	GOFF BLAST BBL / REC		10-3-08	DK
542	APPLY COATINGS (BARREL ACTION)		10 9	✓
545	(BOLT)			
560	RE-ASSEMBLE ACTION			
	A) CLEAN INSIDE OF BOLT ASSEMBLY		10-9-08	SP
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		10-9-08	SP
	C) INSPECT EJECTOR HOLE FOR CHAMFER		10-9-08	SP
	D) OIL FIRING PIN ASSEMBLY		10-31-08	SPD.
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE 2.50 LBS +/- .5 LBS			

F004 REV 5/2006


OP #	OPERATION NAME	READINGS	DATE	INITIAL
560	F) SAFETY ON FORCE 2 LBS MIN 10 LBS MAX	<u>40</u> <u>40</u> <u>30</u>	11-6-08	R. D.
CONT.	G) SAFETY OFF FORCE 2 LBS MIN	<u>50</u> <u>50</u> <u>50</u>	11-6-08	R. D.
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT .020 MIN	<u>-.023</u> <u>-.023</u> <u>-.023</u>	11-6-08	R. D.
	J) ASSEMBLE STOCK		10-31-08	L.P.A.
	K) ASSEMBLE SWIVEL STUDS		11-6-08	R. D.
	L) ATTACH FRONT AND REAR SIGHT ASSY'S			
	M) IRON SIGHT ALIGNMENT			
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER			
640 & 650	FUNCTION TEST AND TARGET	<u>PASS</u> FAIL <u>PASS</u> FAIL	11-3-08	R. D.
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
660	INSPECT FOR LIVE AMMO		11-3-08	TC
670	FINAL INSPECTION A) HEADSPACE		11-6-08	R. D.
	B) TRIGGER PULL +/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	<u>2.35</u> <u>2.42</u> <u>2.31</u> <u>2.38</u> <u>2.43</u>	11-5-08	Fm
	C) FUNCTION		11-6-08	R. D.
690	PACK		11/7/08	Fm

F004 REV 5/2006

Trigger Profile [lbs,inch]

Profile: SWS
 GunType: Rifle
 Make: Remington
 Note: C. Schults 10/28/2008

Model: M/24
 Serial No: Form #F005
 Trigger: 2.5 lbs ini +/- .50 lbs




#	Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
1	2.352	0.053	0.033	0.034	0.050		Set Trigger
2	2.306	0.053	0.033	0.034	0.050		Set Trigger
3	2.384	0.052	0.033	0.034	0.051		Set Trigger
4	2.480	0.052	0.033	0.034	0.050		Set Trigger
5	2.320	0.053	0.033	0.034	0.048		Set Trigger

A-236

Trigger Profile [lbs,inch]

Profile SWS
 GunType: Rifle
 Make: Remington
 Note: C. Schultz 10/28/2008

Model: M/24
 Serial No: Form #F005
 Trigger: 2.5 lbs after 50 cycles+/- .50 lbs




#	Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
1	2.429	0.050	0.032	0.034	0.050		Set Trigger
2	2.558	0.051	0.031	0.033	0.053		Set Trigger
3	2.553	0.050	0.030	0.033	0.052		Set Trigger
4	2.550	0.050	0.030	0.033	0.052		Set Trigger
5 ±	2.409	0.051	0.031	0.034	0.050		Set Trigger

A-2-S-0

Trigger Profile [lbs,inch]

Profile SWS
GunType: Rifle
Make: Remington
Note: C. Schults 10/28/2008

Model: M/24
Serial No: Form #F005
Trigger: 3.0 lbs ini +/- .75 lbs




#	Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
1	3.459	0.050	0.027	0.031	0.073		Set Trigger
2	3.347	0.051	0.028	0.031	0.072		Set Trigger
3	3.340	0.051	0.028	0.031	0.074		Set Trigger
4	3.394	0.050	0.026	0.031	0.072		Set Trigger
5	3.519	0.050	0.028	0.031	0.074		Set Trigger

A 3.41

Trigger Profile [lbs,inch]

Profile SWS
GunType: Rifle
Make: Remington
Note: C. Schults 10/28/2008

Model: M/24
Serial No: Form #F005
Trigger: 3.0 lbs after 20 cycles+/- .75 lbs




#	Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
1	3.377	0.049	0.028	0.030	0.072		Set Trigger
2	3.426	0.050	0.028	0.030	0.073		Set Trigger
3	3.489	0.050	0.027	0.030	0.071		Set Trigger
4	3.398	0.050	0.028	0.030	0.073		Set Trigger
5	3.493	0.050	0.027	0.030	0.073		Set Trigger

A-3-43

Trigger Profile [lbs,inch]

Profile SWS
 GunType: Rifle
 Make: Remington
 Note: C. Schults 10/28/2008

Model: M/24
 Serial No: Form #F005
 Trigger: 4.0 lbs ini +/- 1.0 lbs




#	Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
1	4.497	0.051	0.025	0.021	0.102		Set Trigger
2	4.453	0.050	0.027	0.023	0.096		Set Trigger
3	4.383	0.050	0.027	0.023	0.093		Set Trigger
4	4.275	0.051	0.027	0.023	0.096		Set Trigger
5	4.462	0.051	0.025	0.023	0.098		Set Trigger

A-441

Trigger Profile [lbs,inch]

Profile SWS
 GunType: Rifle
 Make: Remington
 Note: C. Schultz 10/28/2008

Model: M/24
 Serial No: Form #F005
 Trigger: 4.0 lbs after 20 cycles+/- 1.0 lbs




#	Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
1	4.286	0.050	0.027	0.028	0.095		Set Trigger
2	4.312	0.050	0.027	0.028	0.096		Set Trigger
3	4.320	0.050	0.025	0.029	0.093		Set Trigger
4	4.347	0.050	0.026	0.029	0.093		Set Trigger
5	4.281	0.051	0.027	0.029	0.098		Set Trigger

A-4.30

Trigger Profile [lbs,inch]

Profile: SWS
 GunType: Rifle
 Make: Remington
 Note: C. Schults 10/28/2008

Model: M/24
 Serial No: Form #F005
 Trigger: reset to 2.5 lbs +/- .50 lbs




#	Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
1	2.433	0.049	0.030	0.032	0.049		Set Trigger
2	2.256	0.048	0.031	0.033	0.044		Set Trigger
3	2.413	0.049	0.030	0.032	0.049		Set Trigger
4	2.340	0.049	0.030	0.032	0.047		Set Trigger
5	2.291	0.049	0.029	0.032	0.048		Set Trigger

A-2.34

Trigger Profile [lbs,inch]

Profile SWS
 GunType: Rifle
 Make: Remington
 Note: C. Schults 10/28/2008

Model: M/24
 Serial No: Form #F005
 Trigger: set to 4.0 lbs +/- 1.0 lbs for target & accuracy



#	Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
1	4.155	0.055	0.031	0.030	0.093		Set Trigger
2	4.096	0.054	0.030	0.030	0.092		Set Trigger
3	4.185	0.054	0.028	0.030	0.095		Set Trigger
4	4.150	0.055	0.031	0.030	0.095		Set Trigger
5	4.123	0.054	0.030	0.030	0.092		Set Trigger

A-4.14