

56784610

M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO
WITH BIPOD

proof of purchase



owner registration sticker




ORDER NO. 86470

BARREL LENGTH 24"

CAPACITY 6

G6784610

UPC



BM FORM

GUN SERIAL #

G 6784610

OP #	OPERATION NAME	READINGS	DATE	INITIAL
420	ASSEMBLE ACTION		9-5-08	SPD
430	ASSEMBLE TO STOCK		9-6-08	TC
440	PROOF		9-6-08	TC
460	CHECK HEADSPACE		9-6-08	TC
470	DIS-ASSEMBLE ACTION		9-6-08	SPD
472	SERIALIZE BOLT HANDLE	MAGNA - FLUX	9-8-08	RT
475	DRILL AND TAP SIGHT HOLES	SEP 09 2008	9-8-08	SP
480	MAGNAFLUX BBL ACTION	OPERATOR BM	9-9-08	BM
490	MAGNAFLUX BOLT		9/6/08	MR
500	ROLLMARK CALIBER		9/9/08	RT
520	GOFF BLAST BBL / REC		9/10/08	DS
542	APPLY COATINGS (BARREL ACTION)		9/13	C
545	(BOLT)			
560	RE-ASSEMBLE ACTION			
	A) CLEAN INSIDE OF BOLT ASSEMBLY		9-24-08	SP
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		9-24-08	SP
	C) INSPECT EJECTOR HOLE FOR CHAMFER		9-24-08	SP
	D) OIL FIRING PIN ASSEMBLY		9-27-08	PSN
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE	2.50 LBS +/- .5 LBS		

F004 REV 5/2006

OP #	OPERATION NAME	READINGS	DATE	INITIAL
560	F) SAFETY ON FORCE 2 LBS MIN 10 LBS MAX	<u>2.5</u> <u>2.5</u> <u>2.5</u>	10-1-08	ZJH
CONT.	G) SAFETY OFF FORCE 2 LBS MIN	<u>4.0</u> <u>4.0</u> <u>4.0</u>	10-1-08	ZJH
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT .020 MIN	<u>.024</u> <u>.024</u> <u>.027</u>	10-1-08	XJH
	J) ASSEMBLE STOCK		9/27/08	TRW
	K) ASSEMBLE SWIVEL STUDS		10-1-08	XJH
	L) ATTACH FRONT AND REAR SIGHT ASSY'S			
	M) IRON SIGHT ALIGNMENT			
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER			
640 & 650	FUNCTION TEST AND TARGET	<u>PASS</u> <u>FAIL</u> <u>PASS</u> <u>FAIL</u>	9-29-08	XJH
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
660	INSPECT FOR LIVE AMMO		9-29-08	TRW
670	FINAL INSPECTION A) HEADSPACE		10-1-08	XJH
	B) TRIGGER PULL +/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	<u>2.57</u> <u>2.48</u> <u>2.49</u> <u>2.50</u> <u>2.60</u>	9/30/08	FM
	C) FUNCTION		10-1-08	XJH
690	PACK		12/3/08	FM

F004 REV 5/2006

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50 LBS (plus or minus 0.50 LBS)

3.00 LBS (plus or minus 0.75 LBS)

4.00 LBS (plus or minus 1.00 LBS)

DATE

9-25-08

TESTER

TAE

	2.50 LBS INITIAL	2.50 LBS AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50 LBS		COMMENTS
PULL #1	247	266		223	
PULL #2	247	245		209	
PULL #3	251	246		217	
PULL #4	243	248		212	
PULL #5	235	246		224	
TOTAL	1223	1251		1085	
AVERAGE	244	250		217	

	3.00 LBS INITIAL	3.00 LBS AFTER 20 CYCLES		COMMENTS
PULL #1	356	341		
PULL #2	355	359		
PULL #3	342	351		
PULL #4	344	339		
PULL #5	331	334		
TOTAL	1728	1722		
AVERAGE	345	344		

	4.00 LBS INITIAL	4.00 LBS AFTER 20 CYCLES	MAX SETTING GREATER THAN 4 LBS	RESET TO 4 LBS FOR TARGET & ACCURACY
PULL #1	434	430		457
PULL #2	437	435		440
PULL #3	423	425		426
PULL #4	424	429		434
PULL #5	426	430		432
TOTAL	2144	2149		2189
AVERAGE	428	429		437