

G6784634

M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO
WITH BIPOD

proof of purchase



owner registration sticker




ORDER NO. **86470**

BARREL LENGTH **24"**

CAPACITY **6**

G6784634

UPC



BM FORM

INSPECTION CHECKLIST-NEW GUNS

GUN SERIAL #

G 6784634

OP #	OPERATION NAME	READINGS	DATE	INITIAL
420	ASSEMBLE ACTION		8-28-08	SP
430	ASSEMBLE TO STOCK		8-28-08	SP
440	PROOF		8-28-08	SP
460	CHECK HEADSPACE		8-28-08	SP
470	DIS-ASSEMBLE ACTION		8-28-08	SP
472	SERIALIZE BOLT HANDLE	MAGNA-FLUX	8-29-08	Rsn
475	DRILL AND TAP SIGHT HOLES	2008	8-29-08	SP
480	MAGNAFLUX BBL ACTION	OPERATOR B4	9-2-08	B4
490	MAGNAFLUX BOLT		8/28/08	MR
500	ROLLMARK CALIBER		9/3/08	RT
520	GOFF BLAST BBL / REC		9/10/08	DB
542	APPLY COATINGS (BARREL ACTION)		9 9	c
545	(BOLT)			
560	RE-ASSEMBLE ACTION			
	A) CLEAN INSIDE OF BOLT ASSEMBLY		9-18-08	SP
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		9-18-08	SP
	C) INSPECT EJECTOR HOLE FOR CHAMFER		9-18-08	SP
	D) OIL FIRING PIN ASSEMBLY		10-1-08	Rsn
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE	2.50 LBS +/- .5 LBS		

F004 REV 5/2006

OP #	OPERATION NAME	READINGS	DATE	INITIAL
560	BARBER - M24 0068545 F) SAFETY ON FORCE 2 LBS MIN 10 LBS MAX	<u>4.0</u> <u>4.0</u> <u>4.0</u>	10-20-08	Z.P.
CONT.	G) SAFETY OFF FORCE 2 LBS MIN	<u>3.0</u> <u>3.0</u> <u>3.0</u>	10-20-08	Z.P.
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT .020 MIN	<u>.023</u> <u>.023</u> <u>.023</u>	10-20-08	Z.P.
	J) ASSEMBLE STOCK		10-1-08	Rgn
	K) ASSEMBLE SWIVEL STUDS		10-20-08	Z.P.
	L) ATTACH FRONT AND REAR SIGHT ASSY'S			
	M) IRON SIGHT ALIGNMENT			
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER			
640 & 650	FUNCTION TEST AND TARGET	<u>PASS</u> FAIL <u>PASS</u> FAIL	10-2-08	TC
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION <i>N/A</i>		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
660	INSPECT FOR LIVE AMMO		10-2-08	Z.P.
670	FINAL INSPECTION A) HEADSPACE		10-20-08	Z.P.
	B) TRIGGER PULL +/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	<u>2.63</u> <u>2.52</u> <u>2.42</u> <u>2.45</u> <u>2.40</u>	10/2/08	Fm
	C) FUNCTION		10-20-08	Z.P.
690	PACK		12-8-08	TC

F004 REV 5/2006

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50 LBS (plus or minus 0.50 LBS)
 3.00 LBS (plus or minus 0.75 LBS)
 4.00 LBS (plus or minus 1.00 LBS)

DATE

9-24-08

TESTER

TAE

	2.50 LBS INITIAL	2.50 LBS AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50 LBS		COMMENTS
PULL #1	284	268		207	
PULL #2	285	254		226	
PULL #3	228	256		234	
PULL #4	265	254		218	
PULL #5	279	247		233	
TOTAL	1341	1279		1118	
AVERAGE	268	255		223	

	3.00 LBS INITIAL	3.00 LBS AFTER 20 CYCLES		COMMENTS
PULL #1	342	337		
PULL #2	347	359		
PULL #3	352	339		
PULL #4	363	326		
PULL #5	358	352		
TOTAL	1762	1711		
AVERAGE	352	342		

	4.00 LBS INITIAL	4.00 LBS AFTER 20 CYCLES	MAX SETTING GREATER THAN 4 LBS	RESET TO 4 LBS FOR TARGET & ACCURACY
PULL #1	447	449		425
PULL #2	443	454		425
PULL #3	419	449		425
PULL #4	447	450		430
PULL #5	447	448		428
TOTAL	2203	2250		2133
AVERAGE	440	450		426