

G6784637

M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO
WITH BIPOD

proof of purchase




owner registration sticker



ORDER NO.	86470
BARREL LENGTH	24"
CAPACITY	6

G6784637

UPC



BM FORM

INSPECTION CHECKLIST-NEW GUNS

GUN SERIAL # G 6784637

OP #	OPERATION NAME	READINGS	DATE	INITIAL
410	SERIALIZE BOLT HANDLE		8-29-08	RTZ
420	ASSEMBLE ACTION		8-28-08	SP
430	ASSEMBLE TO STOCK		8-28-08	SP
440	PROOF		8-28-08	SP
460	CHECK HEADSPACE		8-28-08	SP
470	DIS-ASSEMBLE ACTION	MAGNA - FLUX	8-28-08	SP
480	MAGNAFLUX BBL ACTION	SEP 2 2008	9-2-08	RTZ
490	MAGNAFLUX BOLT			
500	ROLLMARK CALIBER	OPERATOR <u>RT</u>	9/3/08	RT
510	DRILL AND TAP SIGHT HOLES		8-27-08	SP
520	GOFF BLAST BBL / REC		9/4/08	DG
530 & 540	APPLY COATINGS (BARREL ACTION)		9-8	✓
	(BOLT)			
560	RE-ASSEMBLE ACTION			
	A) CLEAN INSIDE OF BOLT ASSEMBLY		9-10-08	SP
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		9-12-08	SP
	C) INSPECT EJECTOR HOLE FOR CHAMFER		9-12-08	SP
	D) OIL FIRING PIN ASSEMBLY		9-16-08	BSN
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE 2.50 LBS +/- .5 LBS			

F004 REV 5/2006

OP #	OPERATION NAME	READINGS	DATE	INITIAL
560	F) SAFETY ON FORCE 2 LBS MIN 10 LBS MAX	<u>3</u> <u>3</u> <u>3</u>	9-24-08	TL
CONT.	G) SAFETY OFF FORCE 2 LBS MIN	<u>6</u> <u>6</u> <u>6</u>	9-24-08	TL
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT .020 MIN	<u>.026</u> <u>.024</u> <u>.026</u>	9-24-08	TL
	J) ASSEMBLE STOCK		9-16-08	RSN
	K) ASSEMBLE SWIVEL STUDS		9-24-08	TL
	L) ATTACH FRONT AND REAR SIGHT ASSY'S			
	M) IRON SIGHT ALIGNMENT			
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER			
640 & 650	FUNCTION TEST AND TARGET	<u>PASS</u> FAIL <u>PASS</u> FAIL	9-18-08	FM
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
660	INSPECT FOR LIVE AMMO		9-18-08	AA
670	FINAL INSPECTION A) HEADSPACE		9-24-08	TL
	B) TRIGGER PULL +/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	<u>2.18</u> <u>2.17</u> <u>2.14</u> <u>2.07</u> <u>2.17</u>	9-19-08	TRW
	C) FUNCTION		9-24-08	TL
690	PACK		10/13/08	FM

F004 REV 5/2006

BARBER - M24 0068575
 AVERAGE PULL FORCE BETWEEN
 INITIAL & CYCLE TESTS
 2.50 LBS (plus or minus 0.50 LBS)
 3.00 LBS (plus or minus 0.75 LBS)
 4.00 LBS (plus or minus 1.00 LBS)

DATE 9-9-08
 TESTER TRW

	2.50 LBS INITIAL	2.50 LBS AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50 LBS		COMMENTS
PULL #1	2.67	2.23		2.46	
PULL #2	2.50	2.29		2.61	
PULL #3	2.58	2.26		2.40	
PULL #4	2.62	2.49		2.42	
PULL #5	2.52	2.34		2.61	
TOTAL	12.89	11.61		12.50	
AVERAGE	2.57	2.32		2.50	

	3.00 LBS INITIAL	3.00 LBS AFTER 20 CYCLES		COMMENTS
PULL #1	3.27	3.23		
PULL #2	3.31	3.26		
PULL #3	3.32	3.19		
PULL #4	3.34	3.45		
PULL #5	3.39	3.55		
TOTAL	16.63	16.68		
AVERAGE	3.32	3.33		

	4.00 LBS INITIAL	4.00 LBS AFTER 20 CYCLES	MAX SETTING GREATER THAN 4 LBS	RESET TO 4 LBS FOR TARGET & ACCURACY
PULL #1	4.54	4.05		4.11
PULL #2	4.56	4.10		4.31
PULL #3	4.56	4.11		4.37
PULL #4	4.58	4.20		4.32
PULL #5	4.45	4.36		4.34
TOTAL	22.69	20.82		21.45
AVERAGE	4.53	4.16		4.29