

G-6784649

M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO
WITH BIPOD

proof of purchase



owner registration sticker



BM FORM


ORDER NO. **86470**

BARREL LENGTH **24"**

CAPACITY **6**

G6784649

UPC



GUN SERIAL # C6784649

OP #	OPERATION NAME	READINGS	DATE	INITIAL
420	ASSEMBLE ACTION		8-25-08	L.P.D.
430	ASSEMBLE TO STOCK		8-25-08	SP
440	PROOF		8-25-08	L.P.D.
460	CHECK HEADSPACE		8-25-08	L.P.D.
470	DIS-ASSEMBLE ACTION		8-25-08	L.P.D.
472	SERIALIZE BOLT HANDLE	MAGNA-FLUX AUG 24 2008 OPERATOR B.A.	8-26-08	B.W.
475	DRILL AND TAP SIGHT HOLES		8-26-08	SP
480	MAGNAFLUX BBL ACTION		8-28-08	B.W.
490	MAGNAFLUX BOLT		8/25/08	M.R.
500	ROLLMARK CALIBER		8/25/08	R.T.
520	GOFF BLAST BBL / REC		8/25/08	D.G.
542	APPLY COATINGS (BARREL ACTION)		8-31	
545	(BOLT)			
560	RE-ASSEMBLE ACTION			
	A) CLEAN INSIDE OF BOLT ASSEMBLY		9-5-08	SP
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		9-5-08	SP
	C) INSPECT EJECTOR HOLE FOR CHAMFER		9-5-08	SP
	D) OIL FIRING PIN ASSEMBLY		9-12-08	B.W.
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE	2.50 LBS +/- .5 LBS		

F004 REV 5/2006

BARBER - M24 0068697		2 LBS MIN 10 LBS MAX	3.0	3.0	3.0	10-3-08	X. H.		
560	F) SAFETY ON FORCE								
CONT.									
	G) SAFETY OFF FORCE	2 LBS MIN	4.0	3.0	3.0	10-3-08	X. H.		
	H) TRIGGER PULL TEST AND RETAINABILITY								
	I) FIRING PIN INDENT	.020 MIN	.024	.024	.024	10-3-08	X. H.		
	J) ASSEMBLE STOCK					9-12-08	R. H.		
	K) ASSEMBLE SWIVEL STUDS					10-3-08	X. H.		
	L) ATTACH FRONT AND REAR SIGHT ASSY'S								
	M) IRON SIGHT ALIGNMENT								
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER								
640 & 650	FUNCTION TEST AND TARGET		PASS	FAIL					
			PASS	FAIL		9-15-08	F. H.		
	MALFUNCTION		CORRECTION						
	MALFUNCTION		CORRECTION	N.A.					
	MALFUNCTION		CORRECTION						
	MALFUNCTION		CORRECTION						
660	INSPECT FOR LIVE AMMO					9-15-08	TRW		
670	FINAL INSPECTION A) HEADSPACE					10-3-08	X. H.		
	B) TRIGGER PULL	+/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	2.12	2.79	2.48	2.48	2.45	10-3-08	X. H.
	C) FUNCTION					10-3-08	X. H.		
690	PACK					12-5-08	TC		

F004 REV 5/2006

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50 LBS (plus or minus 0.50 LBS)
 3.00 LBS (plus or minus 0.75 LBS)
 4.00 LBS (plus or minus 1.00 LBS)

DATE

9/11/08

TESTER

TAE

	2.50 LBS INITIAL	2.50 LBS AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50 LBS		COMMENTS
PULL #1	290	288		294	
PULL #2	283	292		289	
PULL #3	288	281		278	
PULL #4	281	291		282	
PULL #5	283	291		283 283	
TOTAL	1425	1443		1436	
AVERAGE	285	288		287	

	3.00 LBS INITIAL	3.00 LBS AFTER 20 CYCLES		COMMENTS
PULL #1	300	353		
PULL #2	290	336		
PULL #3	321	343		
PULL #4	326	352		
PULL #5	330	316		
TOTAL	1573	1700		
AVERAGE	314	340		

	4.00 LBS INITIAL	4.00 LBS AFTER 20 CYCLES	MAX SETTING GREATER THAN 4 LBS	RESET TO 4 LBS FOR TARGET & ACCURACY
PULL #1	491	452		366
PULL #2	461	449		444
PULL #3	461	435		458
PULL #4	436	454		443
PULL #5	428	438		451
TOTAL	2277	2228		2162
AVERAGE	455	445		432

M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO
WITH BIPOD

proof of purchase



owner registration sticker



BM FORM


ORDER NO. **86470**

BARREL LENGTH **24"**

CAPACITY **6**

G6785055

UPC



GUN SERIAL # G 67850 55

OP #	OPERATION NAME	READINGS	DATE	INITIAL
420	ASSEMBLE ACTION		9-5-08	SPD
430	ASSEMBLE TO STOCK		9-6-08	TC
440	PROOF		9-6-08	TC
460	CHECK HEADSPACE		9-6-08	TC
470	DIS-ASSEMBLE ACTION		9-6-08	SPD
472	SERIALIZE BOLT HANDLE	MAGNA-FLUX	9-8-08	BSN
475	DRILL AND TAP SIGHT HOLES		9-8-08	SP
480	MAGNAFLUX BBL ACTION	OPERATOR B.M.	9-10-08	BSN
490	MAGNAFLUX BOLT		9/6/08	MR
500	ROLLMARK CALIBER		9/10/08	RT
520	GOFF BLAST BBL / REC		9/10/08	DG
542	APPLY COATINGS (BARREL ACTION)		9/5	c
545	(BOLT)			
560	RE-ASSEMBLE ACTION			
	A) CLEAN INSIDE OF BOLT ASSEMBLY		9-22-08	SP
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		9-22-08	SP
	C) INSPECT EJECTOR HOLE FOR CHAMFER		9-22-08	SP
	D) OIL FIRING PIN ASSEMBLY		9-25-08	BSN
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE 2.50 LBS +/- .5 LBS			

F004 REV 5/2006

560	BARBER - M24 0068701 F) SAFETY ON FORCE	2 LBS MIN 10 LBS MAX	<u>3.0</u>	<u>3.0</u>	<u>3.0</u>	10-7-08	LJ		
CONT.									
	G) SAFETY OFF FORCE	2 LBS MIN	<u>3.0</u>	<u>3.0</u>	<u>3.0</u>	10-7-08	LJ		
	H) TRIGGER PULL TEST AND RETAINABILITY								
	I) FIRING PIN INDENT	.020 MIN	<u>.022</u>	<u>.023</u>	<u>.023</u>	10-7-08	LJ		
	J) ASSEMBLE STOCK					9-25-08	ESN		
	K) ASSEMBLE SWIVEL STUDS					10-7-08	LJ		
	L) ATTACH FRONT AND REAR SIGHT ASSY'S								
	M) IRON SIGHT ALIGNMENT								
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER								
640 & 650	FUNCTION TEST AND TARGET		PASS	FAIL		9-26-08	TRW		
			PASS	FAIL					
	MALFUNCTION		N/A						
		CORRECTION							
	MALFUNCTION								
		CORRECTION							
	MALFUNCTION								
660	INSPECT FOR LIVE AMMO					9-26-08	LJ		
670	FINAL INSPECTION A) HEADSPACE					10-7-08	LJ		
	B) TRIGGER PULL	+/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	<u>2.45</u>	<u>2.37</u>	<u>2.41</u>	<u>2.36</u>	<u>2.39</u>	9-20-08	TL
	C) FUNCTION					10-7-08	LJ		
690	PACK					12-5-08	TL		

F004 REV 5/2006

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

1.5 LBS 1.5 LBS AFTER 50 CYCLES
 2.5 LBS 2.5 LBS AFTER 50 CYCLES
 3.00 LBS 3.00 LBS AFTER 20 CYCLES

DATE

9-20-08

TESTER

TAE

	1.5 LBS INITIAL	2.5 LBS AFTER 50 CYCLES	FINAL TEST & TO RESET 1.5 LBS		COMMENTS
PULL #1	289	273		273	
PULL #2	289	272		273	
PULL #3	286	259		273	
PULL #4	274	262		281	
PULL #5	274	262		273	
TOTAL	1412	1328		1323	
AVERAGE	282	265		274	

	3.00 LBS INITIAL	3.00 LBS AFTER 20 CYCLES		COMMENTS
PULL #1	346	353		
PULL #2	350	353		
PULL #3	337	353		
PULL #4	344	358		
PULL #5	337	361		
TOTAL	1714	1778		
AVERAGE	342	355		

	4.00 LBS INITIAL	4.00 LBS AFTER 20 CYCLES	MAX SETTING GREATER THAN 4 LBS	RESET TO 4 LBS FOR TARGET & ACCURACY
PULL #1	431	428		413
PULL #2	426	428		406
PULL #3	431	415		454
PULL #4	433	420		436
PULL #5	430	412		445
TOTAL	2151	2103		2154
AVERAGE	430	420		430