

66784712

M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO
WITH BIPOD

proof of purchase



owner registration sticker




ORDER NO. **86470**

BARREL LENGTH **24"**

CAPACITY **6**

G6784712

UPC



BM FORM

GUN SERIAL #

G 6784712

OP #	OPERATION NAME	READINGS	DATE	INITIAL
420	ASSEMBLE ACTION		9-9-08	SPD
430	ASSEMBLE TO STOCK		9-9-08	SP
440	PROOF		9-9-08	SPD
460	CHECK HEADSPACE		9-9-08	SPD
470	DIS-ASSEMBLE ACTION		9-9-08	SPD
472	SERIALIZE BOLT HANDLE		9-10-08	RT
475	DRILL AND TAP SIGHT HOLES		9-11-08	SP
480	MAGNAFLUX BBL ACTION		9-12-08	BN
490	MAGNAFLUX BOLT		9/19/08	MR
500	ROLLMARK CALIBER		9/12/08	RT
520	GOFF BLAST BBL / REC		9/10/08	OG
542	APPLY COATINGS (BARREL ACTION)		9/16	
545	(BOLT)			
560	RE-ASSEMBLE ACTION			
	A) CLEAN INSIDE OF BOLT ASSEMBLY		9-19-08	SP
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		9-19-08	SP
	C) INSPECT EJECTOR HOLE FOR CHAMFER		9-19-08	SP
	D) OIL FIRING PIN ASSEMBLY		10-8-08	Rsu
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE	2.50 LBS +/- .5 LBS		

F004 REV 5/2006

OP #	OPERATION NAME	READINGS	DATE	INITIAL
560	F) SAFETY ON FORCE 2 LBS MIN 10 LBS MAX	<u>3.5</u> <u>3.5</u> <u>4.0</u>	10-23-08	X JD
CONT.	G) SAFETY OFF FORCE 2 LBS MIN	<u>4.0</u> <u>4.5</u> <u>5.0</u>	10-23-08	X JD
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT .020 MIN	<u>.024</u> <u>.034</u> <u>-.024</u>	10-23-08	X JD
	J) ASSEMBLE STOCK		10-8-08	PSW
	K) ASSEMBLE SWIVEL STUDS		10-23-08	X JD
	L) ATTACH FRONT AND REAR SIGHT ASSY'S			
	M) IRON SIGHT ALIGNMENT			
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER			
640 & 650	FUNCTION TEST AND TARGET	<u>PASS</u> FAIL <u>PASS</u> FAIL	10-13-08	X JD
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
660	INSPECT FOR LIVE AMMO		10-13-08	TL
670	FINAL INSPECTION A) HEADSPACE		10-23-08	X JD
	B) TRIGGER PULL +/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	<u>2.64</u> <u>2.68</u> <u>2.62</u> <u>2.58</u> <u>2.62</u>	10-20-08	TL
	C) FUNCTION		10-23-08	X JD
690	PACK		12-9-08	PSW

F004 REV 5/2006

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50 LBS (plus or minus 0.50 LBS)

3.00 LBS (plus or minus 0.75 LBS)

4.00 LBS (plus or minus 1.00 LBS)

DATE

10-2-09

TESTER

TQE

	2.50 LBS INITIAL	2.50 LBS AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50 LBS		COMMENTS
PULL #1	240	253		277	
PULL #2	207	265		245	
PULL #3	227	264		211	
PULL #4	229	253		248	
PULL #5	298	228		220	
TOTAL	1201	1263		1201	
AVERAGE	240	252		240	

	3.00 LBS INITIAL	3.00 LBS AFTER 20 CYCLES		COMMENTS
PULL #1	347	310		
PULL #2	349	340		
PULL #3	342	333		
PULL #4	358	321		
PULL #5	328	339		
TOTAL	1724	1643		
AVERAGE	344	328		

	4.00 LBS INITIAL	4.00 LBS AFTER 20 CYCLES	MAX SETTING GREATER THAN 4 LBS	RESET TO 4 LBS FOR TARGET & ACCURACY
PULL #1	461	469		443
PULL #2	432	474		431
PULL #3	445	461		431
PULL #4	432	451		444
PULL #5	450	495		447
TOTAL	2220	2350		2196
AVERAGE	444	470		439