


56784980

M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)**BOLT ACTION CENTERFIRE RIFLE****24" BARREL 7.62 NATO****WITH BIPOD**

proof of purchase



owner registration sticker

**ORDER NO. 86470****BARREL LENGTH 24"****CAPACITY 6****G6784980****UPC****BM FORM**

GUN SERIAL #

G 6784980

OP #	OPERATION NAME	READINGS	DATE	INITIAL
420	ASSEMBLE ACTION		9-18-08	SP
430	ASSEMBLE TO STOCK		9-18-08	SP
440	PROOF		9-18-08	SP
460	CHECK HEADSPACE		9-18-08	SP
470	DIS-ASSEMBLE ACTION		9-18-08	SP
472	SERIALIZE BOLT HANDLE	MAGNA-FLUX SEP 22 2008 OPERATOR BH	9-19-08	SP
475	DRILL AND TAP SIGHT HOLES		9-19-08	SP
480	MAGNAFLUX BBL ACTION		9-22-08	BH
490	MAGNAFLUX BOLT		9/18/08	MR
500	ROLLMARK CALIBER		9/22/08	RT
520	GOFF BLAST BBL / REC		9/23/08	DG
542	APPLY COATINGS (BARREL ACTION)		9-23-08	SP
545	(BOLT)			
560	RE-ASSEMBLE ACTION			
	A) CLEAN INSIDE OF BOLT ASSEMBLY		9-25-08	SP
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		9-25-08	SP
	C) INSPECT EJECTOR HOLE FOR CHAMFER		9-25-08	SP
	D) OIL FIRING PIN ASSEMBLY		11-17-08	SP
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE 2.50 LBS +/- .5 LBS			

F004 REV 5/2006

OP #	OPERATION NAME	READINGS	DATE	INITIAL
560	F) SAFETY ON FORCE 2 LBS MIN 10 LBS MAX	<u>4.0</u> <u>4.0</u> <u>4.0</u>	12-30-08	P. J.
CONT.				
	G) SAFETY OFF FORCE 2 LBS MIN	<u>6.0</u> <u>6.0</u> <u>6.0</u>	12-30-08	R. J.
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT .020 MIN	<u>.025</u> <u>.025</u> <u>.025</u>	12-30-08	R. J.
	J) ASSEMBLE STOCK		11-17-08	R. J.
	K) ASSEMBLE SWIVEL STUDS		12-30-08	R. J.
	L) ATTACH FRONT AND REAR SIGHT ASSY'S			
	M) IRON SIGHT ALIGNMENT			
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER			
640 & 650	FUNCTION TEST AND TARGET	<u>PASS</u> FAIL <u>PASS</u> FAIL	12-22-08	R. J.
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
660	INSPECT FOR LIVE AMMO		12-22-08	RP
670	FINAL INSPECTION A) HEADSPACE		12-30-08	R. J.
	B) TRIGGER PULL +/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	<u>2.54</u> <u>2.47</u> <u>2.53</u> <u>2.55</u> <u>2.51</u>	12-30-08	R. J.
	C) FUNCTION		12-30-08	R. J.
690	PACK		1-8-09	TL

F004 REV 5/2006

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50 LBS (plus or minus 0.50 LBS)
 3.00 LBS (plus or minus 0.75 LBS)
 4.00 LBS (plus or minus 1.00 LBS)

DATE 11-14-08

TESTER TAE

	2.50 LBS INITIAL	2.50 LBS AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50 LBS	COMMENTS
PULL #1	224 ⁷⁵ 424	213	295	
PULL #2	221	216	296	
PULL #3	215	210	281	
PULL #4	227	226	277	
PULL #5	229	226	282	
TOTAL	1116	1091	1391	
AVERAGE	223	218	278	

	3.00 LBS INITIAL	3.00 LBS AFTER 20 CYCLES	COMMENTS
PULL #1	334	339	
PULL #2	328	352	
PULL #3	340	345	
PULL #4	341	342	
PULL #5	338	342	
TOTAL	1681	2062 1720	
AVERAGE	336	344	

	4.00 LBS INITIAL	4.00 LBS AFTER 20 CYCLES	MAX SETTING GREATER THAN 4 LBS	RESET TO 4 LBS FOR TARGET & ACCURACY
PULL #1	423	408		477
PULL #2	415	475		480
PULL #3	402	457		474
PULL #4	409	452		480
PULL #5	405	453		481
TOTAL	4082 2054	2245		4284 2392
AVERAGE	410	449		478