

66785034

M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO
WITH BIPOD

proof of purchase



owner registration sticker




ORDER NO. **86470**

BARREL LENGTH 24"

CAPACITY 6

G6785034

UPC



BM FORM

GUN SERIAL #

G 6785034

OP #	OPERATION NAME	READINGS	DATE	INITIAL
420	ASSEMBLE ACTION		9-8-08	SPD
430	ASSEMBLE TO STOCK		9-8-08	SP
440	PROOF		9-8-08	SPD
460	CHECK HEADSPACE		9-8-08	SPD
470	DIS-ASSEMBLE ACTION		9-8-08	SPD
472	SERIALIZE BOLT HANDLE	MAGNA - FLUX	9-9-08	KBL
475	DRILL AND TAP SIGHT HOLES	SEP 10 2008	9-9-08	SP
480	MAGNAFLUX BBL ACTION	OPERATOR BT	9-10-08	BT
490	MAGNAFLUX BOLT		9-10-08	MR
500	ROLLMARK CALIBER		9/16/08	RT
520	GOFF BLAST BBL / REC		9/11/08	DG
542	APPLY COATINGS (BARREL ACTION)		9/14	cr
545	(BOLT)			
560	RE-ASSEMBLE ACTION			
	A) CLEAN INSIDE OF BOLT ASSEMBLY		9-17-08	SP
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		9-17-08	SP
	C) INSPECT EJECTOR HOLE FOR CHAMFER		9-17-08	SP
	D) OIL FIRING PIN ASSEMBLY		10-11-08	PSN
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE	2.50 LBS +/- .5 LBS		

F004 REV 5/2006

OP #	OPERATION NAME	READINGS	DATE	INITIAL
560	F) SAFETY ON FORCE 2 LBS MIN 10 LBS MAX	<u>40</u> <u>35</u> <u>35</u>	12-11-08	RJ
CONT.				
	G) SAFETY OFF FORCE 2 LBS MIN	<u>40</u> <u>40</u> <u>40</u>	12-11-08	RJ
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT .020 MIN	<u>.024</u> <u>.024</u> <u>.024</u>	12-11-08	RJ
	J) ASSEMBLE STOCK		10-17-08	LSW
	K) ASSEMBLE SWIVEL STUDS		12-11-08	RJ
	L) ATTACH FRONT AND REAR SIGHT ASSY'S			
	M) IRON SIGHT ALIGNMENT			
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER			
640 & 650	FUNCTION TEST AND TARGET	<u>PASS</u> FAIL <u>PASS</u> FAIL	12-9-08	LSW
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION NA		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
660	INSPECT FOR LIVE AMMO		12/9/08	RP
670	FINAL INSPECTION A) HEADSPACE		12-11-08	RJ
	B) TRIGGER PULL +/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	<u>2.49</u> <u>2.45</u> <u>2.50</u> <u>2.36</u> <u>2.45</u>	12-11-08	LSW
	C) FUNCTION		12-11-08	RJ
690	PACK		1/6/09	FM

F004 REV 5/2006

BARBER - M24 0070609

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50 LBS (plus or minus 0.50 LBS)
3.00 LBS (plus or minus 0.75 LBS)
4.00 LBS (plus or minus 1.00 LBS)

DATE 10-15-08

TESTER TAE

	2.50 LBS INITIAL	2.50 LBS AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50 LBS		COMMENTS
PULL #1	268	270		278	
PULL #2	271	250		223	
PULL #3	284	266		205	
PULL #4	276	240		283	
PULL #5	275	245		209	
TOTAL	1374	1271		1198	
AVERAGE	274	254		239	

	3.00 LBS INITIAL	3.00 LBS AFTER 20 CYCLES		COMMENTS
PULL #1	374	350		
PULL #2	356	302		
PULL #3	313	308		
PULL #4	333	303		
PULL #5	307	307		
TOTAL	1683	1570		
AVERAGE	336	314		

	4.00 LBS INITIAL	4.00 LBS AFTER 20 CYCLES	MAX SETTING GREATER THAN 4 LBS	RESET TO 4 LBS FOR TARGET & ACCURACY
PULL #1	446	417		476
PULL #2	441	422		406
PULL #3	440	422		460
PULL #4	441	418		473
PULL #5	482	413		455
TOTAL	2250	2092		2270
AVERAGE	450	418		454

EVALUATION RECORD - M24 TRIGGER ASSEMBLY

F005 REV 5/2006

**CONFIDENTIAL-SUBJECT TO PROTECTIVE ORDER
KINZER V. REMINGTON**

BARBER - M24 0070609