

6678 9960

M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)

BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO
WITH BIPOD

proof of purchase



owner registration sticker



BM FORM


ORDER NO. **86470**

BARREL LENGTH **24"**

CAPACITY **6**

G6789960

UPC



GUN SERIAL # G 678 9960

OP #	OPERATION NAME	READINGS	DATE	INITIAL
420	ASSEMBLE ACTION		12-1-08	SP
430	ASSEMBLE TO STOCK		12-1-08	SP
440	PROOF		12-1-08	SP
460	CHECK HEADSPACE		12-1-08	SP
470	DIS-ASSEMBLE ACTION		12-1-08	SP
472	SERIALIZE BOLT HANDLE	MAGNA - FLUX	12-2-08	RT
475	DRILL AND TAP SIGHT HOLES	DEC 09 2008	12-2-08	SP
480	MAGNAFLUX BBL ACTION	OPERATOR (X)	12/9/08	
490	MAGNAFLUX BOLT		12/9/08	MR
500	ROLLMARK CALIBER		12/9/08	RT
520	GOFF BLAST BBL / REC		12-11-08	DG
542	APPLY COATINGS (BARREL ACTION)		12/6	
545	(BOLT)			
560	RE-ASSEMBLE ACTION			
	A) CLEAN INSIDE OF BOLT ASSEMBLY		12-17-08	SP
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		12-17-08	SP
	C) INSPECT EJECTOR HOLE FOR CHAMFER		12-17-08	SP
	D) OIL FIRING PIN ASSEMBLY		1-6-09	RT
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE	2.50 LBS +/- .5 LBS		

F004 REV 5/2006

OP #	OP	BARBER - M24 6071564	READINGS	DATE	INITIAL
560	F) SAFETY ON FORCE	2 LBS MIN 10 LBS MAX	<u>40</u> <u>40</u> <u>40</u>	1-14-09	L.N.
CONT.	G) SAFETY OFF FORCE	2 LBS MIN	<u>60</u> <u>60</u> <u>60</u>	1-14-09	L.N.
	H) TRIGGER PULL TEST AND RETAINABILITY				
	I) FIRING PIN INDENT	.020 MIN	<u>.024</u> <u>.024</u> <u>.024</u>	1-14-09	L.N.
	J) ASSEMBLE STOCK			1-16-09	RTZ
	K) ASSEMBLE SWIVEL STUDS			1-14-09	L.N.
	L) ATTACH FRONT AND REAR SIGHT ASSY'S				
	M) IRON SIGHT ALIGNMENT				
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER				
640 & 650	FUNCTION TEST AND TARGET		<u>PASS</u> FAIL <u>PASS</u> FAIL	1-12-09	L.N.
	MALFUNCTION		CORRECTION		
	MALFUNCTION		CORRECTION		
	MALFUNCTION		CORRECTION		
	MALFUNCTION		CORRECTION		
660	INSPECT FOR LIVE AMMO			1-12-09	RP
670	FINAL INSPECTION A) HEADSPACE			1-14-09	L.N.
	B) TRIGGER PULL	+/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	<u>248</u> <u>246</u> <u>230</u> <u>238</u> <u>240</u>	1-13-09	L.N.
	C) FUNCTION			1-14-09	L.N.
690	PACK			1/16/09	Fm

F004 REV 5/2006

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50 LBS (plus or minus 0.50 LBS)

3.00 LBS (plus or minus 0.75 LBS)

4.00 LBS (plus or minus 1.00 LBS)

DATE

11-18-08

TESTER

TAC

	2.50 LBS INITIAL	2.50 LBS AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50 LBS		COMMENTS
PULL #1	263	233		274	
PULL #2	254	229		274	
PULL #3	264	226		283	
PULL #4	257	238		285	
PULL #5	262	230		283	
TOTAL	1300	1156		1399	
AVERAGE	260	231		279	

	3.00 LBS INITIAL	3.00 LBS AFTER 20 CYCLES		COMMENTS
PULL #1	316	328		
PULL #2	317	328		
PULL #3	322	335		
PULL #4	322	337		
PULL #5	322	338		
TOTAL	1599	1666		
AVERAGE	319	333		

	4.00 LBS INITIAL	4.00 LBS AFTER 20 CYCLES	MAX SETTING GREATER THAN 4 LBS	RESET TO 4 LBS. FOR TARGET & ACCURACY
PULL #1	419	431		471
PULL #2	414	442		464
PULL #3	412	433		474
PULL #4	417	440		472
PULL #5	417	437		472
TOTAL	2079	2183		2353
AVERAGE	415	436		470