

6678 9977

M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)

BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO
WITH BIPOD

proof of purchase



owner registration sticker



BM FORM


ORDER NO. **86470**

BARREL LENGTH 24"

CAPACITY 6

G6789977

UPC



INSPECTION CHECKLIST-NEW GUNS

GUN SERIAL #

G 678 9977

OP #	OPERATION NAME	READINGS	DATE	INITIAL
420	ASSEMBLE ACTION		12-1-08	SP
430	ASSEMBLE TO STOCK		12-1-08	SP
440	PROOF		12-1-08	SP
460	CHECK HEADSPACE		12-1-08	SP
470	DIS-ASSEMBLE ACTION		12-1-08	SP
472	SERIALIZE BOLT HANDLE	MAGNA-FLUX	12-2-08	RSW
475	DRILL AND TAP SIGHT HOLES	2008	12-2-08	SP
480	MAGNAFLUX BBL ACTION	OPERATOR	12/9/08	RT
490	MAGNAFLUX BOLT		12/9/08	RT
500	ROLLMARK CALIBER		12/9/08	RT
520	GOFF BLAST BBL / REC		12/9/08	DS
542	APPLY COATINGS (BARREL ACTION)		12/1/08	
545	(BOLT)			
560	RE-ASSEMBLE ACTION			
	A) CLEAN INSIDE OF BOLT ASSEMBLY		12-17-08	SP
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		12-17-08	SP
	C) INSPECT EJECTOR HOLE FOR CHAMFER		12-17-08	SP
	D) OIL FIRING PIN ASSEMBLY		1-5-09	RT
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE	2.50 LBS +/- .5 LBS		

F004 REV 5/2006

OP #	OPERATION NAME	READINGS	DATE	INITIAL
560	F) SAFETY ON FORCE 2 LBS MIN 10 LBS MAX	<u>40</u> <u>40</u> <u>40</u>	1-12-09	LH
CONT.	G) SAFETY OFF FORCE 2 LBS MIN	<u>50</u> <u>50</u> <u>50</u>	1-12-09	LH
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT .020 MIN	<u>.024</u> <u>.024</u> <u>.024</u>	1-12-09	LH
	J) ASSEMBLE STOCK		1-5-08	RTZ
	K) ASSEMBLE SWIVEL STUDS		1-12-09	LH
	L) ATTACH FRONT AND REAR SIGHT ASSY'S			
	M) IRON SIGHT ALIGNMENT			
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER			
640 & 650	FUNCTION TEST AND TARGET	<u>PASS</u> FAIL <u>PASS</u> FAIL	1-7-09	L.P.D.
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
660	INSPECT FOR LIVE AMMO		1-7-09	RP
670	FINAL INSPECTION A) HEADSPACE		1-12-09	LH
	B) TRIGGER PULL +/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	<u>2.32</u> <u>2.04</u> <u>2.12</u> <u>2.03</u> <u>2.20</u>	1-8-09	Law
	C) FUNCTION		1-12-09	LH
690	PACK		1/19/09	Fm

F004 REV 5/2006

BARBER - M24 0071748

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50 LBS (plus or minus 0.50 LBS)
3.00 LBS (plus or minus 0.75 LBS)
4.00 LBS (plus or minus 1.00 LBS)

DATE

11/19/08

TESTER

TAE

	2.50 LBS INITIAL	2.50 LBS AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50 LBS		COMMENTS
PULL #1	224	230		276	
PULL #2	226	240		273	
PULL #3	219	228		271	
PULL #4	215	222		285	
PULL #5	231	222		281	
TOTAL	1113	1142		1386	
AVERAGE	222	228		277	

	3.00 LBS INITIAL	3.00 LBS AFTER 20 CYCLES		COMMENTS
PULL #1	330	324		
PULL #2	320	323		
PULL #3	323	316		
PULL #4	319	319		
PULL #5	318	322		
TOTAL	1608	1604		
AVERAGE	321	320		

	4.00 LBS INITIAL	4.00 LBS AFTER 20 CYCLES	MAX SETTING GREATER THAN 4 LBS	RESET TO 4 LBS FOR TARGET & ACCURACY
PULL #1	425	439		429
PULL #2	406	413		426
PULL #3	451	423		420
PULL #4	444	429		420
PULL #5	437	428		421
TOTAL	2163	2128		2116
AVERAGE	432	425		423