

9679 4516

M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO

- INSTRUCTION BOOK 3518

proof of purchase



owner registration sticker




ORDER NO. **25716**

BARREL LENGTH **24"**

CAPACITY **6**

G6794516

UPC



BM FORM

GUN SERIAL #

G 6794516

OP #	OPERATION NAME	READINGS	DATE	INITIAL
420	ASSEMBLE ACTION		11-3-08	SPD
430	ASSEMBLE TO STOCK		11-3-08	SP
440	PROOF		11-3-08	SPD
460	CHECK HEADSPACE		11-3-08	SPD
470	DIS-ASSEMBLE ACTION		11-3-08	SPD
472	SERIALIZE BOLT HANDLE		11-4-08	RTZ
475	DRILL AND TAP SIGHT HOLES		11-4-08	SP
480	MAGNAFLUX BBL ACTION	OPERATOR 	11/6/08	
490	MAGNAFLUX BOLT		11/3/08	MR
500	ROLLMARK CALIBER		11/6/08	RT
520	GOFF BLAST BBL / REC		11/6/08	DS
542	APPLY COATINGS (BARREL ACTION)		11/15	
545	(BOLT)			
560	RE-ASSEMBLE ACTION			
	A) CLEAN INSIDE OF BOLT ASSEMBLY		11-17-08	SP
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		11-17-08	SP
	C) INSPECT EJECTOR HOLE FOR CHAMFER		11-17-08	SP
	D) OIL FIRING PIN ASSEMBLY		11-19-08	Rgn
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE 2.50 LBS +/- .5 LBS			

F004 REV 5/2006

OP #	OPERATION NAME	READINGS	DATE	INITIAL
560	F) SAFETY ON FORCE 2 LBS MIN 10 LBS MAX	<u>40</u> <u>40</u> <u>40</u>	2-11-09	LD
CONT.	G) SAFETY OFF FORCE 2 LBS MIN	<u>50</u> <u>50</u> <u>50</u>	2-11-09	LD
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT .020 MIN	<u>.025</u> <u>.025</u> <u>.025</u>	2-11-09	LD
	J) ASSEMBLE STOCK		11-19-08	BN
	K) ASSEMBLE SWIVEL STUDS		2-11-09	LD
	L) ATTACH FRONT AND REAR SIGHT ASSY'S			
	M) IRON SIGHT ALIGNMENT			
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER			
640 & 650	FUNCTION TEST AND TARGET	<u>PASS</u> FAIL <u>PASS</u> FAIL	2-2-09 11-19-08	TC TC
	MALFUNCTION TOG	CORRECTION	11-20-08	TC
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
660	INSPECT FOR LIVE AMMO		11-19-08	LD
670	FINAL INSPECTION A) HEADSPACE		2-11-09	LD
	B) TRIGGER PULL +/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	<u>2.81</u> <u>2.83</u> <u>2.61</u> <u>2.64</u> <u>2.55</u>	2-4-09	WV
	C) FUNCTION		2-11-09	LD
690	PACK		3/17/09	FM

F004 REV 5/2006

BARBER - M24 0072462

 AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50 LBS (plus or minus 0.50 LBS)

3.00 LBS (plus or minus 0.75 LBS)

4.00 LBS (plus or minus 1.00 LBS)

DATE

11-13-08

TESTER

TAE

	2.50 LBS INITIAL	2.50 LBS AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50 LBS	COMMENTS
PULL #1	255	231	225	
PULL #2	254	227	233	
PULL #3	250	237	227	
PULL #4	249	245	235	
PULL #5	241	248	229	
TOTAL	1249	1188	1149	
AVERAGE	249	237	229	

	3.00 LBS INITIAL	3.00 LBS AFTER 20 CYCLES	COMMENTS
PULL #1	353	341	
PULL #2	358	327	
PULL #3	351	321	
PULL #4	338	313	
PULL #5	345	327	
TOTAL	1743	1629	
AVERAGE	348	325	

	4.00 LBS INITIAL	4.00 LBS AFTER 20 CYCLES	MAX SETTING GREATER THAN 4 LBS	RESET TO 4 LBS FOR TARGET & ACCURACY
PULL #1	411	435		403
PULL #2	431	435		410
PULL #3	426	439		404
PULL #4	430	431		405
PULL #5	433	435		407
TOTAL	3399	2029		2029
AVERAGE	679	426	435	405